


# Map tiles

Patrick Brown



February 26, 2014

The following are some examples of maps produced with  
`mymap=openmap(x, path="something")`

```
1 plot (openmap(x,path=" osm "))
```



```
2 plot (openmap(x,path=" osm-no-labels "))
```




```
3 plot (openmap(x,path=" osm-transport "))
```



```
4 plot (openmap(x,path=" bw-mapnik "))
```



```
5 plot RGB (openmap(x,path=" mapquest "))
```



```
6 plot RGB (openmap(x,path=" mapquest-sat "))
```



```
7 plot (openmap(x,path=" landscape "))
```



```
8 plot (openmap(x,path=" opentopomap "))
```


opentopomap has  
not currently  
evolved



9 `plot (openmap(x,path=" maptoolkit "))`



10 `plot (openmap(x,path=" waze "))`



11 `plot (openmap(x,path=" humanitarian "))`



```
12 plot (openmap(x,path=" parking-bw "))
```



```
13 plot (openmap(x,path=" osm-locale-de "))
```



```
14 plot (openmap(x,path=" bw-noicons "))
```





```
18 plot (openmap(x,path=" osm-labels-it "))
```




```
19 plot (openmap(x,path=" osm-labels-es "))
```



```
20 plot (openmap(x,path=" osm-labels-ru "))
```



```
21 plot (openmap(x,path=" stamen-toner "))
```



```
22 plot RGB (openmap(x,path=" stamen-watercolor "))
```

