

# Package ‘CDMConnector’

October 31, 2023

**Title** Connect to an OMOP Common Data Model

**Version** 1.2.0

**Description** Provides tools for working with observational health data in the Observational Medical Outcomes Partnership (OMOP) Common Data Model format with a pipe friendly syntax.  
Common data model database table references are stored in a single compound object along with metadata.

**License** Apache License (>= 2)

**URL** <https://darwin-eu.github.io/CDMConnector/>,  
<https://github.com/darwin-eu/CDMConnector>

**BugReports** <https://github.com/darwin-eu/CDMConnector/issues>

**Encoding** UTF-8

**RoxygenNote** 7.2.3

**Depends** R (>= 4.0)

**Imports** dplyr, DBI (>= 0.3.0), checkmate, dbplyr (>= 2.4.0), cli, purrr, rlang, tidyselect, readr, glue, waldo, methods, withr, lifecycle, jsonlite, stringr, stringi, fs, generics, tidyr, pool

**Suggests** arrow, SqlRender, rJava, covr, knitr, rmarkdown, duckdb, RSQLite, RPostgres, odbc, ggplot2, bigrquery, testthat (>= 3.0.0), DatabaseConnector, lubridate, tibble, zeallot

**Enhances** CirceR, Capr

**Config/testthat/edition** 3

**Config/testthat/parallel** true

**VignetteBuilder** knitr

**Additional\_repositories** <https://OHDSI.github.io/drat>

**NeedsCompilation** no

**Author** Adam Black [aut, cre] (<<https://orcid.org/0000-0001-5576-8701>>),  
Artem Gorbachev [aut],  
Edward Burn [aut],  
Marti Catala Sabate [aut]

**Maintainer** Adam Black <black@ohdsi.org>

**Repository** CRAN

**Date/Publication** 2023-10-31 16:40:17 UTC

## R topics documented:

appendPermanent . . . . .	3
asDate . . . . .	4
assert_tables . . . . .	5
assert_write_schema . . . . .	6
cdmDisconnect . . . . .	6
cdmFlatten . . . . .	7
cdmName . . . . .	8
cdmSample . . . . .	9
cdmSubset . . . . .	10
cdmSubsetCohort . . . . .	11
cdm_from_con . . . . .	13
cdm_from_files . . . . .	14
cdm_select_tbl . . . . .	15
cohortAttrition . . . . .	16
cohortCount . . . . .	16
cohortSet . . . . .	17
cohort_erafy . . . . .	17
cohort_union . . . . .	18
collect.cdm_reference . . . . .	18
computeQuery . . . . .	19
copy_cdm_to . . . . .	20
dateadd . . . . .	21
datediff . . . . .	22
datepart . . . . .	22
dbms . . . . .	23
downloadEunomiaData . . . . .	24
dropTable . . . . .	25
eunomiaDir . . . . .	26
eunomia_is_available . . . . .	27
exampleDatasets . . . . .	28
generateCohortSet . . . . .	28
generateConceptCohortSet . . . . .	30
inSchema . . . . .	31
intersect_cohorts . . . . .	32
list_tables . . . . .	32
new_generated_cohort_set . . . . .	33
print.cdm_reference . . . . .	35
read_cohort_set . . . . .	36
recordCohortAttrition . . . . .	37
snapshot . . . . .	38
stow . . . . .	38

summarise_quantile . . . . .	39
tbl_group . . . . .	40
union_cohorts . . . . .	41
uniqueTableName . . . . .	42
validate_cdm . . . . .	42
version . . . . .	43
[.cdm_reference . . . . .	44
[[.cdm_reference . . . . .	44
\$.cdm_reference . . . . .	45

<b>Index</b>	<b>46</b>
--------------	-----------

---

appendPermanent	<i>Run a dplyr query and add the result set to an existing</i>
-----------------	--

---

## Description

Run a dplyr query and add the result set to an existing

## Usage

```
appendPermanent(x, name, schema = NULL)
```

```
append_permanent(x, name, schema = NULL)
```

## Arguments

x	A dplyr query
name	Name of the table to be appended. If it does not already exist it will be created.
schema	Schema where the table exists. Can be a length 1 or 2 vector. (e.g. schema = "my_schema", schema = c("my_schema", "dbo"))

## Value

A dplyr reference to the newly created table

## Examples

```
## Not run:
library(CDMConnector)

con <- DBI::dbConnect(duckdb::duckdb(), dbdir = eunomia_dir())
concept <- dplyr::tbl(con, "concept")

# create a table
rxnorm_count <- concept %>%
  dplyr::filter(domain_id == "Drug") %>%
  dplyr::mutate(isRxnorm = (vocabulary_id == "RxNorm")) %>%
  dplyr::count(domain_id, isRxnorm) %>%
```

```

computeQuery("rxnorm_count")

# append to an existing table
rxnorm_count <- concept %>%
  dplyr::filter(domain_id == "Procedure") %>%
  dplyr::mutate(isRxnorm = (vocabulary_id == "RxNorm")) %>%
  dplyr::count(domain_id, isRxnorm) %>%
  appendPermanent("rxnorm_count")

DBI::dbDisconnect(con, shutdown = TRUE)

## End(Not run)

```

asDate

*as.Date dbplyr translation wrapper***Description**

This is a workaround for using `as.Date` inside `dplyr` verbs against a database backend. This function should only be used inside `dplyr` verbs where the first argument is a database table reference. `asDate` must be unquoted with `!!` inside `dplyr` verbs (see example).

**Usage**

```

asDate(x)

as_date(x)

```

**Arguments**

`x` an R expression

**Examples**

```

## Not run:
con <- DBI::dbConnect(odbc::odbc(), "Oracle")
date_tbl <- dplyr::copy_to(con,
  data.frame(y = 2000L, m = 10L, d = 10L),
  name = "tmp",
  temporary = TRUE)

df <- date_tbl %>%
  dplyr::mutate(date_from_parts = !!asDate(paste0(
    .data$y, "/",
    .data$m, "/",
    .data$d
  ))) %>%
  collect()

## End(Not run)

```

---

assert_tables	<i>Assert that tables exist in a cdm object</i>
---------------	---

---

### Description

A cdm object is a list of references to a subset of tables in the OMOP Common Data Model. If you write a function that accepts a cdm object as a parameter `assert_tables/assertTables` will help you check that the tables you need are in the cdm object, have the correct columns/fields, and (optionally) are not empty.

### Usage

```
assert_tables(cdm, tables, empty.ok = FALSE, add = NULL)
```

```
assertTables(cdm, tables, empty.ok = FALSE, add = NULL)
```

### Arguments

cdm	A cdm object
tables	A character vector of table names to check.
empty.ok	Should an empty table (0 rows) be considered an error? TRUE or FALSE (default)
add	An optional <code>AssertCollection</code> created by <code>checkmate::makeAssertCollection()</code> that errors should be added to.

### Value

Invisibly returns the cdm object

### Examples

```
## Not run:
# Use assertTables inside a function to check that tables exist
countDrugsByGender <- function(cdm) {
  assertTables(cdm, tables = c("person", "drug_era"), empty.ok = FALSE)

  cdm$person %>%
    dplyr::inner_join(cdm$drug_era, by = "person_id") %>%
    dplyr::count(.data$gender_concept_id, .data$drug_concept_id) %>%
    dplyr::collect()
}

library(CDMConnector)
con <- DBI::dbConnect(duckdb::duckdb(), dbdir = eunomia_dir())
cdm <- cdm_from_con(con)

countDrugsByGender(cdm)
```

```
DBI::dbDisconnect(con, shutdown = TRUE)

## End(Not run)
```

---

```
assert_write_schema    Assert that cdm has a writable schema
```

---

### Description

A cdm object can optionally contain a single schema in a database with write access. `assert_write_schema` checks that the cdm contains the "write\_schema" attribute and tests that local dataframes can be written to tables in this schema.

### Usage

```
assert_write_schema(cdm, add = NULL)

assertWriteSchema(cdm, add = NULL)
```

### Arguments

cdm	A cdm object
add	An optional <code>AssertCollection</code> created by <code>checkmate::makeAssertCollection()</code> that errors should be added to.

### Value

Invisibly returns the cdm object

---

```
cdmDisconnect    Disconnect the connection of the cdm object
```

---

### Description

Disconnect the connection of the cdm object

### Usage

```
cdmDisconnect(cdm)

cdm_disconnect(cdm)
```

### Arguments

cdm	cdm reference
-----	---------------

---

cdmFlatten	<i>Flatten a cdm into a single observation table</i>
------------	--

---

## Description

This experimental function transforms the OMOP CDM into a single observation table. This is only recommended for use with a filtered CDM or a cdm that is small in size.

## Usage

```
cdmFlatten(
  cdm,
  domain = c("condition", "drug", "procedure"),
  includeConceptName = TRUE
)

cdm_flatten(
  cdm,
  domain = c("condition", "drug", "procedure"),
  include_concept_name = TRUE
)
```

## Arguments

cdm	A cdm_reference object
domain	Domains to include. Must be a subset of "condition", "drug", "procedure", "measurement", "visit", "death", "observation".
include_concept_name, includeConceptName	Should concept_name and type_concept_name be include in the output table? TRUE (default) or FALSE

## Details

**[Experimental]**

## Value

A lazy query that when evaluated will result in a single cdm table

## Examples

```
## Not run:
library(CDMConnector)
library(dplyr, warn.conflicts = FALSE)

con <- DBI::dbConnect(duckdb::duckdb(), eunomia_dir())

cdm <- cdm_from_con(con, cdm_schema = "main")
```

```

all_observations <- cdmSubset(cdm, personId = c(2, 18, 42)) %>%
  cdmFlatten() %>%
  collect()

all_observations
#> # A tibble: 213 × 8
#>   person_id observation_ start_date end_date type_ domain obser. type_
#>   <dbl>         <dbl> <date>   <date>   <dbl> <chr> <chr> <chr>
#> 1             2     40213201 1986-09-09 1986-09-09 5.81e5 drug  pneumo <NA>
#> 2             18     4116491 1997-11-09 1998-01-09 3.20e4 condi Escher <NA>
#> 3             18     40213227 2017-01-04 2017-01-04 5.81e5 drug  tetanu <NA>
#> 4             42     4156265 1974-06-13 1974-06-27 3.20e4 condi Facial <NA>
#> 5             18     40213160 1966-02-23 1966-02-23 5.81e5 drug  poliov <NA>
#> 6             42     4198190 1933-10-29 1933-10-29 3.80e7 proce Append <NA>
#> 7             2      4109685 1952-07-13 1952-07-27 3.20e4 condi Lacera <NA>
#> 8             18     40213260 2017-01-04 2017-01-04 5.81e5 drug  zoster <NA>
#> 9             42     4151422 1985-02-03 1985-02-03 3.80e7 proce Sputum <NA>
#> 10            2      4163872 1993-03-29 1993-03-29 3.80e7 proce Plain <NA>
#> # ... with 203 more rows, and abbreviated variable names observation_concept_id,
#> #   type_concept_id, observation_concept_name, type_concept_name

DBI::dbDisconnect(con, shutdown = TRUE)

## End(Not run)

```

---

cdmName

*Get the CDM name*

---

## Description

Extract the CDM name attribute from a cdm\_reference object

## Usage

```
cdmName(cdm)
```

```
cdm_name(cdm)
```

## Arguments

cdm                    A cdm object

## Value

The name of the CDM as a character string



## Examples

```
## Not run:
library(CDMConnector)
con <- DBI::dbConnect(duckdb::duckdb(), eunomia_dir())
cdm <- cdm_from_con(con, "main")
cdmName(cdm)
#> [1] "Synthea synthetic health database"

cdm <- cdm_from_con(con, "main", cdm_name = "Example CDM")
cdmName(cdm)
#> [1] "Example CDM"

DBI::dbDisconnect(con, shutdown = TRUE)

## End(Not run)
```

---

cdmSample

*Subset a cdm object to a random sample of individuals*

---

## Description

cdmSample takes a cdm object and returns a new cdm that includes only a random sample of persons in the cdm. Only person\_ids in both the person table and observation\_period table will be considered.

## Usage

```
cdmSample(cdm, n)
```

```
cdm_sample(cdm, n)
```

## Arguments

cdm	A cdm_reference object
n	Number of persons to include in the cdm

## Details

**[Experimental]**

## Value

A modified cdm\_reference object where all clinical tables are lazy queries pointing to subset

**Examples**

```
## Not run:
library(CDMConnector)
library(dplyr, warn.conflicts = FALSE)

con <- DBI::dbConnect(duckdb::duckdb(), eunomia_dir())

cdm <- cdm_from_con(con, cdm_schema = "main")

cdmSampled <- cdmSample(cdm, n = 2)

cdmSampled$person %>%
  select(person_id)
#> # Source:   SQL [2 x 1]
#> # Database: DuckDB 0.6.1
#>   person_id
#>       <dbl>
#> 1         155
#> 2        3422

DBI::dbDisconnect(con, shutdown = TRUE)

## End(Not run)
```

---

cdmSubset

*Subset a cdm object to a set of persons*


---

**Description**

cdmSubset takes a cdm object and a list of person IDs as input. It returns a new cdm that includes data only for persons matching the provided person IDs. Generated cohorts in the cdm will also be subset to the IDs provided.

**Usage**

```
cdmSubset(cdm, personId)

cdm_subset(cdm, person_id)
```

**Arguments**

```
cdm          A cdm_reference object
person_id, personId  A numeric vector of person IDs to include in the cdm
```

**Details**

**[Experimental]**

**Value**

A modified `cdm_reference` object where all clinical tables are lazy queries pointing to subset

**Examples**

```
## Not run:
library(CDMConnector)
library(dplyr, warn.conflicts = FALSE)

con <- DBI::dbConnect(duckdb::duckdb(), eunomia_dir())

cdm <- cdm_from_con(con, cdm_schema = "main")

cdm2 <- cdmSubset(cdm, personId = c(2, 18, 42))

cdm2$person %>%
  select(1:3)
#> # Source:   SQL [3 x 3]
#> # Database: DuckDB 0.6.1
#>   person_id gender_concept_id year_of_birth
#>   <dbl>         <dbl>         <dbl>
#> 1         2             8532         1920
#> 2        18             8532         1965
#> 3         42             8532         1909

DBI::dbDisconnect(con, shutdown = TRUE)

## End(Not run)
```

---

cdmSubsetCohort

*Subset a cdm to the individuals in one or more cohorts*

---

**Description**

`cdmSubset` will return a new `cdm` object that contains lazy queries pointing to each of the `cdm` tables but subset to individuals in a generated cohort. Since the `cdm` tables are lazy queries, the subset operation will only be done when the tables are used. `computeQuery` can be used to run the SQL used to subset a `cdm` table and store it as a new table in the database.

**Usage**

```
cdmSubsetCohort(cdm, cohortTable = "cohort", cohortId = NULL, verbose = FALSE)

cdm_subset_cohort(
  cdm,
  cohort_table = "cohort",
  cohort_id = NULL,
  verbose = FALSE
)
```

**Arguments**

cdm                    A cdm\_reference object  
 cohortTable, cohort\_table                    The name of a cohort table in the cdm reference  
 cohortId, cohort\_id                    IDs of the cohorts that we want to subset from the cohort table. If NULL (default) all cohorts in cohort table are considered.  
 verbose                Should subset messages be printed? TRUE or FALSE (default)

**Details****[Experimental]****Value**

A modified cdm\_reference with all clinical tables subset to just the persons in the selected cohorts.

**Examples**

```
## Not run:
library(CDMConnector)
library(dplyr, warn.conflicts = FALSE)

con <- DBI::dbConnect(duckdb::duckdb(), eunomia_dir())

cdm <- cdm_from_con(con, cdm_schema = "main", write_schema = "main")

# generate a cohort
path <- system.file("cohorts2", mustWork = TRUE, package = "CDMConnector")

cohortSet <- readCohortSet(path) %>%
  filter(cohort_name == "GIBleed_male")

# subset cdm to persons in the generated cohort
cdm <- generateCohortSet(cdm, cohortSet = cohortSet, name = "gibleed")

cdmGiBleed <- cdmSubsetCohort(cdm, cohortTable = "gibleed")

cdmGiBleed$person %>%
  tally()
#> # Source:   SQL [1 x 1]
#> # Database: DuckDB 0.6.1
#>       n
#>   <dbl>
#> 1   237

cdm$person %>%
  tally()
#> # Source:   SQL [1 x 1]
#> # Database: DuckDB 0.6.1
#>       n
```

```
#> <dbl>
#> 1 2694

DBI::dbDisconnect(con, shutdown = TRUE)

## End(Not run)
```

---

cdm_from_con	<i>Create a CDM reference object from a database connection</i>
--------------	---

---

## Description

Create a CDM reference object from a database connection

## Usage

```
cdm_from_con(
  con,
  cdm_schema = NULL,
  write_schema = NULL,
  cohort_tables = NULL,
  cdm_version = "5.3",
  cdm_name = NULL
)

cdmFromCon(
  con,
  cdmSchema = NULL,
  writeSchema = NULL,
  cohortTables = NULL,
  cdmVersion = "5.3",
  cdmName = NULL
)
```

## Arguments

con	A DBI database connection to a database where an OMOP CDM v5.4 or v5.3 instance is located.
cdm_schema, cdmSchema	The schema where the OMOP CDM tables are located. Defaults to NULL.
write_schema, writeSchema	An optional schema in the CDM database that the user has write access to.
cohort_tables, cohortTables	A character vector listing the cohort table names to be included in the CDM object.

cdm\_version, cdmVersion

The version of the OMOP CDM: "5.3" (default), "5.4", "auto". "auto" attempts to automatically determine the cdm version using heuristics. Cohort tables must be in the write\_schema.

cdm\_name, cdmName

The name of the CDM. If NULL (default) the cdm\_source\_name . field in the CDM\_SOURCE table will be used.

### Value

A list of dplyr database table references pointing to CDM tables

---

cdm_from_files	<i>Create a CDM reference from a folder containing parquet, csv, or feather files</i>
----------------	---

---

### Description

Create a CDM reference from a folder containing parquet, csv, or feather files

### Usage

```
cdm_from_files(
  path,
  format = "auto",
  cdm_version = "5.3",
  cdm_name = NULL,
  as_data_frame = TRUE
)
```

```
cdmFromFiles(
  path,
  format = "auto",
  cdmVersion = "5.3",
  cdmName = NULL,
  asDataFrame = TRUE
)
```

### Arguments

path            A folder where an OMOP CDM v5.4 instance is located.

format            What is the file format to be read in? Must be "auto" (default), "parquet", "csv", "feather".

cdm\_version, cdmVersion            The version of the cdm (5.3 or 5.4)

cdm\_name, cdmName            A name to use for the cdm.

as\_data\_frame, asDataFrame  
 TRUE (default) will read files into R as dataframes. FALSE will read files into R as Arrow Datasets.

### Value

A list of dplyr database table references pointing to CDM tables

---

cdm_select_tbl	<i>Select a subset of tables in a cdm reference object</i>
----------------	--

---

### Description

This function uses syntax similar to `dplyr::select` and can be used to subset a cdm reference object to a specific tables

### Usage

```
cdm_select_tbl(cdm, ...)
```

### Arguments

cdm	A cdm reference object created by <code>cdm_from_con</code>
...	One or more table names of the tables of the cdm object. <code>tidyselect</code> is supported, see <code>dplyr::select()</code> for details on the semantics.

### Value

A cdm reference object containing the selected tables

### Examples

```
## Not run:
con <- DBI::dbConnect(duckdb::duckdb(), dbdir = eunomia_dir())

cdm <- cdm_from_con(con, "main")

cdm_select_tbl(cdm, person)
cdm_select_tbl(cdm, person, observation_period)
cdm_select_tbl(cdm, tbl_group("vocab"))
cdm_select_tbl(cdm, "person")

DBI::dbDisconnect(con)

## End(Not run)
```

---

cohortAttrition	<i>Get attrition table from a GeneratedCohortSet object</i>
-----------------	---

---

**Description**

Get attrition table from a GeneratedCohortSet object

**Usage**

cohortAttrition(x)

cohort\_attrition(x)

**Arguments**

x                    A generatedCohortSet object

---

cohortCount	<i>Get cohort counts from a GeneratedCohortSet object</i>
-------------	---

---

**Description**

Get cohort counts from a GeneratedCohortSet object

**Usage**

cohortCount(x)

cohort\_count(x)

**Arguments**

x                    A generatedCohortSet object



---

cohortSet	<i>Get cohort settings from a GeneratedCohortSet object</i>
-----------	---

---

**Description**

Get cohort settings from a GeneratedCohortSet object

**Usage**

cohortSet(x)

cohort\_set(x)

**Arguments**

x	A generatedCohortSet object
---	-----------------------------

---

cohort_erafy	<i>Collapse cohort records within a certain number of days</i>
--------------	--

---

**Description**

Collapse cohort records within a certain number of days

**Usage**

cohort\_erafy(x, gap)

cohortErafy(x, gap)

**Arguments**

x	A generated cohort set
gap	When two cohort records are 'gap' days apart or less the periods will be collapsed into a single record

**Value**

A lazy query on a generated cohort set

---

cohort_union	<i>Union all cohorts in a cohort set with cohorts in a second cohort set</i>
--------------	--

---

**Description**

Union all cohorts in a cohort set with cohorts in a second cohort set

**Usage**

```
cohort_union(x, y)
```

```
cohortUnion(x, y)
```

**Arguments**

x A tbl reference to a cohort table with one or more generated cohorts

y A tbl reference to a cohort table with one generated cohort

**Value**

A lazy query that when executed will resolve to a new cohort table with one the same cohort\_definitions\_ids in x resulting from the union of all cohorts in x with the single cohort in y cohort table

---

collect.cdm_reference	<i>Bring a remote CDM reference into R</i>
-----------------------	--

---

**Description**

This function calls collect on a list of lazy queries and returns the result as a list of dataframes.

**Usage**

```
## S3 method for class 'cdm_reference'
collect(x, ...)
```

**Arguments**

x A cdm\_reference object.

... Not used. Included for compatibility.

**Value**

A cdm\_reference object that is a list of R dataframes.

**Examples**

```
## Not run:
con <- DBI::dbConnect(duckdb::duckdb(), dbdir = eunomia_dir())
vocab <- cdm_from_con(con, "main") %>%
  cdm_select_tbl("concept", "concept_ancestor")

local_vocab <- collect(vocab)
DBI::dbDisconnect(con, shutdown = TRUE)

## End(Not run)
```

---

computeQuery

*Execute dplyr query and save result in remote database*


---

**Description**

This function is a wrapper around `dplyr::compute` that is tested on several database systems. It is needed to handle edge cases where `dplyr::compute` does not produce correct SQL.

**Usage**

```
computeQuery(
  x,
  name = uniqueTableName(),
  temporary = TRUE,
  schema = NULL,
  overwrite = FALSE,
  ...
)

compute_query(
  x,
  name = uniqueTableName(),
  temporary = TRUE,
  schema = NULL,
  overwrite = FALSE,
  ...
)
```

**Arguments**

x	A dplyr query
name	The name of the table to create.
temporary	Should the table be temporary: TRUE (default) or FALSE
schema	The schema where the table should be created. Ignored if temporary = TRUE.
overwrite	Should the table be overwritten if it already exists: TRUE or FALSE (default) Ignored if temporary = TRUE.
...	Further arguments passed on the <code>dplyr::compute</code>

**Value**

A `dplyr::tbl()` reference to the newly created table.

**Examples**

```
## Not run:
library(CDMConnector)

con <- DBI::dbConnect(duckdb::duckdb(), dbdir = eunomia_dir())
cdm <- cdm_from_con(con, "main")

# create a temporary table in the remote database from a dplyr query
drugCount <- cdm$concept %>%
  dplyr::count(domain_id == "Drug") %>%
  computeQuery()

# create a permanent table in the remote database from a dplyr query
drugCount <- cdm$concept %>%
  dplyr::count(domain_id == "Drug") %>%
  computeQuery("tmp_table", temporary = FALSE, schema = "main")

DBI::dbDisconnect(con, shutdown = TRUE)

## End(Not run)
```

---

copy\_cdm\_to

*Copy a cdm object from one database to another*

---

**Description**

It may be helpful to be able to easily copy a small test cdm from a local database to a remote for testing. `copy_cdm_to` takes a cdm object and a connection. It copies the cdm to the remote database connection. CDM tables can be prefixed in the new database allowing for multiple cdms in a single shared database schema.

**Usage**

```
copy_cdm_to(con, cdm, schema, overwrite = FALSE)
```

```
copyCdmTo(con, cdm, schema, overwrite = FALSE)
```

**Arguments**

<code>con</code>	A DBI database connection created by <code>DBI::dbConnect</code>
<code>cdm</code>	A cdm reference object created by <code>CDMConnector::cdmFromCon</code> or <code>CDMConnector::cdm_from_con</code>
<code>schema</code>	schema name in the remote database where the user has write permission
<code>overwrite</code>	Should the cohort table be overwritten if it already exists? TRUE or FALSE (default)

**Details****[Experimental]****Value**

A cdm reference object pointing to the newly created cdm in the remote database

---

dateadd	<i>Add days or years to a date in a dplyr query</i>
---------	---

---

**Description**

This function must be "unquoted" using the "bang bang" operator (!!). See example.

**Usage**

```
dateadd(date, number, interval = "day")
```

**Arguments**

date	The name of a date column in the database table as a character string
number	The number of units to add. Can be a positive or negative whole number.
interval	The units to add. Must be either "day" (default) or "year"

**Value**

Platform specific SQL that can be used in a dplyr query.

**Examples**

```
## Not run:
con <- DBI::dbConnect(duckdb::duckdb())
date_tbl <- dplyr::copy_to(con, data.frame(date1 = as.Date("1999-01-01")),
                           name = "tmpdate", overwrite = TRUE, temporary = TRUE)

df <- date_tbl %>%
  dplyr::mutate(date2 = !!dateadd("date1", 1, interval = "year")) %>%
  dplyr::collect()

DBI::dbDisconnect(con, shutdown = TRUE)

## End(Not run)
```

---

`datediff`                      *Compute the difference between two days*

---

### Description

This function must be "unquoted" using the "bang bang" operator (!!). See example.

### Usage

```
datediff(start, end, interval = "day")
```

### Arguments

<code>start</code>	The name of the start date column in the database as a string.
<code>end</code>	The name of the end date column in the database as a string.
<code>interval</code>	The units to use for difference calculation. Must be either "day" (default) or "year".

### Value

Platform specific SQL that can be used in a dplyr query.

### Examples

```
## Not run:
con <- DBI::dbConnect(duckdb::duckdb())
date_tbl <- dplyr::copy_to(con, data.frame(date1 = as.Date("1999-01-01")),
                           name = "tmpdate", overwrite = TRUE, temporary = TRUE)

df <- date_tbl %>%
  dplyr::mutate(date2 = !!dateadd("date1", 1, interval = "year")) %>%
  dplyr::mutate(dif_years = !!datediff("date1", "date2", interval = "year")) %>%
  dplyr::collect()

DBI::dbDisconnect(con, shutdown = TRUE)

## End(Not run)
```

---

`datepart`                      *Extract the day, month or year of a date in a dplyr pipeline*

---

### Description

Extract the day, month or year of a date in a dplyr pipeline

**Usage**

```
datepart(date, interval = "year", dbms = NULL)
```

**Arguments**

date	Character string that represents to a date column.
interval	Interval to extract from a date. Valid options are "year", "month", or "day".
dbms	Database system, if NULL it is auto detected.

**Examples**

```
## Not run:
con <- DBI::dbConnect(duckdb::duckdb(), ":memory:")
date_tbl <- dplyr::copy_to(con,
                           data.frame(birth_date = as.Date("1993-04-19")),
                           name = "tmp",
                           temporary = TRUE)
df <- date_tbl %>%
  dplyr::mutate(year = !!datepart("birth_date", "year")) %>%
  dplyr::mutate(month = !!datepart("birth_date", "month")) %>%
  dplyr::mutate(day = !!datepart("birth_date", "day")) %>%
  dplyr::collect()
DBI::dbDisconnect(con, shutdown = TRUE)

## End(Not run)
```

---

dbms	<i>Get the database management system (dbms) from a cdm_reference or DBI connection</i>
------	---

---

**Description**

Get the database management system (dbms) from a cdm\_reference or DBI connection

**Usage**

```
dbms(con)
```

**Arguments**

con	A DBI connection or cdm_reference
-----	-----------------------------------

**Value**

A character string representing the dbms that can be used with SqlRender

## Examples

```
## Not run:
con <- DBI::dbConnect(duckdb::duckdb(), dbdir = eunomia_dir())
cdm <- cdm_from_con(con)
dbms(cdm)
dbms(con)

## End(Not run)
```

---

downloadEunomiaData    *Download Eunomia data files*

---

## Description

Download the Eunomia data files from <https://github.com/darwin-eu/EunomiaDatasets>

## Usage

```
downloadEunomiaData(
  datasetName = "GiBleed",
  cdmVersion = "5.3",
  pathToData = Sys.getenv("EUNOMIA_DATA_FOLDER"),
  overwrite = FALSE
)

download_eunomia_data(
  dataset_name = "GiBleed",
  cdm_version = "5.3",
  path_to_data = Sys.getenv("EUNOMIA_DATA_FOLDER"),
  overwrite = FALSE
)
```

## Arguments

**overwrite**            Control whether the existing archive file will be overwritten should it already exist.

**dataset\_name, datasetName**  
The data set name as found on <https://github.com/darwin-eu/EunomiaDatasets>.  
The data set name corresponds to the folder with the data set ZIP files

**cdm\_version, cdmVersion**  
The OMOP CDM version. This version will appear in the suffix of the data file, for example: synpuf\_5.3.zip. Default: '5.3'

**path\_to\_data, pathToData**  
The path where the Eunomia data is stored on the file system., By default the value of the environment variable "EUNOMIA\_DATA\_FOLDER" is used.



**Value**

Invisibly returns the destination if the download was successful.

**Examples**

```
## Not run:
downloadEunomiaData("GiBleed")

## End(Not run)
```

---

dropTable	<i>Drop tables from write_schema of a cdm object</i>
-----------	--

---

**Description**

cdm objects can have zero or more cohort tables stored in a special schema where the user has write access. This function removes tables from a cdm's write\_schema

**Usage**

```
dropTable(cdm, name, verbose = FALSE)

drop_table(cdm, name, verbose = FALSE)
```

**Arguments**

cdm	A cdm reference
name	A character vector of tables in the cdm's write_schema or a <b>tidyselect</b> specification of tables to drop. (e.g. starts_with("temp"), matches("study01"), etc.)
verbose	Print a message when dropping a table? TRUE or FALSE (default)

**Value**

Returns the cdm object with selected tables removed

**Examples**

```
## Not run:
library(CDMConnector)

con <- DBI::dbConnect(duckdb::duckdb(), dbdir = eunomia_dir())
cdm <- cdm_from_con(con, cdm_schema = "main", write_schema = "main")

# create two temporary tables in the remote database from a query with a common prefix
cdm$tmp_table <- cdm$concept %>%
  dplyr::count(domain_id == "Drug") %>%
  computeQuery("tmp_table", temporary = FALSE, schema = "main")
```

```

cdm$tmp_table2 <- cdm$concept %>%
  dplyr::count(domain_id == "Condition") %>%
  computeQuery("tmp_table2", temporary = FALSE, schema = "main")

stringr::str_subset(DBI::dbListTables(con), "tmp")
#> [1] "tmp_table" "tmp_table2"
stringr::str_subset(names(cdm), "tmp")
#> [1] "tmp_table" "tmp_table2"

# drop tables with a common prefix
cdm <- dropTable(cdm, name = dplyr::starts_with("tmp"))

stringr::str_subset(DBI::dbListTables(con), "tmp")
#> character(0)
stringr::str_subset(names(cdm), "tmp")
#> character(0)

DBI::dbDisconnect(con, shutdown = TRUE)

## End(Not run)

```

---

eunomiaDir

*Create a copy of an example OMOP CDM dataset*


---

## Description

Creates a copy of a Eunomia database, and returns the path to the new database file. If the dataset does not yet exist on the user's computer it will attempt to download the source data to the the path defined by the EUNOMIA\_DATA\_FOLDER environment variable.

## Usage

```

eunomiaDir(
  datasetName = "GiBleed",
  cdmVersion = "5.3",
  databaseFile = tempfile(fileext = ".duckdb")
)

eunomia_dir(
  dataset_name = "GiBleed",
  cdm_version = "5.3",
  database_file = tempfile(fileext = ".duckdb")
)

```

## Arguments

datasetName, dataset\_name

One of "GiBleed" (default), "synthea-allergies-10k", "synthea-anemia-10k", "synthea-breast\_cancer-10k", "synthea-contraceptives-10k", "synthea-covid19-10k", "synthea-

covid19-200k", "synthea-dermatitis-10k", "synthea-heart-10k", "synthea-hiv-10k",  
 "synthea-lung\_cancer-10k", "synthea-medications-10k", "synthea-metabolic\_syndrome-  
 10k", "synthea-opioid\_addiction-10k", "synthea-rheumatoid\_arthritis-10k", "synthea-  
 snf-10k", "synthea-surgery-10k", "synthea-total\_joint\_replacement-10k", "synthea-  
 veteran\_prostate\_cancer-10k", "synthea-veterans-10k", "synthea-weight\_loss-10k"

cdmVersion, cdm\_version

The OMOP CDM version. Currently only "5.3" is supported.

databaseFile, database\_file

The full path to the new copy of the example CDM dataset.

### Value

The file path to the new Eunomia dataset copy

### Examples

```
## Not run:
con <- DBI::dbConnect(duckdb::duckdb(), eunomiaDir("GiBleed"))
DBI::dbDisconnect(con, shutdown = TRUE)

## End(Not run)
```

---

eunomia\_is\_available *Has the Eunomia dataset been cached?*

---

### Description

Has the Eunomia dataset been cached?

### Usage

```
eunomia_is_available(dataset_name = "GiBleed", cdm_version = "5.3")
```

```
eunomiaIsAvailable(datasetName = "GiBleed", cdmVersion = "5.3")
```

### Arguments

dataset\_name, datasetName

Name of the Eunomia dataset to check. Defaults to "GiBleed".

cdm\_version, cdmVersion

Version of the Eunomia dataset to check. Must be "5.3" or "5.4".

### Value

TRUE if the eunomia example dataset is available and FALSE otherwise

---

exampleDatasets      *List the available example CDM datasets*

---

### Description

List the available example CDM datasets

### Usage

```
exampleDatasets()
```

```
example_datasets()
```

### Value

A character vector with example CDM dataset identifiers

### Examples

```
## Not run:
library(CDMConnector)
exampleDatasets()[1]
#> [1] "GiBleed"

con <- DBI::dbConnect(duckdb::duckdb(), eunomiaDir("GiBleed"))
cdm <- cdm_from_con(con)

## End(Not run)
```

---

generateCohortSet      *Generate a cohort set on a cdm object*

---

### Description

A "GeneratedCohortSet" object consists of four components

- A remote table reference to an OHDSI cohort table with at least the columns: cohort\_definition\_id, subject\_id, cohort\_start\_date, cohort\_end\_date. Additional columns are optional and some analytic packages define additional columns specific to certain analytic cohorts.
- A **settings attribute** which points to a remote table containing cohort settings including the names of the cohorts.
- An **attrition attribute** which points to a remote table with attrition information recorded during generation. This attribute is optional. Since calculating attrition takes additional compute it can be skipped resulting in a NULL attrition attribute.
- A **cohortCounts attribute** which points to a remote table containing cohort counts

Each of the three attributes are tidy tables. The implementation of this object is experimental and user feedback is welcome.

### **[Experimental]**

One key design principle is that GeneratedCohortSet objects are created once and can persist across analysis execution but should not be modified after creation. While it is possible to modify a GeneratedCohortSet object doing so will invalidate it and it's attributes may no longer be accurate.

### **Usage**

```
generateCohortSet(
  cdm,
  cohortSet,
  name = "cohort",
  computeAttrition = TRUE,
  overwrite = FALSE
)

generate_cohort_set(
  cdm,
  cohort_set,
  name = "cohort",
  compute_attrition = TRUE,
  overwrite = FALSE
)
```

### **Arguments**

cdm	A cdm reference created by CDMConnector. write_schema must be specified.
name	Name of the cohort table to be created. This will also be used as a prefix for the cohort attribute tables.
overwrite	Should the cohort table be overwritten if it already exists? TRUE or FALSE (default)
cohort_set, cohortSet	Can be a cohortSet object created with readCohortSet(), a single Capr cohort definition, or a named list of Capr cohort definitions.
compute_attrition, computeAttrition	Should attrition be computed? TRUE (default) or FALSE

### **Examples**

```
## Not run:
library(CDMConnector)
con <- DBI::dbConnect(duckdb::duckdb(), eunomia_dir())
cdm <- cdm_from_con(con,
  cdm_schema = "main",
  write_schema = "main")

cohortSet <- readCohortSet(system.file("cohorts2", package = "CDMConnector"))
```

```

cdm <- generateCohortSet(cdm, cohortSet, name = "cohort")

print(cdm$cohort)

cohortAttrition(cdm$cohort)
cohortSet(cdm$cohort)
cohortCount(cdm$cohort)

## End(Not run)

```

---

```
generateConceptCohortSet
```

*Create a new generated cohort set from a list of concept sets*

---

## Description

Generate a new cohort set from one or more concept sets. Each concept set will result in one cohort and represent the time during which the concept was observed for each subject/person. Concept sets can be passed to this function as:

- A named list of numeric vectors, one vector per concept set
- A named list of Capr concept sets

Clinical observation records will be looked up in the respective domain tables using the vocabulary in the CDM. If a required domain table does not exist in the cdm object a warning will be given. Concepts that are not in the vocabulary or in the data will be silently ignored. If end dates are missing or do not exist, as in the case of the procedure and observation domains, the the start date will be used as the end date.

## Usage

```

generateConceptCohortSet(
  cdm,
  conceptSet = NULL,
  name = "cohort",
  limit = "first",
  requiredObservation = c(0, 0),
  end = "observation_period_end_date",
  overwrite = FALSE
)

generate_concept_cohort_set(
  cdm,
  concept_set = NULL,
  name = "cohort",
  limit = "first",
  required_observation = c(0, 0),
  end = "observation_period_end_date",
  overwrite = FALSE
)

```

**Arguments**

cdm	A cdm reference object created by <code>CDMConnector::cdmFromCon</code> or <code>CDMConnector::cdm_from_con</code>
conceptSet, concept_set	A named list of numeric vectors or Capr concept sets
name	The name of the new generated cohort table as a character string
limit	Include "first" (default) or "all" occurrences of events in the cohort <ul style="list-style-type: none"> <li>• "first" will include only the first occurrence of any event in the concept set in the cohort.</li> <li>• "all" will include all occurrences of the events defined by the concept set in the cohort.</li> </ul>
requiredObservation, required_observation	A numeric vector of length 2 that specifies the number of days of required observation time prior to index and post index for an event to be included in the cohort.
end	How should the <code>cohort_end_date</code> be defined? <ul style="list-style-type: none"> <li>• "observation_period_end_date" (default): The earliest <code>observation_period_end_date</code> after the event start date</li> <li>• numeric scalar: A fixed number of days from the event start date</li> <li>• "event_end_date": The event end date. If the event end date is not populated then the event start date will be used</li> </ul>
overwrite	Should the cohort table be overwritten if it already exists? TRUE or FALSE (default)

**Value**

A cdm reference object with the new generated cohort set table added

---

inSchema *Helper for working with compound schemas*

---

**Description**

This is similar to `dbplyr::in_schema` but has been tested across multiple database platforms. It only exists to work around some of the limitations of `dbplyr::in_schema`.

**Usage**

```
inSchema(schema, table, dbms = NULL)
```

```
in_schema(schema, table, dbms = NULL)
```

**Arguments**

schema	A schema name as a character string
table	A table name as character string
dbms	The name of the database management system as returned by <code>dbms(connection)</code>

**Value**

A DBI::Id that represents a qualified table and schema

---

intersect_cohorts	<i>Intersect all cohorts in a single cohort table</i>
-------------------	---

---

**Description**

Intersect all cohorts in a single cohort table

**Usage**

```
intersect_cohorts(x, cohort_definition_id = 1L)
```

```
intersectCohorts(x, cohort_definition_id = 1L)
```

**Arguments**

x	A tbl reference to a cohort table
cohort_definition_id	A number to use for the new cohort_definition_id

**[Superseded]**

**Value**

A lazy query that when executed will resolve to a new cohort table with one cohort\_definition\_id resulting from the intersection of all cohorts in the original cohort table

---

list_tables	<i>List tables in a schema</i>
-------------	--------------------------------

---

**Description**

DBI::dbListTables can be used to get all tables in a database but not always in a specific schema. listTables will list tables in a schema.

**Usage**

```
list_tables(con, schema = NULL)
```

```
listTables(con, schema = NULL)
```

**Arguments**

con	A DBI connection to a database
schema	The name of a schema in a database. If NULL, returns DBI::dbListTables(con).



**Value**

A character vector of table names

**Examples**

```
## Not run:  
con <- DBI::dbConnect(duckdb::duckdb(), dbdir = eunomia_dir())  
listTables(con, schema = "main")  
  
## End(Not run)
```

---

new\_generated\_cohort\_set

*Constructor for GeneratedCohortSet objects*

---

**Description**

This constructor function is to be used by analytic package developers to create generatedCohortSet objects.

**Usage**

```
new_generated_cohort_set(  
  cohort_ref,  
  cohort_set_ref = NULL,  
  cohort_attrition_ref = NULL,  
  cohort_count_ref = NULL,  
  overwrite = FALSE  
)
```

```
newGeneratedCohortSet(  
  cohortRef,  
  cohortSetRef = NULL,  
  cohortAttritionRef = NULL,  
  cohortCountRef = NULL,  
  overwrite = FALSE  
)
```

**Arguments**

cohort\_ref, cohortRef

A tbl\_sql object that points to a remote cohort table with the following first four columns: cohort\_definition\_id, subject\_id, cohort\_start\_date, cohort\_end\_date. Additional columns are optional.

cohort_set_ref, cohortSetRef	A tbl_sql object that points to a remote table with the following first two columns: cohort_definition_id, cohort_name. Additional columns are optional. cohort_definition_id should be a primary key on this table and uniquely identify rows.
cohort_attrition_ref, cohortAttritionRef	A tbl_sql object that points to an attrition table in a remote database with the first column being cohort_definition_id.
cohort_count_ref, cohortCountRef	A tbl_sql object that points to a cohort_count table in a remote database with columns cohort_definition_id, cohort_entries, cohort_subjects.
overwrite	Should tables be overwritten if they already exist? TRUE or FALSE (default)

## Details

A generatedCohort is a set of person-time from an OMOP CDM database. A generatedCohort can be represented by a table with three columns: subject\_id, cohort\_start\_date, cohort\_end\_date. Subject\_id is the same as person\_id in the OMOP CDM. A generatedCohortSet is a collection of one or more generatedCohorts and can be represented as a table with four columns: cohort\_definition\_id, subject\_id, cohort\_start\_date, cohort\_end\_date.

This constructor function defines the generatedCohortSet object in R.

The object is an extension of a tbl\_sql object defined in dplyr. This is a lazy database query that points to a cohort table in the database with at least the columns cohort\_definition\_id, subject\_id, cohort\_start\_date, cohort\_end\_date. The table could optionally have more columns as well.

In addition the generatedCohortSet object has three optional attributes. These are: cohort\_set, cohort\_attrition, cohort\_count. Each of these attributes is also a lazy SQL query (tbl\_sql) that points to a table in a database and is described below.

### cohort\_set:

cohort\_set is a table with one row per cohort\_definition\_id. The first two columns of the cohort\_set table are: cohort\_definition\_id, and cohort\_name. Additional columns can be added. The cohort\_set table is meant to store metadata about the cohort definition. Since this table is required it will be created if it is not supplied.

### cohort\_attrition:

cohort\_attrition is an optional table that stores attrition information recorded during the cohort generation process such as how many persons were dropped at each step of inclusion rule application. The first column of this table should be cohort\_definition\_id but all other columns currently have no constraints.

### cohort\_count:

cohort\_count is a optional attribute table that records the number of records and the number of unique persons in each cohort in a generatedCohortSet. It is derived metadata that can be re-derived as long as cohort\_set, the complete list of cohorts in the set, is available. Column names of cohort\_count are: cohort\_definition\_id, number\_records, number\_subjects. This table is required for generatedCohortSet objects and will be created if not supplied.

**Value**

A generatedCohortSet object that is a tbl\_sql reference to a cohort table in the write\_schema of an OMOP CDM

**Examples**

```
## Not run:
# This function is for developers who are creating generatedCohortSet
# objects in their packages. The function should accept a cdm_reference
# object as the first argument and return a cdm_reference object with the
# cohort table added. The second argument should be `name` which will be
# the prefix for the database tables, the name of the cohort table in the
# database and the name of the cohort table in the cdm object.
# Other optional arguments can be added after the first two.

generateCustomCohort <- function(cdm, name, ...) {

  # accept a cdm_reference object as input
  checkmate::assertClass(cdm, "cdm_reference")
  con <- attr(cdm, "dbcon")

  # Create the tables in the database however you like
  # All the tables should be prefixed with `name`
  # The cohort table should be called `name` in the database

  # Create the dplyr table references
  cohort_ref <- dplyr::tbl(con, name)
  cohort_set <- dplyr::tbl(con, paste0(name, "_set"))
  cohort_attrition_ref <- dplyr::tbl(con, paste0(name, "_attrition"))
  cohort_count_ref <- dplyr::tbl(con, paste0(name, "_count"))

  # add to the cdm
  cdm[[name]] <- cohort_ref

  # create the generated cohort set object using the constructor
  cdm[[name]] <- new_generated_cohort_set(
    cdm[[name]],
    cohort_set_ref = cohort_set_ref,
    cohort_attrition_ref = cohort_attrition_ref,
    cohort_count_ref = cohort_count_ref)

  return(cdm)
}

## End(Not run)
```

**Description**

Print a CDM reference object

**Usage**

```
## S3 method for class 'cdm_reference'
print(x, ...)
```

**Arguments**

x	A cdm_reference object
...	Included for compatibility with generic. Not used.

**Value**

Invisibly returns the input

---

read_cohort_set	<i>Read a set of cohort definitions into R</i>
-----------------	--

---

**Description**

A "cohort set" is a collection of cohort definitions. In R this is stored in a dataframe with cohort\_definition\_id, cohort\_name, and cohort columns. On disk this is stored as a folder with a CohortsToCreate.csv file and one or more json files. If the CohortsToCreate.csv file is missing then all of the json files in the folder will be used, cohort\_definition\_id will be automatically assigned in alphabetical order, and cohort\_name will match the file names.

**Usage**

```
read_cohort_set(path)
readCohortSet(path)
```

**Arguments**

path	The path to a folder containing Circe cohort definition json files and optionally a csv file named CohortsToCreate.csv with columns cohortId, cohortName, and jsonPath.
------	---

---

recordCohortAttrition *Add attrition reason to a GeneratedCohortSet object*

---

### Description

Update the cohort attrition table with new counts and a reason for attrition.

### Usage

```
recordCohortAttrition(cohort, reason, cohortId = NULL)
```

```
record_cohort_attrition(cohort, reason, cohortId = NULL)
```

### Arguments

cohort	A generated cohort set
reason	The reason for attrition as a character string
cohortId	Cohort definition id of the cohort you want to update the attrition

### Value

The cohort object with the attributes created or updated.

**[Experimental]**

### Examples

```
## Not run:
library(CDMConnector)
library(dplyr)

con <- DBI::dbConnect(duckdb::duckdb(), eunomia_dir())
cdm <- cdm_from_con(con = con, cdm_schema = "main", write_schema = "main")
cdm <- generateConceptCohortSet(
  cdm = cdm, conceptSet = list(pharyngitis = 4112343), name = "new_cohort"
)

cohortSet(cdm$new_cohort)
cohortCount(cdm$new_cohort)
cohortAttrition(cdm$new_cohort)

cdm$new_cohort <- cdm$new_cohort %>%
  filter(cohort_start_date >= as.Date("2010-01-01"))

cdm$new_cohort <- updateCohortAttributes(
  cohort = cdm$new_cohort, reason = "Only events after 2010"
)

cohortSet(cdm$new_cohort)
```

```

cohortCount(cdm$new_cohort)
cohortAttrition(cdm$new_cohort)

## End(Not run)

```

---

snapshot	<i>Extract CDM metadata</i>
----------	-----------------------------

---

### Description

Extract the name, version, and selected record counts from a cdm.

### Usage

```
snapshot(cdm)
```

### Arguments

cdm                    A cdm object

### Value

A named list of attributes about the cdm including selected fields from the cdm\_source table and record counts from the person and observation\_period tables

### Examples

```

## Not run:
library(CDMConnector)
con <- DBI::dbConnect(duckdb::duckdb(), eunomia_dir())
cdm <- cdm_from_con(con, "main")
snapshot(cdm)

DBI::dbDisconnect(con, shutdown = TRUE)

## End(Not run)

```

---

stow	<i>Collect a list of lazy queries and save the results as files</i>
------	---

---

### Description

Collect a list of lazy queries and save the results as files

### Usage

```
stow(cdm, path, format = "parquet")
```

**Arguments**

cdm	A cdm object
path	A folder to save the cdm object to
format	The file format to use: "parquet" (default), "csv", "feather" or "duckdb".

**Value**

Invisibly returns the cdm input

**Examples**

```
## Not run:
con <- DBI::dbConnect(duckdb::duckdb(), dbdir = eunomia_dir())
vocab <- cdm_from_con(con, "main") %>%
  cdm_select_tbl("concept", "concept_ancestor")
stow(vocab, here::here("vocab_tables"))
DBI::dbDisconnect(con, shutdown = TRUE)

## End(Not run)
```

---

summarise\_quantile      *Quantile calculation using dbplyr*

---

**Description**

This function provides DBMS independent syntax for quantiles estimation. Can be used by itself or in combination with mutate() when calculating other aggregate metrics (min, max, mean).

summarise\_quantile(), summarize\_quantile(), summariseQuantile() and summarizeQuantile() are synonyms.

**Usage**

```
summarise_quantile(.data, x = NULL, probs, name_suffix = "value")
```

```
summarize_quantile(.data, x = NULL, probs, name_suffix = "value")
```

```
summariseQuantile(.data, x = NULL, probs, nameSuffix = "value")
```

```
summarizeQuantile(.data, x = NULL, probs, nameSuffix = "value")
```

**Arguments**

.data	lazy data frame backed by a database query.
x	column name whose sample quantiles are wanted.
probs	numeric vector of probabilities with values in [0,1].
name_suffix, nameSuffix	character; is appended to numerical quantile value as a column name part.

**Details**

Implemented quantiles estimation algorithm returns values analogous to `quantile{stats}` with argument `type = 1`. See discussion in Hyndman and Fan (1996). Results differ from `PERCENTILE_CONT` natively implemented in various DBMS, where returned values are equal to `quantile{stats}` with default argument `type = 7`

**Value**

An object of the same type as `'data'`

**Examples**

```
## Not run:
con <- DBI::dbConnect(duckdb::duckdb())
mtcars_tbl <- dplyr::copy_to(con, mtcars, name = "tmp", overwrite = TRUE, temporary = TRUE)

df <- mtcars_tbl %>%
  dplyr::group_by(cyl) %>%
  dplyr::mutate(mean = mean(mpg, na.rm = TRUE)) %>%
  summarise_quantile(mpg, probs = c(0, 0.2, 0.4, 0.6, 0.8, 1),
                    name_suffix = "quant") %>%
  dplyr::collect()

DBI::dbDisconnect(con, shutdown = TRUE)

## End(Not run)
```

---

tbl\_group

*CDM table selection helper*


---

**Description**

The OMOP CDM tables are grouped together and the `tbl_group` function allows users to easily create a CDM reference including one or more table groups.

**Usage**

```
tbl_group(group)
```

```
tblGroup(group)
```

**Arguments**

`group` A character vector of CDM table groups: "vocab", "clinical", "all", "default", "derived".



**Details**

" alt" alt

The "default" table group is meant to capture the most commonly used set of CDM tables. Currently the "default" group is: person, observation\_period, visit\_occurrence, visit\_detail, condition\_occurrence, drug\_exposure, procedure\_occurrence, device\_exposure, measurement, observation, death, note, note\_nlp, specimen, fact\_relationship, location, care\_site, provider, payer\_plan\_period, cost, drug\_era, dose\_era, condition\_era, concept, vocabulary, concept\_relationship, concept\_ancestor, concept\_synonym, drug\_strength

**Value**

A character vector of CDM tables names in the groups

**Examples**

```
## Not run:
con <- DBI::dbConnect(RPostgres::Postgres(),
                      dbname = "cdm",
                      host = "localhost",
                      user = "postgres",
                      password = Sys.getenv("PASSWORD"))

cdm <- cdm_from_con(con) %>%
  cdm_select_tbl(tbl_group("vocab"))

## End(Not run)
```

---

union_cohorts	<i>Union all cohorts in a single cohort table</i>
---------------	---

---

**Description**

Union all cohorts in a single cohort table

**Usage**

```
union_cohorts(x, cohort_definition_id = 1L)
```

```
unionCohorts(x, cohort_definition_id = 1L)
```

**Arguments**

x                   A tbl reference to a cohort table  
 cohort\_definition\_id   A number to use for the new cohort\_definition\_id  
**[Superseded]**

**Value**

A lazy query that when executed will resolve to a new cohort table with one cohort\_definition\_id resulting from the union of all cohorts in the original cohort table

---

uniqueTableName	<i>Create a unique table name for temp tables</i>
-----------------	---

---

**Description**

Create a unique table name for temp tables

**Usage**

```
uniqueTableName()
```

```
unique_table_name()
```

**Value**

A string that can be used as a dbplyr temp table name

---

validate_cdm	<i>Validation report for a CDM</i>
--------------	------------------------------------

---

**Description**

Print a short validation report for a cdm object. The validation includes checking that column names are correct and that no tables are empty. A short report is printed to the console. This function is meant for interactive use.

**Usage**

```
validate_cdm(cdm)
```

```
validateCdm(cdm)
```

**Arguments**

cdm                    A cdm reference object.

**Value**

Invisibly returns the cdm input

## Examples

```
## Not run:
con <- DBI::dbConnect(duckdb::duckdb(), eunomia_dir())
cdm <- cdm_from_con(con, cdm_schema = "main")
validate_cdm(cdm)
DBI::dbDisconnect(con)

## End(Not run)
```

---

version	<i>Get the CDM version</i>
---------	----------------------------

---

## Description

Extract the CDM version attribute from a `cdm_reference` object

## Usage

```
version(cdm)
```

## Arguments

cdm            A cdm object

## Value

"5.3" or "5.4"

## Examples

```
## Not run:
library(CDMConnector)
con <- DBI::dbConnect(duckdb::duckdb(), eunomia_dir())
cdm <- cdm_from_con(con, "main")
version(cdm)

DBI::dbDisconnect(con, shutdown = TRUE)

## End(Not run)
```

---

[.cdm\_reference      *Subset a cdm reference object*

---

**Description**

Subset a cdm reference object

**Usage**

```
## S3 method for class 'cdm_reference'  
x[i]
```

**Arguments**

x                    A cdm reference  
i                    The name or index of the table to extract from the cdm object

**Value**

A single cdm table reference

---

[[.cdm\_reference      *Subset a cdm reference object*

---

**Description**

Subset a cdm reference object

**Usage**

```
## S3 method for class 'cdm_reference'  
x[[i]]
```

**Arguments**

x                    A cdm reference  
i                    The name or index of the table to extract from the cdm object

**Value**

A single cdm table reference

---

\$.cdm\_reference      *Subset a cdm reference object*

---

**Description**

Subset a cdm reference object

**Usage**

```
## S3 method for class 'cdm_reference'  
x$name
```

**Arguments**

x                    A cdm reference  
name                The name of the table to extract from the cdm object

**Value**

A single cdm table reference

# Index

[.cdm\_reference, 44  
[[.cdm\_reference, 44  
\$.cdm\_reference, 45

append\_permanent (appendPermanent), 3  
appendPermanent, 3  
as\_date (asDate), 4  
asDate, 4  
assert\_tables, 5  
assert\_write\_schema, 6  
assertTables (assert\_tables), 5  
assertWriteSchema  
    (assert\_write\_schema), 6

cdm\_disconnect (cdmDisconnect), 6  
cdm\_flatten (cdmFlatten), 7  
cdm\_from\_con, 13  
cdm\_from\_files, 14  
cdm\_name (cdmName), 8  
cdm\_sample (cdmSample), 9  
cdm\_select\_tbl, 15  
cdm\_subset (cdmSubset), 10  
cdm\_subset\_cohort (cdmSubsetCohort), 11  
cdmDisconnect, 6  
cdmFlatten, 7  
cdmFromCon (cdm\_from\_con), 13  
cdmFromFiles (cdm\_from\_files), 14  
cdmName, 8  
cdmSample, 9  
cdmSubset, 10  
cdmSubsetCohort, 11  
cohort\_attrition (cohortAttrition), 16  
cohort\_count (cohortCount), 16  
cohort\_erafy, 17  
cohort\_set (cohortSet), 17  
cohort\_union, 18  
cohortAttrition, 16  
cohortCount, 16  
cohortErafy (cohort\_erafy), 17  
cohortSet, 17

cohortUnion (cohort\_union), 18  
collect.cdm\_reference, 18  
compute\_query (computeQuery), 19  
computeQuery, 19  
copy\_cdm\_to, 20  
copyCdmTo (copy\_cdm\_to), 20

dateadd, 21  
datediff, 22  
datepart, 22  
dbms, 23  
download\_eunomia\_data  
    (downloadEunomiaData), 24  
downloadEunomiaData, 24  
drop\_table (dropTable), 25  
dropTable, 25

eunomia\_dir (eunomiaDir), 26  
eunomia\_is\_available, 27  
eunomiaDir, 26  
eunomiaIsAvailable  
    (eunomia\_is\_available), 27  
example\_datasets (exampleDatasets), 28  
exampleDatasets, 28

generate\_cohort\_set  
    (generateCohortSet), 28  
generate\_concept\_cohort\_set  
    (generateConceptCohortSet), 30  
generateCohortSet, 28  
generateConceptCohortSet, 30

in\_schema (inSchema), 31  
inSchema, 31  
intersect\_cohorts, 32  
intersectCohorts (intersect\_cohorts), 32

list\_tables, 32  
listTables (list\_tables), 32  
new\_generated\_cohort\_set, 33

`newGeneratedCohortSet`  
    (`new_generated_cohort_set`), 33

`print.cdm_reference`, 35

`read_cohort_set`, 36  
`readCohortSet` (`read_cohort_set`), 36  
`record_cohort_attrition`  
    (`recordCohortAttrition`), 37  
`recordCohortAttrition`, 37

`snapshot`, 38  
`stow`, 38  
`summarise_quantile`, 39  
`summariseQuantile` (`summarise_quantile`),  
    39  
`summarize_quantile`  
    (`summarise_quantile`), 39  
`summarizeQuantile` (`summarise_quantile`),  
    39

`tbl_group`, 40  
`tblGroup` (`tbl_group`), 40

`union_cohorts`, 41  
`unionCohorts` (`union_cohorts`), 41  
`unique_table_name` (`uniqueTableName`), 42  
`uniqueTableName`, 42

`validate_cdm`, 42  
`validateCdm` (`validate_cdm`), 42  
`version`, 43