

Package ‘ash’

September 1, 2015

Version 1.0-15

Title David Scott's ASH Routines

Author S original by David W. Scott

R port by Albrecht Gebhardt <albrecht.gebhardt@aau.at>

adopted to recent S-PLUS by Stephen Kaluzny <spk@insightful.com>

Maintainer Albrecht Gebhardt <albrecht.gebhardt@aau.at>

Description David Scott's ASH routines ported from S-PLUS to R.

License GPL (>= 2)

Date 2015-08-27

NeedsCompilation yes

Repository CRAN

Date/Publication 2015-09-01 17:56:55

R topics documented:

ash-internal	1
ash1	2
ash2	3
bin1	4
bin2	4

Index	6
--------------	----------

ash-internal	<i>Internal ash functions</i>
--------------	-------------------------------

Description

Internal ash functions

Details

These functions are not intended to be called by the user.

ash1	<i>univariate ASH</i>
------	-----------------------

Description

Computes univariate averaged shifted histogram (polynomial kernel)

Usage

```
ash1(bins, m, kopt)
```

Arguments

bins	(input list) \$nc=integer vector of bin counts and \$ab=bin interval
m	(input) optional integer smoothing parameter; default=5.
kopt	(input) vector of length 2 specifying the kernel, which is proportional to $(1 - \text{abs}(i/m)^{k_{opt}(1)})^{k_{opt}(2)}$; (2,2)=biweight (default); (0,0)=uniform; (1,0)=triangle; (2,1)=Epanechnikov; (2,3)=triweight.

Value

returns structure suitable for input to plot dd

x=t	vector of bin center locations
y=f	vector of ash estimates
ier	0=normal exit; 1=estimate nonzero outside interval ab

See Also

[bin1](#)

Examples

```
x <- rnorm(100)          # data
f <- ash1(bin1(x,nbin=50),5) # compute ash estimate
plot( f , type="l" )     # line plot of estimate
```

ash2	<i>bivariate ASH</i>
------	----------------------

Description

Compute bivariate ASH estimate (product polynomial kernel)

Usage

```
ash2(bins, m, kopt)
```

Arguments

bins	(input list) bin count matrix nc and interval matrix ab from bin2
m	(input integer vector of length 2) x and y direction smoothing parameters. Default is 5 by 5.
kopt	see ash1

Value

Matrix of ASH estimates returned. Components x,y,z can be given to the contour function directly. Other input variables returned in list for record keeping.

See Also

[bin2](#)

Examples

```
# Continuing example from help(bin2)
m <- c(5,5)
f <- ash2(bins,m)
image(f$x, f$y, f$z)
contour(f$x, f$y, f$z, add=TRUE)
```

bin1 *univariate binning*

Description

Function to compute array of bin counts for a data vector

Usage

```
bin1(x, ab, nbin=50)
```

Arguments

x (input) data vector
ab (input vector of length 2): half-open interval for bins $[a, b)$. If no value is specified, the range of x is stretched by 5% at each end and used the interval.
nbin (input integer): number of bins desired. Default 50.

Value

bin1 returns a list including the vector of integer bin counts and the ab vector and the number of points outside the ab interval.

See Also

[ash1](#)

Examples

```
x <- rnorm(100)      # data vector
ab <- c(-5,5)       # bin interval
bins <- bin1(x,ab,10) # bin x into 10 bins over ab
```

bin2 *2D binning*

Description

Bin bivariate data x

Usage

```
bin2(x, ab, nbin)
```

Arguments

x	(input matrix with 2 columns) data sample
ab	(input 2 x 2 matrix) rows 1 and 2 contain x and y axis bin intervals, respectively. If not specified, the ranges are stretched by 5% at each end for each dimension.
nbin	(input vector of length 2) number of bins along x and y axes. Default is 20 by 20.

Value

bin2 returns a list including the bivariate bin matrix and the number of points outside the ab rectangle.

See Also

[ash2](#)

Examples

```
x <- matrix( rnorm(200), 100 , 2)      # bivariate normal n=100
ab <- matrix( c(-5,-5,5,5), 2, 2)     # interval [-5,5) x [-5,5)
nbin <- c( 20, 20)                   # 400 bins
bins <- bin2(x, ab, nbin)             # bin counts,ab,nskip
```

Index

*Topic **nonparametric**

ash-internal, 1

ash1, 2

ash2, 3

bin1, 4

bin2, 4

ash-internal, 1

ash1, 2, 3, 4

ash2, 3, 5

bin1, 2, 4

bin2, 3, 4

center (ash-internal), 1

nicerange (ash-internal), 1