

Package ‘datawizard’

March 22, 2023

Type Package

Title Easy Data Wrangling and Statistical Transformations

Version 0.7.0

Maintainer Etienne Bacher <etienne.bacher@protonmail.com>

Description A lightweight package to assist in key steps involved in any data analysis workflow: (1) wrangling the raw data to get it in the needed form, (2) applying preprocessing steps and statistical transformations, and (3) compute statistical summaries of data properties and distributions. It is also the data wrangling backend for packages in 'easystats' ecosystem. References: Patil et al. (2022) <doi:10.21105/joss.04684>.

License GPL (>= 3)

URL <https://easystats.github.io/datawizard/>

BugReports <https://github.com/easystats/datawizard/issues>

Depends R (>= 3.6)

Imports insight (>= 0.18.8), stats, utils

Suggests bayestestR, boot, brms, data.table, dplyr (>= 1.0), effectsize, gamm4, ggplot2, gt, haven, htmltools, httr, knitr, lme4, mediation, parameters, poorman (>= 0.2.6), psych, readxl, readr, rio, rmarkdown, rstanarm, see, testthat (>= 3.1.0), tidyr, withr

VignetteBuilder knitr

Encoding UTF-8

Language en-US

RoxygenNote 7.2.3.9000

Config/testthat/edition 3

Config/Needs/website rstudio/bslib, r-lib/pkgdown, easystats/easystatstemplate

NeedsCompilation no

Author Indrajeet Patil [aut] (<<https://orcid.org/0000-0003-1995-6531>>, @patilindrajeets),
 Etienne Bacher [aut, cre] (<<https://orcid.org/0000-0002-9271-5075>>),
 Dominique Makowski [aut] (<<https://orcid.org/0000-0001-5375-9967>>, @Dom_Makowski),
 Daniel Lüdecke [aut] (<<https://orcid.org/0000-0002-8895-3206>>, @strengjacke),
 Mattan S. Ben-Shachar [aut] (<<https://orcid.org/0000-0002-4287-4801>>),
 Brenton M. Wiernik [aut] (<<https://orcid.org/0000-0001-9560-6336>>, @bmwiernik),
 Rémi Thériault [ctb] (<<https://orcid.org/0000-0003-4315-6788>>, @rempsysc),
 Thomas J. Faulkenberry [rev],
 Robert Garrett [rev]

Repository CRAN

Date/Publication 2023-03-22 16:40:06 UTC

R topics documented:

add_labs	3
adjust	6
categorize	9
center	13
coef_var	17
coerce_to_numeric	18
convert_na_to	19
convert_to_na	22
data_addprefix	24
data_arrange	27
data_codebook	28
data_duplicated	31
data_extract	33
data_group	35
data_match	37
data_merge	40
data_partition	43
data_peek	45
data_read	47
data_relocate	49
data_restoretype	52
data_rotate	53
data_tabulate	54
data_to_long	56
data_to_wide	60
data_unique	63
demean	65
describe_distribution	69

distribution_mode	72
efc	73
find_columns	73
makepredictcall.dw_transformer	77
mean_sd	78
nhanes_sample	79
normalize	79
ranktransform	82
recode_into	84
recode_values	85
remove_empty	90
replace_nan_inf	92
rescale	93
rescale_weights	95
reshape_ci	97
reverse	98
rownames_as_column	100
row_to_colnames	101
skewness	102
slide	104
smoothness	106
standardize	107
standardize.default	112
text_format	114
to_factor	116
to_numeric	118
visualisation_recipe	120
weighted_mean	121
winsorize	122

Index**125**

add_labs	<i>Add variable and value labels</i>
----------	--------------------------------------

Description

Add variable and values labels to a variable or variables in a data frame. Labels are stored as attributes ("label" for variable labels and "labels") for value labels.

Usage

```
add_labs(x, ...)

## S3 method for class 'numeric'
add_labs(x, variable = NULL, values = NULL, ...)

## S3 method for class 'data.frame'
```

```

add_labs(
  x,
  select = NULL,
  exclude = NULL,
  values = NULL,
  ignore_case = FALSE,
  regex = FALSE,
  verbose = TRUE,
  ...
)

```

Arguments

x	A data frame, factor or vector.
...	Currently not used.
variable	The variable label as string.
values	The value labels as (named) character vector. If values is <i>not</i> a named vector, the length of labels must be equal to the length of unique values. For a named vector, the left-hand side (LHS) is the value in x, the right-hand side (RHS) the associated value label. Non-matching labels are omitted.
select	Variables that will be included when performing the required tasks. Can be either <ul style="list-style-type: none"> • a variable specified as a literal variable name (e.g., column_name), • a string with the variable name (e.g., "column_name"), or a character vector of variable names (e.g., c("col1", "col2", "col3")), • a formula with variable names (e.g., ~column_1 + column_2), • a vector of positive integers, giving the positions counting from the left (e.g. 1 or c(1, 3, 5)), • a vector of negative integers, giving the positions counting from the right (e.g., -1 or -1:-3), • one of the following select-helpers: starts_with(), ends_with(), contains(), a range using : or regex(""). starts_with(), ends_with(), and contains() accept several patterns, e.g starts_with("Sep", "Petal"). • or a function testing for logical conditions, e.g. is.numeric() (or is.numeric), or any user-defined function that selects the variables for which the function returns TRUE (like: foo <- function(x) mean(x) > 3), • ranges specified via literal variable names, select-helpers (except regex()) and (user-defined) functions can be negated, i.e. return non-matching elements, when prefixed with a -, e.g. -ends_with(""), -is.numeric or -(Sepal.Width:Petal.Length). Note: Negation means that matches are <i>excluded</i>, and thus, the exclude argument can be used alternatively. For instance, select=-ends_with("Length") (with -) is equivalent to exclude=ends_with("Length") (no -). In case negation should not work as expected, use the exclude argument instead.

If NULL, selects all columns. Patterns that found no matches are silently ignored, e.g. find_columns(iris, select = c("Species", "Test")) will just return "Species".

exclude	See select, however, column names matched by the pattern from exclude will be excluded instead of selected. If NULL (the default), excludes no columns.
ignore_case	Logical, if TRUE and when one of the select-helpers or a regular expression is used in select, ignores lower/upper case in the search pattern when matching against variable names.
regex	Logical, if TRUE, the search pattern from select will be treated as regular expression. When regex = TRUE, select <i>must</i> be a character string (or a variable containing a character string) and is not allowed to be one of the supported select-helpers or a character vector of length > 1. regex = TRUE is comparable to using one of the two select-helpers, select = contains("") or select = regex(""), however, since the select-helpers may not work when called from inside other functions (see 'Details'), this argument may be used as workaround.
verbose	Toggle warnings.

Value

A labelled variable, or a data frame of labelled variables.

Selection of variables - the select argument

For most functions that have a select argument (including this function), the complete input data frame is returned, even when select only selects a range of variables. That is, the function is only applied to those variables that have a match in select, while all other variables remain unchanged. In other words: for this function, select will not omit any non-included variables, so that the returned data frame will include all variables from the input data frame.

Examples

```
x <- 1:3
# labelling by providing required number of labels
add_labs(
  x,
  variable = "My x",
  values = c("one", "two", "three")
)

# labelling using named vectors
data(iris)
out <- add_labs(
  iris$Species,
  variable = "Labelled Species",
  values = c(`setosa` = "Spec1", `versicolor` = "Spec2", `virginica` = "Spec3")
)
str(out)

# data frame example
out <- add_labs(
  iris,
  select = "Species",
  variable = "Labelled Species",
```

```
  values = c(`setosa` = "Spec1", `versicolor` = "Spec2", `virginica` = "Spec3")
)
str(out$Species)

# Partial labelling
x <- 1:5
add_labs(
  x,
  variable = "My x",
  values = c(`1` = "lowest", `5` = "highest")
)
```

adjust

Adjust data for the effect of other variable(s)

Description

This function can be used to adjust the data for the effect of other variables present in the dataset. It is based on an underlying fitting of regressions models, allowing for quite some flexibility, such as including factors as random effects in mixed models (multilevel partialization), continuous variables as smooth terms in general additive models (non-linear partialization) and/or fitting these models under a Bayesian framework. The values returned by this function are the residuals of the regression models. Note that a regular correlation between two "adjusted" variables is equivalent to the partial correlation between them.

Usage

```
adjust(
  data,
  effect = NULL,
  select = is.numeric,
  exclude = NULL,
  multilevel = FALSE,
  additive = FALSE,
  bayesian = FALSE,
  keep_intercept = FALSE,
  ignore_case = FALSE,
  regex = FALSE,
  verbose = FALSE
)
```

```
data_adjust(
  data,
  effect = NULL,
  select = is.numeric,
  exclude = NULL,
  multilevel = FALSE,
  additive = FALSE,
```

```

    bayesian = FALSE,
    keep_intercept = FALSE,
    ignore_case = FALSE,
    regex = FALSE,
    verbose = FALSE
  )

```

Arguments

data	A data frame.
effect	Character vector of column names to be adjusted for (regressed out). If NULL (the default), all variables will be selected.
select	<p>Variables that will be included when performing the required tasks. Can be either</p> <ul style="list-style-type: none"> • a variable specified as a literal variable name (e.g., <code>column_name</code>), • a string with the variable name (e.g., <code>"column_name"</code>), or a character vector of variable names (e.g., <code>c("col1", "col2", "col3")</code>), • a formula with variable names (e.g., <code>~column_1 + column_2</code>), • a vector of positive integers, giving the positions counting from the left (e.g. 1 or <code>c(1, 3, 5)</code>), • a vector of negative integers, giving the positions counting from the right (e.g., -1 or <code>-1:-3</code>), • one of the following select-helpers: <code>starts_with()</code>, <code>ends_with()</code>, <code>contains()</code>, a range using <code>:</code> or <code>regex("")</code>. <code>starts_with()</code>, <code>ends_with()</code>, and <code>contains()</code> accept several patterns, e.g <code>starts_with("Sep", "Petal")</code>. • or a function testing for logical conditions, e.g. <code>is.numeric()</code> (or <code>is.numeric</code>), or any user-defined function that selects the variables for which the function returns TRUE (like: <code>foo <- function(x) mean(x) > 3</code>), • ranges specified via literal variable names, select-helpers (except <code>regex()</code>) and (user-defined) functions can be negated, i.e. return non-matching elements, when prefixed with a <code>-</code>, e.g. <code>-ends_with("")</code>, <code>-is.numeric</code> or <code>-(Sepal.Width:Petal.Length)</code>. Note: Negation means that matches are <i>excluded</i>, and thus, the <code>exclude</code> argument can be used alternatively. For instance, <code>select=-ends_with("Length")</code> (with <code>-</code>) is equivalent to <code>exclude=ends_with("Length")</code> (no <code>-</code>). In case negation should not work as expected, use the <code>exclude</code> argument instead. <p>If NULL, selects all columns. Patterns that found no matches are silently ignored, e.g. <code>find_columns(iris, select = c("Species", "Test"))</code> will just return <code>"Species"</code>.</p>
exclude	See <code>select</code> , however, column names matched by the pattern from <code>exclude</code> will be excluded instead of selected. If NULL (the default), excludes no columns.
multilevel	If TRUE, the factors are included as random factors. Else, if FALSE (default), they are included as fixed effects in the simple regression model.
additive	If TRUE, continuous variables as included as smooth terms in additive models. The goal is to regress-out potential non-linear effects.

bayesian	If TRUE, the models are fitted under the Bayesian framework using <code>rstanarm</code> .
keep_intercept	If FALSE (default), the intercept of the model is re-added. This avoids the centering around 0 that happens by default when regressing out another variable (see the examples below for a visual representation of this).
ignore_case	Logical, if TRUE and when one of the select-helpers or a regular expression is used in <code>select</code> , ignores lower/upper case in the search pattern when matching against variable names.
regex	Logical, if TRUE, the search pattern from <code>select</code> will be treated as regular expression. When <code>regex = TRUE</code> , <code>select</code> <i>must</i> be a character string (or a variable containing a character string) and is not allowed to be one of the supported select-helpers or a character vector of length > 1. <code>regex = TRUE</code> is comparable to using one of the two select-helpers, <code>select = contains("")</code> or <code>select = regex("")</code> , however, since the select-helpers may not work when called from inside other functions (see 'Details'), this argument may be used as workaround.
verbose	Toggle warnings.

Value

A data frame comparable to `data`, with adjusted variables.

Examples

```
adjusted_all <- adjust(attitude)
head(adjusted_all)
adjusted_one <- adjust(attitude, effect = "complaints", select = "rating")
head(adjusted_one)

adjust(attitude, effect = "complaints", select = "rating", bayesian = TRUE)
adjust(attitude, effect = "complaints", select = "rating", additive = TRUE)
attitude$complaints_LMH <- cut(attitude$complaints, 3)
adjust(attitude, effect = "complaints_LMH", select = "rating", multilevel = TRUE)

# Generate data
data <- simulate_correlation(n = 100, r = 0.7)
data$V2 <- (5 * data$V2) + 20 # Add intercept

# Adjust
adjusted <- adjust(data, effect = "V1", select = "V2")
adjusted_icpt <- adjust(data, effect = "V1", select = "V2", keep_intercept = TRUE)

# Visualize
plot(data$V1, data$V2,
      pch = 19, col = "blue",
      ylim = c(min(adjusted$V2), max(data$V2)),
      main = "Original (blue), adjusted (green), and adjusted - intercept kept (red) data"
)
abline(lm(V2 ~ V1, data = data), col = "blue")
points(adjusted$V1, adjusted$V2, pch = 19, col = "green")
```



```
abline(lm(V2 ~ V1, data = adjusted), col = "green")
points(adjusted_icpt$V1, adjusted_icpt$V2, pch = 19, col = "red")
abline(lm(V2 ~ V1, data = adjusted_icpt), col = "red")
```

categorize

Recode (or "cut") data into groups of values.

Description

This functions divides the range of variables into intervals and recodes the values inside these intervals according to their related interval. It is basically a wrapper around base R's `cut()`, providing a simplified and more accessible way to define the interval breaks (cut-off values).

Usage

```
categorize(x, ...)
```

```
## S3 method for class 'numeric'
categorize(
  x,
  split = "median",
  n_groups = NULL,
  range = NULL,
  lowest = 1,
  labels = NULL,
  verbose = TRUE,
  ...
)
```

```
## S3 method for class 'data.frame'
categorize(
  x,
  select = NULL,
  exclude = NULL,
  split = "median",
  n_groups = NULL,
  range = NULL,
  lowest = 1,
  labels = NULL,
  append = FALSE,
  ignore_case = FALSE,
  regex = FALSE,
  verbose = TRUE,
  ...
)
```

Arguments

<code>x</code>	A (grouped) data frame, numeric vector or factor.
<code>...</code>	not used.
<code>split</code>	Character vector, indicating at which breaks to split variables, or numeric values with values indicating breaks. If character, may be one of "median", "mean", "quantile", "equal_length", or "equal_range". "median" or "mean" will return dichotomous variables, split at their mean or median, respectively. "quantile" and "equal_length" will split the variable into <code>n_groups</code> groups, where each group refers to an interval of a specific range of values. Thus, the length of each interval will be based on the number of groups. "equal_range" also splits the variable into multiple groups, however, the length of the interval is given, and the number of resulting groups (and hence, the number of breaks) will be determined by how many intervals can be generated, based on the full range of the variable.
<code>n_groups</code>	If <code>split</code> is "quantile" or "equal_length", this defines the number of requested groups (i.e. resulting number of levels or values) for the recoded variable(s). "quantile" will define intervals based on the distribution of the variable, while "equal_length" tries to divide the range of the variable into pieces of equal length.
<code>range</code>	If <code>split</code> = "equal_range", this defines the range of values that are recoded into a new value.
<code>lowest</code>	Minimum value of the recoded variable(s). If NULL (the default), for numeric variables, the minimum of the original input is preserved. For factors, the default minimum is 1. For <code>split</code> = "equal_range", the default minimum is always 1, unless specified otherwise in <code>lowest</code> .
<code>labels</code>	Character vector of value labels. If not NULL, <code>categorize()</code> will return factors instead of numeric variables, with <code>labels</code> used for labelling the factor levels. Can also be "mean" or "median" for a factor with labels as the mean/median of each groups.
<code>verbose</code>	Toggle warnings.
<code>select</code>	Variables that will be included when performing the required tasks. Can be either <ul style="list-style-type: none"> • a variable specified as a literal variable name (e.g., <code>column_name</code>), • a string with the variable name (e.g., <code>"column_name"</code>), or a character vector of variable names (e.g., <code>c("col1", "col2", "col3")</code>), • a formula with variable names (e.g., <code>~column_1 + column_2</code>), • a vector of positive integers, giving the positions counting from the left (e.g. 1 or <code>c(1, 3, 5)</code>), • a vector of negative integers, giving the positions counting from the right (e.g., -1 or <code>-1:-3</code>), • one of the following select-helpers: <code>starts_with()</code>, <code>ends_with()</code>, <code>contains()</code>, a range using <code>:</code> or <code>regex("")</code>. <code>starts_with()</code>, <code>ends_with()</code>, and <code>contains()</code> accept several patterns, e.g <code>starts_with("Sep", "Petal")</code>.

- or a function testing for logical conditions, e.g. `is.numeric()` (or `is.numeric`), or any user-defined function that selects the variables for which the function returns TRUE (like: `foo <- function(x) mean(x) > 3`),
- ranges specified via literal variable names, select-helpers (except `regex()`) and (user-defined) functions can be negated, i.e. return non-matching elements, when prefixed with a `-`, e.g. `-ends_with("")`, `-is.numeric` or `-(Sepal.Width:Petal.Length)`. **Note:** Negation means that matches are *excluded*, and thus, the `exclude` argument can be used alternatively. For instance, `select=-ends_with("Length")` (with `-`) is equivalent to `exclude=ends_with("Length")` (no `-`). In case negation should not work as expected, use the `exclude` argument instead.

If NULL, selects all columns. Patterns that found no matches are silently ignored, e.g. `find_columns(iris, select = c("Species", "Test"))` will just return "Species".

<code>exclude</code>	See <code>select</code> , however, column names matched by the pattern from <code>exclude</code> will be excluded instead of selected. If NULL (the default), excludes no columns.
<code>append</code>	Logical or string. If TRUE, recoded or converted variables get new column names and are appended (column bind) to <code>x</code> , thus returning both the original and the recoded variables. The new columns get a suffix, based on the calling function: <code>"_r"</code> for recode functions, <code>"_n"</code> for <code>to_numeric()</code> , <code>"_f"</code> for <code>to_factor()</code> , or <code>"_s"</code> for <code>slide()</code> . If <code>append=FALSE</code> , original variables in <code>x</code> will be overwritten by their recoded versions. If a character value, recoded variables are appended with new column names (using the defined suffix) to the original data frame.
<code>ignore_case</code>	Logical, if TRUE and when one of the select-helpers or a regular expression is used in <code>select</code> , ignores lower/upper case in the search pattern when matching against variable names.
<code>regex</code>	Logical, if TRUE, the search pattern from <code>select</code> will be treated as regular expression. When <code>regex = TRUE</code> , <code>select</code> <i>must</i> be a character string (or a variable containing a character string) and is not allowed to be one of the supported select-helpers or a character vector of length > 1. <code>regex = TRUE</code> is comparable to using one of the two select-helpers, <code>select = contains("")</code> or <code>select = regex("")</code> , however, since the select-helpers may not work when called from inside other functions (see 'Details'), this argument may be used as workaround.

Value

`x`, recoded into groups. By default `x` is numeric, unless `labels` is specified. In this case, a factor is returned, where the factor levels (i.e. recoded groups are labelled accordingly).

Splits and breaks (cut-off values)

Breaks are in general *exclusive*, this means that these values indicate the lower bound of the next group or interval to begin. Take a simple example, a numeric variable with values from 1 to 9. The median would be 5, thus the first interval ranges from 1-4 and is recoded into 1, while 5-9 would turn into 2 (compare `cbind(1:9, categorize(1:9))`). The same variable, using `split = "quantile"` and `n_groups = 3` would define breaks at 3.67 and 6.33 (see `quantile(1:9, probs = c(1/3, 2/3))`), which means that values from 1 to 3 belong to the first interval and are recoded into 1 (because the next interval starts at 3.67), 4 to 6 into 2 and 7 to 9 into 3.

Recoding into groups with equal size or range

`split = "equal_length"` and `split = "equal_range"` try to divide the range of `x` into intervals of similar (or same) length. The difference is that `split = "equal_length"` will divide the range of `x` into `n_groups` pieces and thereby defining the intervals used as breaks (hence, it is equivalent to `cut(x, breaks = n_groups)`), while `split = "equal_range"` will cut `x` into intervals that all have the length of range, where the first interval by defaults starts at 1. The lowest (or starting) value of that interval can be defined using the lowest argument.

Selection of variables - the select argument

For most functions that have a `select` argument (including this function), the complete input data frame is returned, even when `select` only selects a range of variables. That is, the function is only applied to those variables that have a match in `select`, while all other variables remain unchanged. In other words: for this function, `select` will not omit any non-included variables, so that the returned data frame will include all variables from the input data frame.

See Also

- Functions to rename stuff: `data_rename()`, `data_rename_rows()`, `data_addprefix()`, `data_addsuffix()`
- Functions to reorder or remove columns: `data_reorder()`, `data_relocate()`, `data_remove()`
- Functions to reshape, pivot or rotate data frames: `data_to_long()`, `data_to_wide()`, `data_rotate()`
- Functions to recode data: `rescale()`, `reverse()`, `categorize()`, `recode_values()`, `slide()`
- Functions to standardize, normalize, rank-transform: `center()`, `standardize()`, `normalize()`, `ranktransform()`, `winsorize()`
- Split and merge data frames: `data_partition()`, `data_merge()`
- Functions to find or select columns: `data_select()`, `data_find()`
- Functions to filter rows: `data_match()`, `data_filter()`

Examples

```
set.seed(123)
x <- sample(1:10, size = 50, replace = TRUE)

table(x)

# by default, at median
table(categorize(x))

# into 3 groups, based on distribution (quantiles)
table(categorize(x, split = "quantile", n_groups = 3))

# into 3 groups, user-defined break
table(categorize(x, split = c(3, 5)))

set.seed(123)
x <- sample(1:100, size = 500, replace = TRUE)

# into 5 groups, try to recode into intervals of similar length,
```

```

# i.e. the range within groups is the same for all groups
table(categorize(x, split = "equal_length", n_groups = 5))

# into 5 groups, try to return same range within groups
# i.e. 1-20, 21-40, 41-60, etc. Since the range of "x" is
# 1-100, and we have a range of 20, this results into 5
# groups, and thus is for this particular case identical
# to the previous result.
table(categorize(x, split = "equal_range", range = 20))

# return factor with value labels instead of numeric value
set.seed(123)
x <- sample(1:10, size = 30, replace = TRUE)
categorize(x, "equal_length", n_groups = 3)
categorize(x, "equal_length", n_groups = 3, labels = c("low", "mid", "high"))

# cut numeric into groups with the mean or median as a label name
x <- sample(1:10, size = 30, replace = TRUE)
categorize(x, "equal_length", n_groups = 3, labels = "mean")
categorize(x, "equal_length", n_groups = 3, labels = "median")

```

center

Centering (Grand-Mean Centering)

Description

Performs a grand-mean centering of data.

Usage

```
center(x, ...)
```

```
centre(x, ...)
```

```
## S3 method for class 'numeric'
```

```
center(
  x,
  robust = FALSE,
  weights = NULL,
  reference = NULL,
  center = NULL,
  verbose = TRUE,
  ...
)
```

```
## S3 method for class 'data.frame'
```

```
center(
  x,
  select = NULL,
```

```

exclude = NULL,
robust = FALSE,
weights = NULL,
reference = NULL,
center = NULL,
force = FALSE,
remove_na = c("none", "selected", "all"),
append = FALSE,
ignore_case = FALSE,
verbose = TRUE,
regex = FALSE,
...
)

```

Arguments

x	A (grouped) data frame, a (numeric or character) vector or a factor.
...	Currently not used.
robust	Logical, if TRUE, centering is done by subtracting the median from the variables. If FALSE, variables are centered by subtracting the mean.
weights	Can be NULL (for no weighting), or: <ul style="list-style-type: none"> • For data frames: a numeric vector of weights, or a character of the name of a column in the data.frame that contains the weights. • For numeric vectors: a numeric vector of weights.
reference	A data frame or variable from which the centrality and deviation will be computed instead of from the input variable. Useful for standardizing a subset or new data according to another data frame.
center	Numeric value, which can be used as alternative to reference to define a reference centrality. If center is of length 1, it will be recycled to match the length of selected variables for centering. Else, center must be of same length as the number of selected variables. Values in center will be matched to selected variables in the provided order, unless a named vector is given. In this case, names are matched against the names of the selected variables.
verbose	Toggle warnings and messages.
select	Variables that will be included when performing the required tasks. Can be either <ul style="list-style-type: none"> • a variable specified as a literal variable name (e.g., column_name), • a string with the variable name (e.g., "column_name"), or a character vector of variable names (e.g., c("col1", "col2", "col3")), • a formula with variable names (e.g., ~column_1 + column_2), • a vector of positive integers, giving the positions counting from the left (e.g. 1 or c(1, 3, 5)), • a vector of negative integers, giving the positions counting from the right (e.g., -1 or -1:-3),

- one of the following select-helpers: `starts_with()`, `ends_with()`, `contains()`, a range using `:` or `regex("")`. `starts_with()`, `ends_with()`, and `contains()` accept several patterns, e.g. `starts_with("Sep", "Petal")`.
- or a function testing for logical conditions, e.g. `is.numeric()` (or `is.numeric`), or any user-defined function that selects the variables for which the function returns TRUE (like: `foo <- function(x) mean(x) > 3`),
- ranges specified via literal variable names, select-helpers (except `regex()`) and (user-defined) functions can be negated, i.e. return non-matching elements, when prefixed with a `-`, e.g. `-ends_with("")`, `-is.numeric` or `-(Sepal.Width:Petal.Length)`. **Note:** Negation means that matches are *excluded*, and thus, the `exclude` argument can be used alternatively. For instance, `select=-ends_with("Length")` (with `-`) is equivalent to `exclude=ends_with("Length")` (no `-`). In case negation should not work as expected, use the `exclude` argument instead.

If NULL, selects all columns. Patterns that found no matches are silently ignored, e.g. `find_columns(iris, select = c("Species", "Test"))` will just return "Species".

<code>exclude</code>	See <code>select</code> , however, column names matched by the pattern from <code>exclude</code> will be excluded instead of selected. If NULL (the default), excludes no columns.
<code>force</code>	Logical, if TRUE, forces centering of factors as well. Factors are converted to numerical values, with the lowest level being the value 1 (unless the factor has numeric levels, which are converted to the corresponding numeric value).
<code>remove_na</code>	How should missing values (NA) be treated: if "none" (default): each column's standardization is done separately, ignoring NAs. Else, rows with NA in the columns selected with <code>select / exclude</code> ("selected") or in all columns ("all") are dropped before standardization, and the resulting data frame does not include these cases.
<code>append</code>	Logical or string. If TRUE, centered variables get new column names (with the suffix <code>"_c"</code>) and are appended (column bind) to <code>x</code> , thus returning both the original and the centered variables. If FALSE, original variables in <code>x</code> will be overwritten by their centered versions. If a character value, centered variables are appended with new column names (using the defined suffix) to the original data frame.
<code>ignore_case</code>	Logical, if TRUE and when one of the select-helpers or a regular expression is used in <code>select</code> , ignores lower/upper case in the search pattern when matching against variable names.
<code>regex</code>	Logical, if TRUE, the search pattern from <code>select</code> will be treated as regular expression. When <code>regex = TRUE</code> , <code>select</code> <i>must</i> be a character string (or a variable containing a character string) and is not allowed to be one of the supported select-helpers or a character vector of length > 1. <code>regex = TRUE</code> is comparable to using one of the two select-helpers, <code>select = contains("")</code> or <code>select = regex("")</code> , however, since the select-helpers may not work when called from inside other functions (see 'Details'), this argument may be used as workaround.

Value

The centered variables.

Selection of variables - the select argument

For most functions that have a select argument (including this function), the complete input data frame is returned, even when select only selects a range of variables. That is, the function is only applied to those variables that have a match in select, while all other variables remain unchanged. In other words: for this function, select will not omit any non-included variables, so that the returned data frame will include all variables from the input data frame.

Note

Difference between centering and standardizing: Standardized variables are computed by subtracting the mean of the variable and then dividing it by the standard deviation, while centering variables involves only the subtraction.

See Also

If centering within-clusters (instead of grand-mean centering) is required, see [demean\(\)](#). For standardizing, see [standardize\(\)](#), and [makepredictcall.dw_transformer\(\)](#) for use in model formulas.

Examples

```
data(iris)

# entire data frame or a vector
head(iris$Sepal.Width)
head(center(iris$Sepal.Width))
head(center(iris))
head(center(iris, force = TRUE))

# only the selected columns from a data frame
center(anscombe, select = c("x1", "x3"))
center(anscombe, exclude = c("x1", "x3"))

# centering with reference center and scale
d <- data.frame(
  a = c(-2, -1, 0, 1, 2),
  b = c(3, 4, 5, 6, 7)
)

# default centering at mean
center(d)

# centering, using 0 as mean
center(d, center = 0)

# centering, using -5 as mean
center(d, center = -5)
```

coef_var	<i>Compute the coefficient of variation</i>
----------	---

Description

Compute the coefficient of variation (CV, ratio of the standard deviation to the mean, σ/μ) for a set of numeric values.

Usage

```
coef_var(x, ...)

distribution_coef_var(x, ...)

## S3 method for class 'numeric'
coef_var(
  x,
  mu = NULL,
  sigma = NULL,
  method = c("standard", "unbiased", "median_mad", "qcd"),
  trim = 0,
  na.rm = FALSE,
  n = NULL,
  ...
)
```

Arguments

x	A numeric vector of ratio scale (see details), or vector of values than can be coerced to one.
...	Further arguments passed to computation functions.
mu	A numeric vector of mean values to use to compute the coefficient of variation. If supplied, x is not used to compute the mean.
sigma	A numeric vector of standard deviation values to use to compute the coefficient of variation. If supplied, x is not used to compute the SD.
method	Method to use to compute the CV. Can be "standard" to compute by dividing the standard deviation by the mean, "unbiased" for the unbiased estimator for normally distributed data, or one of two robust alternatives: "median_mad" to divide the median by the <code>stats::mad()</code> , or "qcd" (quartile coefficient of dispersion, interquartile range divided by the sum of the quartiles [twice the midhinge]: $(Q_3 - Q_1)/(Q_3 + Q_1)$).
trim	the fraction (0 to 0.5) of values to be trimmed from each end of x before the mean and standard deviation (or other measures) are computed. Values of trim outside the range of (0 to 0.5) are taken as the nearest endpoint.

na.rm	Logical. Should NA values be removed before computing (TRUE) or not (FALSE, default)?
n	If method = "unbiased" and both mu and sigma are provided (not computed from x), what sample size to use to adjust the computed CV for small-sample bias?

Details

CV is only applicable of values taken on a ratio scale: values that have a *fixed* meaningfully defined 0 (which is either the lowest or highest possible value), and that ratios between them are interpretable. For example, how many sandwiches have I eaten this week? 0 means "none" and 20 sandwiches is 4 times more than 5 sandwiches. If I were to center the number of sandwiches, it will no longer be on a ratio scale (0 is no "none" it is the mean, and the ratio between 4 and -2 is not meaningful). Scaling a ratio scale still results in a ratio scale. So I can re define "how many half sandwiches did I eat this week (= sandwiches * 0.5) and 0 would still mean "none", and 20 half-sandwiches is still 4 times more than 5 half-sandwiches.

This means that CV is **NOT** invariant to shifting, but it is to scaling:

```
sandwiches <- c(0, 4, 15, 0, 0, 5, 2, 7)
coef_var(sandwiches)
#> [1] 1.239094

coef_var(sandwiches / 2) # same
#> [1] 1.239094

coef_var(sandwiches + 4) # different! 0 is no longer meaningful!
#> [1] 0.6290784
```

Value

The computed coefficient of variation for x.

Examples

```
coef_var(1:10)
coef_var(c(1:10, 100), method = "median_mad")
coef_var(c(1:10, 100), method = "qcd")
coef_var(mu = 10, sigma = 20)
coef_var(mu = 10, sigma = 20, method = "unbiased", n = 30)
```

coerce_to_numeric *Convert to Numeric (if possible)*

Description

Tries to convert vector to numeric if possible (if no warnings or errors). Otherwise, leaves it as is.

Usage

```
coerce_to_numeric(x)
```

Arguments

x A vector to be converted.

Value

Numeric vector (if possible)

Examples

```
coerce_to_numeric(c("1", "2"))
coerce_to_numeric(c("1", "2", "A"))
```

convert_na_to	<i>Replace missing values in a variable or a data frame.</i>
---------------	--

Description

Replace missing values in a variable or a data frame.

Usage

```
convert_na_to(x, ...)

## S3 method for class 'numeric'
convert_na_to(x, replacement = NULL, verbose = TRUE, ...)

## S3 method for class 'character'
convert_na_to(x, replacement = NULL, verbose = TRUE, ...)

## S3 method for class 'data.frame'
convert_na_to(
  x,
  select = NULL,
  exclude = NULL,
  replacement = NULL,
  replace_num = replacement,
  replace_char = replacement,
  replace_fac = replacement,
  ignore_case = FALSE,
  regex = FALSE,
  verbose = TRUE,
  ...
)
```

Arguments

x	A numeric, factor, or character vector, or a data frame.
...	Not used.
replacement	Numeric or character value that will be used to replace NA.
verbose	Toggle warnings.
select	<p>Variables that will be included when performing the required tasks. Can be either</p> <ul style="list-style-type: none"> • a variable specified as a literal variable name (e.g., <code>column_name</code>), • a string with the variable name (e.g., <code>"column_name"</code>), or a character vector of variable names (e.g., <code>c("col1", "col2", "col3")</code>), • a formula with variable names (e.g., <code>~column_1 + column_2</code>), • a vector of positive integers, giving the positions counting from the left (e.g. <code>1</code> or <code>c(1, 3, 5)</code>), • a vector of negative integers, giving the positions counting from the right (e.g., <code>-1</code> or <code>-1:-3</code>), • one of the following select-helpers: <code>starts_with()</code>, <code>ends_with()</code>, <code>contains()</code>, a range using <code>:</code> or <code>regex("")</code>. <code>starts_with()</code>, <code>ends_with()</code>, and <code>contains()</code> accept several patterns, e.g. <code>starts_with("Sep", "Petal")</code>. • or a function testing for logical conditions, e.g. <code>is.numeric()</code> (or <code>is.numeric</code>), or any user-defined function that selects the variables for which the function returns TRUE (like: <code>foo <- function(x) mean(x) > 3</code>), • ranges specified via literal variable names, select-helpers (except <code>regex()</code>) and (user-defined) functions can be negated, i.e. return non-matching elements, when prefixed with a <code>-</code>, e.g. <code>-ends_with("")</code>, <code>-is.numeric</code> or <code>-(Sepal.Width:Petal.Length)</code>. Note: Negation means that matches are <i>excluded</i>, and thus, the <code>exclude</code> argument can be used alternatively. For instance, <code>select=-ends_with("Length")</code> (with <code>-</code>) is equivalent to <code>exclude=ends_with("Length")</code> (no <code>-</code>). In case negation should not work as expected, use the <code>exclude</code> argument instead. <p>If NULL, selects all columns. Patterns that found no matches are silently ignored, e.g. <code>find_columns(iris, select = c("Species", "Test"))</code> will just return <code>"Species"</code>.</p>
exclude	See <code>select</code> , however, column names matched by the pattern from <code>exclude</code> will be excluded instead of selected. If NULL (the default), excludes no columns.
replace_num	Value to replace NA when variable is of type numeric.
replace_char	Value to replace NA when variable is of type character.
replace_fac	Value to replace NA when variable is of type factor.
ignore_case	Logical, if TRUE and when one of the select-helpers or a regular expression is used in <code>select</code> , ignores lower/upper case in the search pattern when matching against variable names.
regex	Logical, if TRUE, the search pattern from <code>select</code> will be treated as regular expression. When <code>regex = TRUE</code> , <code>select</code> <i>must</i> be a character string (or a variable containing a character string) and is not allowed to be one of the supported

select-helpers or a character vector of length > 1. `regex = TRUE` is comparable to using one of the two select-helpers, `select = contains("")` or `select = regex("")`, however, since the select-helpers may not work when called from inside other functions (see 'Details'), this argument may be used as workaround.

Value

x, where NA values are replaced by replacement.

Selection of variables - the select argument

For most functions that have a `select` argument (including this function), the complete input data frame is returned, even when `select` only selects a range of variables. That is, the function is only applied to those variables that have a match in `select`, while all other variables remain unchanged. In other words: for this function, `select` will not omit any non-included variables, so that the returned data frame will include all variables from the input data frame.

Examples

```
# Convert NA to 0 in a numeric vector
convert_na_to(
  c(9, 3, NA, 2, 3, 1, NA, 8),
  replacement = 0
)

# Convert NA to "missing" in a character vector
convert_na_to(
  c("a", NA, "d", "z", NA, "t"),
  replacement = "missing"
)

### For data frames

test_df <- data.frame(
  x = c(1, 2, NA),
  x2 = c(4, 5, NA),
  y = c("a", "b", NA)
)

# Convert all NA to 0 in numeric variables, and all NA to "missing" in
# character variables
convert_na_to(
  test_df,
  replace_num = 0,
  replace_char = "missing"
)

# Convert a specific variable in the data frame
convert_na_to(
  test_df,
  replace_num = 0,
  replace_char = "missing",
```

```

    select = "x"
  )

# Convert all variables starting with "x"
convert_na_to(
  test_df,
  replace_num = 0,
  replace_char = "missing",
  select = starts_with("x")
)

# Convert NA to 1 in variable 'x2' and to 0 in all other numeric
# variables
convert_na_to(
  test_df,
  replace_num = 0,
  select = list(x2 = 1)
)

```

 convert_to_na

Convert non-missing values in a variable into missing values.

Description

Convert non-missing values in a variable into missing values.

Usage

```

convert_to_na(x, ...)

## S3 method for class 'numeric'
convert_to_na(x, na = NULL, verbose = TRUE, ...)

## S3 method for class 'factor'
convert_to_na(x, na = NULL, drop_levels = FALSE, verbose = TRUE, ...)

## S3 method for class 'data.frame'
convert_to_na(
  x,
  select = NULL,
  exclude = NULL,
  na = NULL,
  drop_levels = FALSE,
  ignore_case = FALSE,
  regex = FALSE,
  verbose = TRUE,
  ...
)

```

Arguments

x	A vector, factor or a data frame.
...	Not used.
na	Numeric, character vector or logical (or a list of numeric, character vectors or logicals) with values that should be converted to NA. Numeric values applied to numeric vectors, character values are used for factors, character vectors or date variables, and logical values for logical vectors.
verbose	Toggle warnings.
drop_levels	Logical, for factors, when specific levels are replaced by NA, should unused levels be dropped?
select	<p>Variables that will be included when performing the required tasks. Can be either</p> <ul style="list-style-type: none"> • a variable specified as a literal variable name (e.g., <code>column_name</code>), • a string with the variable name (e.g., <code>"column_name"</code>), or a character vector of variable names (e.g., <code>c("col1", "col2", "col3")</code>), • a formula with variable names (e.g., <code>~column_1 + column_2</code>), • a vector of positive integers, giving the positions counting from the left (e.g. 1 or <code>c(1, 3, 5)</code>), • a vector of negative integers, giving the positions counting from the right (e.g., -1 or <code>-1:-3</code>), • one of the following select-helpers: <code>starts_with()</code>, <code>ends_with()</code>, <code>contains()</code>, a range using <code>:</code> or <code>regex("")</code>. <code>starts_with()</code>, <code>ends_with()</code>, and <code>contains()</code> accept several patterns, e.g. <code>starts_with("Sep", "Petal")</code>. • or a function testing for logical conditions, e.g. <code>is.numeric()</code> (or <code>is.numeric</code>), or any user-defined function that selects the variables for which the function returns TRUE (like: <code>foo <- function(x) mean(x) > 3</code>), • ranges specified via literal variable names, select-helpers (except <code>regex()</code>) and (user-defined) functions can be negated, i.e. return non-matching elements, when prefixed with a <code>-</code>, e.g. <code>-ends_with("")</code>, <code>-is.numeric</code> or <code>-(Sepal.Width:Petal.Length)</code>. Note: Negation means that matches are <i>excluded</i>, and thus, the <code>exclude</code> argument can be used alternatively. For instance, <code>select=-ends_with("Length")</code> (with <code>-</code>) is equivalent to <code>exclude=ends_with("Length")</code> (no <code>-</code>). In case negation should not work as expected, use the <code>exclude</code> argument instead. <p>If NULL, selects all columns. Patterns that found no matches are silently ignored, e.g. <code>find_columns(iris, select = c("Species", "Test"))</code> will just return "Species".</p>
exclude	See <code>select</code> , however, column names matched by the pattern from <code>exclude</code> will be excluded instead of selected. If NULL (the default), excludes no columns.
ignore_case	Logical, if TRUE and when one of the select-helpers or a regular expression is used in <code>select</code> , ignores lower/upper case in the search pattern when matching against variable names.
regex	Logical, if TRUE, the search pattern from <code>select</code> will be treated as regular expression. When <code>regex = TRUE</code> , <code>select</code> <i>must</i> be a character string (or a variable

containing a character string) and is not allowed to be one of the supported select-helpers or a character vector of length > 1. `regex = TRUE` is comparable to using one of the two select-helpers, `select = contains("")` or `select = regex("")`, however, since the select-helpers may not work when called from inside other functions (see 'Details'), this argument may be used as workaround.

Value

`x`, where all values in `na` are converted to NA.

Examples

```
x <- sample(1:6, size = 30, replace = TRUE)
x
# values 4 and 5 to NA
convert_to_na(x, na = 4:5)

# data frames
set.seed(123)
x <- data.frame(
  a = sample(1:6, size = 20, replace = TRUE),
  b = sample(letters[1:6], size = 20, replace = TRUE),
  c = sample(c(30:33, 99), size = 20, replace = TRUE)
)
# for all numerics, convert 5 to NA. Character/factor will be ignored.
convert_to_na(x, na = 5)

# for numerics, 5 to NA, for character/factor, "f" to NA
convert_to_na(x, na = list(6, "f"))

# select specific variables
convert_to_na(x, select = c("a", "b"), na = list(6, "f"))
```

data_addprefix

Rename columns and variable names

Description

Safe and intuitive functions to rename variables or rows in data frames. `data_rename()` will rename column names, i.e. it facilitates renaming variables `data_addprefix()` or `data_addsuffix()` add prefixes or suffixes to column names. `data_rename_rows()` is a convenient shortcut to add or rename row names of a data frame, but unlike `row.names()`, its input and output is a data frame, thus, integrating smoothly into a possible pipe-workflow.

Usage

```
data_addprefix(
  data,
  pattern,
```



```

    select = NULL,
    exclude = NULL,
    ignore_case = FALSE,
    regex = FALSE,
    verbose = TRUE,
    ...
)

data_addsuffix(
  data,
  pattern,
  select = NULL,
  exclude = NULL,
  ignore_case = FALSE,
  regex = FALSE,
  verbose = TRUE,
  ...
)

data_rename(
  data,
  pattern = NULL,
  replacement = NULL,
  safe = TRUE,
  verbose = TRUE,
  ...
)

data_rename_rows(data, rows = NULL)

```

Arguments

data	A data frame, or an object that can be coerced to a data frame.
pattern	Character vector. For <code>data_rename()</code> , indicates columns that should be selected for renaming. Can be <code>NULL</code> (in which case all columns are selected). For <code>data_addprefix()</code> or <code>data_addsuffix()</code> , a character string, which will be added as prefix or suffix to the column names.
select	Variables that will be included when performing the required tasks. Can be either <ul style="list-style-type: none"> • a variable specified as a literal variable name (e.g., <code>column_name</code>), • a string with the variable name (e.g., <code>"column_name"</code>), or a character vector of variable names (e.g., <code>c("col1", "col2", "col3")</code>), • a formula with variable names (e.g., <code>~column_1 + column_2</code>), • a vector of positive integers, giving the positions counting from the left (e.g. <code>1</code> or <code>c(1, 3, 5)</code>), • a vector of negative integers, giving the positions counting from the right (e.g., <code>-1</code> or <code>-1:-3</code>),

- one of the following select-helpers: `starts_with()`, `ends_with()`, `contains()`, a range using `:` or `regex("")`. `starts_with()`, `ends_with()`, and `contains()` accept several patterns, e.g. `starts_with("Sep", "Petal")`.
- or a function testing for logical conditions, e.g. `is.numeric()` (or `is.numeric`), or any user-defined function that selects the variables for which the function returns TRUE (like: `foo <- function(x) mean(x) > 3`),
- ranges specified via literal variable names, select-helpers (except `regex()`) and (user-defined) functions can be negated, i.e. return non-matching elements, when prefixed with a `-`, e.g. `-ends_with("")`, `-is.numeric` or `-(Sepal.Width:Petal.Length)`. **Note:** Negation means that matches are *excluded*, and thus, the `exclude` argument can be used alternatively. For instance, `select=-ends_with("Length")` (with `-`) is equivalent to `exclude=ends_with("Length")` (no `-`). In case negation should not work as expected, use the `exclude` argument instead.

If NULL, selects all columns. Patterns that found no matches are silently ignored, e.g. `find_columns(iris, select = c("Species", "Test"))` will just return "Species".

<code>exclude</code>	See <code>select</code> , however, column names matched by the pattern from <code>exclude</code> will be excluded instead of selected. If NULL (the default), excludes no columns.
<code>ignore_case</code>	Logical, if TRUE and when one of the select-helpers or a regular expression is used in <code>select</code> , ignores lower/upper case in the search pattern when matching against variable names.
<code>regex</code>	Logical, if TRUE, the search pattern from <code>select</code> will be treated as regular expression. When <code>regex = TRUE</code> , <code>select</code> <i>must</i> be a character string (or a variable containing a character string) and is not allowed to be one of the supported select-helpers or a character vector of length > 1. <code>regex = TRUE</code> is comparable to using one of the two select-helpers, <code>select = contains("")</code> or <code>select = regex("")</code> , however, since the select-helpers may not work when called from inside other functions (see 'Details'), this argument may be used as workaround.
<code>verbose</code>	Toggle warnings and messages.
<code>...</code>	Other arguments passed to or from other functions.
<code>replacement</code>	Character vector. Indicates the new name of the columns selected in pattern. Can be NULL (in which case column are numbered in sequential order). If not NULL, pattern and replacement must be of the same length.
<code>safe</code>	Do not throw error if for instance the variable to be renamed/removed doesn't exist.
<code>rows</code>	Vector of row names.

Value

A modified data frame.

See Also

- Functions to rename stuff: `data_rename()`, `data_rename_rows()`, `data_addprefix()`, `data_addsuffix()`
- Functions to reorder or remove columns: `data_reorder()`, `data_relocate()`, `data_remove()`

- Functions to reshape, pivot or rotate data frames: `data_to_long()`, `data_to_wide()`, `data_rotate()`
- Functions to recode data: `rescale()`, `reverse()`, `categorize()`, `recode_values()`, `slide()`
- Functions to standardize, normalize, rank-transform: `center()`, `standardize()`, `normalize()`, `ranktransform()`, `winsorize()`
- Split and merge data frames: `data_partition()`, `data_merge()`
- Functions to find or select columns: `data_select()`, `data_find()`
- Functions to filter rows: `data_match()`, `data_filter()`

Examples

```
# Add prefix / suffix to all columns
head(data_addprefix(iris, "NEW_"))
head(data_addsuffix(iris, "_OLD"))

# Rename columns
head(data_rename(iris, "Sepal.Length", "length"))
# data_rename(iris, "FakeCol", "length", safe=FALSE) # This fails
head(data_rename(iris, "FakeCol", "length")) # This doesn't
head(data_rename(iris, c("Sepal.Length", "Sepal.Width"), c("length", "width")))

# Reset names
head(data_rename(iris, NULL))

# Change all
head(data_rename(iris, replacement = paste0("Var", 1:5)))
```

data_arrange	<i>Arrange rows by column values</i>
--------------	--------------------------------------

Description

`data_arrange()` orders the rows of a data frame by the values of selected columns.

Usage

```
data_arrange(data, select = NULL, safe = TRUE)
```

Arguments

<code>data</code>	A data frame, or an object that can be coerced to a data frame.
<code>select</code>	Character vector of column names. Use a dash just before column name to arrange in decreasing order, for example <code>"-x1"</code> .
<code>safe</code>	Do not throw an error if one of the variables specified doesn't exist.

Value

A data frame.

Examples

```
# Arrange using several variables
data_arrange(head(mtcars), c("gear", "carb"))

# Arrange in decreasing order
data_arrange(head(mtcars), "-carb")

# Throw an error if one of the variables specified doesn't exist
try(data_arrange(head(mtcars), c("gear", "foo"), safe = FALSE))
```

data_codebook	<i>Generate a codebook of a data frame.</i>
---------------	---

Description

`data_codebook()` generates codebooks from data frames, i.e. overviews of all variables and some more information about each variable (like labels, values or value range, frequencies, amount of missing values).

Usage

```
data_codebook(
  data,
  select = NULL,
  exclude = NULL,
  variable_label_width = NULL,
  value_label_width = NULL,
  max_values = 10,
  range_at = 6,
  ignore_case = FALSE,
  regex = FALSE,
  verbose = TRUE,
  ...
)

## S3 method for class 'data_codebook'
print_html(
  x,
  font_size = "100%",
  line_padding = 3,
  row_color = "#eeeeee",
  ...
)
```

Arguments

data	A data frame, or an object that can be coerced to a data frame.
select	<p>Variables that will be included when performing the required tasks. Can be either</p> <ul style="list-style-type: none"> • a variable specified as a literal variable name (e.g., <code>column_name</code>), • a string with the variable name (e.g., <code>"column_name"</code>), or a character vector of variable names (e.g., <code>c("col1", "col2", "col3")</code>), • a formula with variable names (e.g., <code>~column_1 + column_2</code>), • a vector of positive integers, giving the positions counting from the left (e.g. <code>1</code> or <code>c(1, 3, 5)</code>), • a vector of negative integers, giving the positions counting from the right (e.g., <code>-1</code> or <code>-1:-3</code>), • one of the following select-helpers: <code>starts_with()</code>, <code>ends_with()</code>, <code>contains()</code>, a range using <code>:</code> or <code>regex("")</code>. <code>starts_with()</code>, <code>ends_with()</code>, and <code>contains()</code> accept several patterns, e.g. <code>starts_with("Sep", "Petal")</code>. • or a function testing for logical conditions, e.g. <code>is.numeric()</code> (or <code>is.numeric</code>), or any user-defined function that selects the variables for which the function returns TRUE (like: <code>foo <- function(x) mean(x) > 3</code>), • ranges specified via literal variable names, select-helpers (except <code>regex()</code>) and (user-defined) functions can be negated, i.e. return non-matching elements, when prefixed with a <code>-</code>, e.g. <code>-ends_with("")</code>, <code>-is.numeric</code> or <code>-(Sepal.Width:Petal.Length)</code>. Note: Negation means that matches are <i>excluded</i>, and thus, the <code>exclude</code> argument can be used alternatively. For instance, <code>select=-ends_with("Length")</code> (with <code>-</code>) is equivalent to <code>exclude=ends_with("Length")</code> (no <code>-</code>). In case negation should not work as expected, use the <code>exclude</code> argument instead. <p>If NULL, selects all columns. Patterns that found no matches are silently ignored, e.g. <code>find_columns(iris, select = c("Species", "Test"))</code> will just return "Species".</p>
exclude	See <code>select</code> , however, column names matched by the pattern from <code>exclude</code> will be excluded instead of selected. If NULL (the default), excludes no columns.
variable_label_width	Length of variable labels. Longer labels will be wrapped at <code>variable_label_width</code> chars. If NULL, longer labels will not be split into multiple lines. Only applies to <i>labelled data</i> .
value_label_width	Length of value labels. Longer labels will be shortened, where the remaining part is truncated. Only applies to <i>labelled data</i> or factor levels.
max_values	Number of maximum values that should be displayed. Can be used to avoid too many rows when variables have lots of unique values.
range_at	Indicates how many unique values in a numeric vector are needed in order to print a range for that variable instead of a frequency table for all numeric values. Can be useful if the data contains numeric variables with only a few unique values and where full frequency tables instead of value ranges should be displayed.

ignore_case	Logical, if TRUE and when one of the select-helpers or a regular expression is used in select, ignores lower/upper case in the search pattern when matching against variable names.
regex	Logical, if TRUE, the search pattern from select will be treated as regular expression. When regex = TRUE, select <i>must</i> be a character string (or a variable containing a character string) and is not allowed to be one of the supported select-helpers or a character vector of length > 1. regex = TRUE is comparable to using one of the two select-helpers, select = contains("") or select = regex(""), however, since the select-helpers may not work when called from inside other functions (see 'Details'), this argument may be used as workaround.
verbose	Toggle warnings and messages on or off.
...	Arguments passed to or from other methods.
x	A (grouped) data frame, a vector or a statistical model (for unstandardize()) cannot be a model).
font_size	For HTML tables, the font size.
line_padding	For HTML tables, the distance (in pixel) between lines.
row_color	For HTML tables, the fill color for odd rows.

Value

A formatted data frame, summarizing the content of the data frame. Returned columns include the column index of the variables in the original data frame (ID), column name, variable label (if data is labelled), type of variable, number of missing values, unique values (or value range), value labels (for labelled data), and a frequency table (N for each value). Most columns are formatted as character vectors.

Note

There are methods to print() the data frame in a nicer output, as well methods for printing in markdown or HTML format (print_md() and print_html()).

Examples

```
data(iris)
data_codebook(iris, select = starts_with("Sepal"))

data(efc)
data_codebook(efc)

# shorten labels
data_codebook(efc, variable_label_width = 20, value_label_width = 15)

# automatic range for numerics at more than 5 unique values
data(mtcars)
data_codebook(mtcars, select = starts_with("c"))

# force all values to be displayed
data_codebook(mtcars, select = starts_with("c"), range_at = 100)
```

data_duplicated	<i>Extract all duplicates</i>
-----------------	-------------------------------

Description

Extract all duplicates, for visual inspection. Note that it also contains the first occurrence of future duplicates, unlike `duplicated()` or `dplyr::distinct()`. Also contains an additional column reporting the number of missing values for that row, to help in the decision-making when selecting which duplicates to keep.

Usage

```
data_duplicated(
  data,
  select = NULL,
  exclude = NULL,
  ignore_case = FALSE,
  regex = FALSE,
  verbose = TRUE
)
```

Arguments

data	A data frame.
select	Variables that will be included when performing the required tasks. Can be either <ul style="list-style-type: none"> • a variable specified as a literal variable name (e.g., <code>column_name</code>), • a string with the variable name (e.g., <code>"column_name"</code>), or a character vector of variable names (e.g., <code>c("col1", "col2", "col3")</code>), • a formula with variable names (e.g., <code>~column_1 + column_2</code>), • a vector of positive integers, giving the positions counting from the left (e.g. <code>1</code> or <code>c(1, 3, 5)</code>), • a vector of negative integers, giving the positions counting from the right (e.g., <code>-1</code> or <code>-1:-3</code>), • one of the following select-helpers: <code>starts_with()</code>, <code>ends_with()</code>, <code>contains()</code>, a range using <code>:</code> or <code>regex("")</code>. <code>starts_with()</code>, <code>ends_with()</code>, and <code>contains()</code> accept several patterns, e.g <code>starts_with("Sep", "Petal")</code>. • or a function testing for logical conditions, e.g. <code>is.numeric()</code> (or <code>is.numeric</code>), or any user-defined function that selects the variables for which the function returns TRUE (like: <code>foo <- function(x) mean(x) > 3</code>), • ranges specified via literal variable names, select-helpers (except <code>regex()</code>) and (user-defined) functions can be negated, i.e. return non-matching elements, when prefixed with a <code>-</code>, e.g. <code>-ends_with("")</code>, <code>-is.numeric</code> or <code>-(Sepal.Width:Petal.Length)</code>. Note: Negation means that matches are <i>excluded</i>, and thus, the <code>exclude</code> argument can be used alternatively.

For instance, `select=-ends_with("Length")` (with `-`) is equivalent to `exclude=ends_with("Length")` (no `-`). In case negation should not work as expected, use the `exclude` argument instead.

If `NULL`, selects all columns. Patterns that found no matches are silently ignored, e.g. `find_columns(iris, select = c("Species", "Test"))` will just return "Species".

<code>exclude</code>	See <code>select</code> , however, column names matched by the pattern from <code>exclude</code> will be excluded instead of selected. If <code>NULL</code> (the default), excludes no columns.
<code>ignore_case</code>	Logical, if <code>TRUE</code> and when one of the <code>select</code> -helpers or a regular expression is used in <code>select</code> , ignores lower/upper case in the search pattern when matching against variable names.
<code>regex</code>	Logical, if <code>TRUE</code> , the search pattern from <code>select</code> will be treated as regular expression. When <code>regex = TRUE</code> , <code>select</code> <i>must</i> be a character string (or a variable containing a character string) and is not allowed to be one of the supported <code>select</code> -helpers or a character vector of length <code>> 1</code> . <code>regex = TRUE</code> is comparable to using one of the two <code>select</code> -helpers, <code>select = contains("")</code> or <code>select = regex("")</code> , however, since the <code>select</code> -helpers may not work when called from inside other functions (see 'Details'), this argument may be used as workaround.
<code>verbose</code>	Toggle warnings.

Value

A dataframe, containing all duplicates.

See Also

[data_unique\(\)](#)

Examples

```
df1 <- data.frame(
  id = c(1, 2, 3, 1, 3),
  year = c(2022, 2022, 2022, 2022, 2000),
  item1 = c(NA, 1, 1, 2, 3),
  item2 = c(NA, 1, 1, 2, 3),
  item3 = c(NA, 1, 1, 2, 3)
)

data_duplicated(df1, select = "id")

data_duplicated(df1, select = c("id", "year"))

# Filter to exclude duplicates
df2 <- df1[-c(1, 5), ]
df2
```

data_extract	<i>Extract one or more columns or elements from an object</i>
--------------	---

Description

`data_extract()` (or its alias `extract()`) is similar to `$`. It extracts either a single column or element from an object (e.g., a data frame, list), or multiple columns resp. elements.

Usage

```
data_extract(data, select, ...)

## S3 method for class 'data.frame'
data_extract(
  data,
  select,
  name = NULL,
  extract = "all",
  as_data_frame = FALSE,
  ignore_case = FALSE,
  regex = FALSE,
  verbose = TRUE,
  ...
)
```

Arguments

- | | |
|---------------------|--|
| <code>data</code> | The object to subset. Methods are currently available for data frames and data frame extensions (e.g., tibbles). |
| <code>select</code> | Variables that will be included when performing the required tasks. Can be either <ul style="list-style-type: none"> • a variable specified as a literal variable name (e.g., <code>column_name</code>), • a string with the variable name (e.g., <code>"column_name"</code>), or a character vector of variable names (e.g., <code>c("col1", "col2", "col3")</code>), • a formula with variable names (e.g., <code>~column_1 + column_2</code>), • a vector of positive integers, giving the positions counting from the left (e.g. <code>1</code> or <code>c(1, 3, 5)</code>), • a vector of negative integers, giving the positions counting from the right (e.g., <code>-1</code> or <code>-1:-3</code>), • one of the following select-helpers: <code>starts_with()</code>, <code>ends_with()</code>, <code>contains()</code>, a range using <code>:</code> or <code>regex("")</code>. <code>starts_with()</code>, <code>ends_with()</code>, and <code>contains()</code> accept several patterns, e.g. <code>starts_with("Sep", "Petal")</code>. • or a function testing for logical conditions, e.g. <code>is.numeric()</code> (or <code>is.numeric</code>), or any user-defined function that selects the variables for which the function returns TRUE (like: <code>foo <- function(x) mean(x) > 3</code>), |

- ranges specified via literal variable names, select-helpers (except `regex()`) and (user-defined) functions can be negated, i.e. return non-matching elements, when prefixed with a `-`, e.g. `-ends_with("")`, `-is.numeric` or `-(Sepal.Width:Petal.Length)`. **Note:** Negation means that matches are *excluded*, and thus, the `exclude` argument can be used alternatively. For instance, `select=-ends_with("Length")` (with `-`) is equivalent to `exclude=ends_with("Length")` (no `-`). In case negation should not work as expected, use the `exclude` argument instead.

If `NULL`, selects all columns. Patterns that found no matches are silently ignored, e.g. `find_columns(iris, select = c("Species", "Test"))` will just return `"Species"`.

...	For use by future methods.
name	An optional argument that specifies the column to be used as names for the vector elements after extraction. Must be specified either as literal variable name (e.g., <code>column_name</code>) or as string (" <code>column_name</code> "). <code>name</code> will be ignored when a data frame is returned.
extract	String, indicating which element will be extracted when <code>select</code> matches multiple variables. Can be <code>"all"</code> (the default) to return all matched variables, <code>"first"</code> or <code>"last"</code> to return the first or last match, or <code>"odd"</code> and <code>"even"</code> to return all odd-numbered or even-numbered matches. Note that <code>"first"</code> or <code>"last"</code> return a vector (unless <code>as_data_frame = TRUE</code>), while <code>"all"</code> can return a vector (if only one match was found) <i>or</i> a data frame (for more than one match). Type safe return values are only possible when <code>extract</code> is <code>"first"</code> or <code>"last"</code> (will always return a vector) or when <code>as_data_frame = TRUE</code> (always returns a data frame).
as_data_frame	Logical, if <code>TRUE</code> , will always return a data frame, even if only one variable was matched. If <code>FALSE</code> , either returns a vector or a data frame. See <code>extract</code> for details.
ignore_case	Logical, if <code>TRUE</code> and when one of the select-helpers or a regular expression is used in <code>select</code> , ignores lower/upper case in the search pattern when matching against variable names.
regex	Logical, if <code>TRUE</code> , the search pattern from <code>select</code> will be treated as regular expression. When <code>regex = TRUE</code> , <code>select</code> <i>must</i> be a character string (or a variable containing a character string) and is not allowed to be one of the supported select-helpers or a character vector of length <code>> 1</code> . <code>regex = TRUE</code> is comparable to using one of the two select-helpers, <code>select = contains("")</code> or <code>select = regex("")</code> , however, since the select-helpers may not work when called from inside other functions (see 'Details'), this argument may be used as workaround.
verbose	Toggle warnings.

Details

`data_extract()` can be used to select multiple variables or pull a single variable from a data frame. Thus, the return value is by default not type safe - `data_extract()` either returns a vector or a data frame.

Extracting single variables (vectors): When `select` is the name of a single column, or when `select` only matches one column, a vector is returned. A single variable is also returned when `extract` is either `"first"` or `"last"`. Setting `as_data_frame` to `TRUE` overrides this behaviour and `always` returns a data frame.

Extracting a data frame of variables: When `select` is a character vector containing more than one column name (or a numeric vector with more than one valid column indices), or when `select` uses one of the supported `select`-helpers that match multiple columns, a data frame is returned. Setting `as_data_frame` to `TRUE` *always* returns a data frame.

Value

A vector (or a data frame) containing the extracted element, or `NULL` if no matching variable was found.

Examples

```
# single variable
data_extract(mtcars, cyl, name = gear)
data_extract(mtcars, "cyl", name = gear)
data_extract(mtcars, -1, name = gear)
data_extract(mtcars, cyl, name = 0)
data_extract(mtcars, cyl, name = "row.names")

# selecting multiple variables
head(data_extract(iris, starts_with("Sepal")))
head(data_extract(iris, ends_with("Width")))
head(data_extract(iris, 2:4))

# select first of multiple variables
data_extract(iris, starts_with("Sepal"), extract = "first")

# select first of multiple variables, return as data frame
head(data_extract(iris, starts_with("Sepal"), extract = "first", as_data_frame = TRUE))
```

data_group

Create a grouped data frame

Description

This function is comparable to `dplyr::group_by()`, but just following the **datawizard** function design. `data_ungroup()` removes the grouping information from a grouped data frame.

Usage

```
data_group(
  data,
  select = NULL,
  exclude = NULL,
```

```

    ignore_case = FALSE,
    regex = FALSE,
    verbose = TRUE,
    ...
)

data_ungroup(data, verbose = TRUE, ...)

```

Arguments

data	A data frame
select	<p>Variables that will be included when performing the required tasks. Can be either</p> <ul style="list-style-type: none"> • a variable specified as a literal variable name (e.g., <code>column_name</code>), • a string with the variable name (e.g., <code>"column_name"</code>), or a character vector of variable names (e.g., <code>c("col1", "col2", "col3")</code>), • a formula with variable names (e.g., <code>~column_1 + column_2</code>), • a vector of positive integers, giving the positions counting from the left (e.g. 1 or <code>c(1, 3, 5)</code>), • a vector of negative integers, giving the positions counting from the right (e.g., <code>-1</code> or <code>-1:-3</code>), • one of the following select-helpers: <code>starts_with()</code>, <code>ends_with()</code>, <code>contains()</code>, a range using <code>:</code> or <code>regex("")</code>. <code>starts_with()</code>, <code>ends_with()</code>, and <code>contains()</code> accept several patterns, e.g. <code>starts_with("Sep", "Petal")</code>. • or a function testing for logical conditions, e.g. <code>is.numeric()</code> (or <code>is.numeric</code>), or any user-defined function that selects the variables for which the function returns TRUE (like: <code>foo <- function(x) mean(x) > 3</code>), • ranges specified via literal variable names, select-helpers (except <code>regex()</code>) and (user-defined) functions can be negated, i.e. return non-matching elements, when prefixed with a <code>-</code>, e.g. <code>-ends_with("")</code>, <code>-is.numeric</code> or <code>-(Sepal.Width:Petal.Length)</code>. Note: Negation means that matches are <i>excluded</i>, and thus, the <code>exclude</code> argument can be used alternatively. For instance, <code>select=-ends_with("Length")</code> (with <code>-</code>) is equivalent to <code>exclude=ends_with("Length")</code> (no <code>-</code>). In case negation should not work as expected, use the <code>exclude</code> argument instead. <p>If NULL, selects all columns. Patterns that found no matches are silently ignored, e.g. <code>find_columns(iris, select = c("Species", "Test"))</code> will just return "Species".</p>
exclude	See <code>select</code> , however, column names matched by the pattern from <code>exclude</code> will be excluded instead of selected. If NULL (the default), excludes no columns.
ignore_case	Logical, if TRUE and when one of the select-helpers or a regular expression is used in <code>select</code> , ignores lower/upper case in the search pattern when matching against variable names.
regex	Logical, if TRUE, the search pattern from <code>select</code> will be treated as regular expression. When <code>regex = TRUE</code> , <code>select</code> <i>must</i> be a character string (or a variable containing a character string) and is not allowed to be one of the supported

select-helpers or a character vector of length > 1. `regex = TRUE` is comparable to using one of the two select-helpers, `select = contains("")` or `select = regex("")`, however, since the select-helpers may not work when called from inside other functions (see 'Details'), this argument may be used as workaround.

`verbose` Toggle warnings.

`...` Arguments passed down to other functions. Mostly not used yet.

Value

A grouped data frame, i.e. a data frame with additional information about the grouping structure saved as attributes.

Examples

```
data(efc)
suppressPackageStartupMessages(library(poorman, quietly = TRUE))

# total mean
efc %>%
  summarize(mean_hours = mean(c12hour, na.rm = TRUE))

# mean by educational level
efc %>%
  data_group(c172code) %>%
  summarize(mean_hours = mean(c12hour, na.rm = TRUE))
```

data_match

Return filtered or sliced data frame, or row indices

Description

Return a filtered (or sliced) data frame or row indices of a data frame that match a specific condition. `data_filter()` works like `data_match()`, but works with logical expressions or row indices of a data frame to specify matching conditions.

Usage

```
data_match(x, to, match = "and", return_indices = FALSE, drop_na = TRUE, ...)

data_filter(x, filter, ...)
```

Arguments

x	A data frame.
to	A data frame matching the specified conditions. Note that if match is a value other than "and", the original row order might be changed. See 'Details'.
match	String, indicating with which logical operation matching conditions should be combined. Can be "and" (or "&"), "or" (or " ") or "not" (or "!").
return_indices	Logical, if FALSE, return the vector of rows that can be used to filter the original data frame. If FALSE (default), returns directly the filtered data frame instead of the row indices.
drop_na	Logical, if TRUE, missing values (NAs) are removed before filtering the data. This is the default behaviour, however, sometimes when row indices are requested (i.e. return_indices=TRUE), it might be useful to preserve NA values, so returned row indices match the row indices of the original data frame.
...	Not used.
filter	A logical expression indicating which rows to keep, or a numeric vector indicating the row indices of rows to keep. Can also be a string representation of a logical expression. e.g. filter = "x > 4". This might be useful when used in packages to avoid defining undefined global variables.

Details

For data_match(), if match is either "or" or "not", the original row order from x might be changed. If preserving row order is required, use data_filter() instead.

```
# mimics subset() behaviour, preserving original row order
head(data_filter(mtcars[c("mpg", "vs", "am")], vs == 0 | am == 1))
#>           mpg vs am
#> Mazda RX4      21.0 0 1
#> Mazda RX4 Wag  21.0 0 1
#> Datsun 710     22.8 1 1
#> Hornet Sportabout 18.7 0 0
#> Duster 360    14.3 0 0
#> Merc 450SE    16.4 0 0

# re-sorting rows
head(data_match(mtcars[c("mpg", "vs", "am")],
                data.frame(vs = 0, am = 1),
                match = "or"))
#>           mpg vs am
#> Mazda RX4      21.0 0 1
#> Mazda RX4 Wag  21.0 0 1
#> Hornet Sportabout 18.7 0 0
#> Duster 360    14.3 0 0
#> Merc 450SE    16.4 0 0
#> Merc 450SL    17.3 0 0
```

While `data_match()` works with data frames to match conditions against, `data_filter()` is basically a wrapper around `subset(subset = <filter>)`. However, unlike `subset()`, it preserves label attributes and is useful when working with labelled data.

Value

A filtered data frame, or the row indices that match the specified configuration.

See Also

- Functions to rename stuff: `data_rename()`, `data_rename_rows()`, `data_addprefix()`, `data_addsuffix()`
- Functions to reorder or remove columns: `data_reorder()`, `data_relocate()`, `data_remove()`
- Functions to reshape, pivot or rotate data frames: `data_to_long()`, `data_to_wide()`, `data_rotate()`
- Functions to recode data: `rescale()`, `reverse()`, `categorize()`, `recode_values()`, `slide()`
- Functions to standardize, normalize, rank-transform: `center()`, `standardize()`, `normalize()`, `ranktransform()`, `winsorize()`
- Split and merge data frames: `data_partition()`, `data_merge()`
- Functions to find or select columns: `data_select()`, `data_find()`
- Functions to filter rows: `data_match()`, `data_filter()`

Examples

```
# styler: off
data_match(mtcars, data.frame(vs = 0, am = 1))
data_match(mtcars, data.frame(vs = 0, am = c(0, 1)))

# observations where "vs" is NOT 0 AND "am" is NOT 1
data_match(mtcars, data.frame(vs = 0, am = 1), match = "not")
# equivalent to
data_filter(mtcars, vs != 0 & am != 1)

# observations where EITHER "vs" is 0 OR "am" is 1
data_match(mtcars, data.frame(vs = 0, am = 1), match = "or")
# equivalent to
data_filter(mtcars, vs == 0 | am == 1)

# slice data frame by row indices
data_filter(mtcars, 5:10)

# Define a custom function containing data_filter() and pass variable names
# to it using curly brackets
my_filter <- function(data, variable) {
  data_filter(data, {variable} <= 20)
}
my_filter(mtcars, "mpg")

# Pass complete filter-condition as string
my_filter <- function(data, condition) {
  data_filter(data, {condition})
}
```

```

}
my_filter(mtcars, "am != 0")

# string can also be used directly as argument
data_filter(mtcars, "am != 0")
# styler: on

```

data_merge

Merge (join) two data frames, or a list of data frames

Description

Merge (join) two data frames, or a list of data frames. However, unlike base R's `merge()`, `data_merge()` offers a few more methods to join data frames, and it does not drop data frame nor column attributes.

Usage

```

data_merge(x, ...)

data_join(x, ...)

## S3 method for class 'data.frame'
data_merge(x, y, join = "left", by = NULL, id = NULL, verbose = TRUE, ...)

## S3 method for class 'list'
data_merge(x, join = "left", by = NULL, id = NULL, verbose = TRUE, ...)

```

Arguments

<code>x, y</code>	A data frame to merge. <code>x</code> may also be a list of data frames that will be merged. Note that the list-method has no <code>y</code> argument.
<code>...</code>	Not used.
<code>join</code>	Character vector, indicating the method of joining the data frames. Can be "full", "left" (default), "right", "inner", "anti", "semi" or "bind". See details below.
<code>by</code>	Specifications of the columns used for merging.
<code>id</code>	Optional name for ID column that will be created to indicate the source data frames for appended rows. Only applies if <code>join = "bind"</code> .
<code>verbose</code>	Toggle warnings.

Details

Merging data frames: Merging data frames is performed by adding rows (cases), columns (variables) or both from the source data frame (`y`) to the target data frame (`x`). This usually requires one or more variables which are included in both data frames and that are used for merging, typically indicated with the `by` argument. When `by` contains a variable present in both data frames, cases are matched and filtered by identical values of `by` in `x` and `y`.

Left- and right-joins: Left- and right joins usually don't add new rows (cases), but only new columns (variables) for existing cases in *x*. For `join = "left"` or `join = "right"` to work, *by* *must* indicate one or more columns that are included in both data frames. For `join = "left"`, if *by* is an identifier variable, which is included in both *x* and *y*, all variables from *y* are copied to *x*, but only those cases from *y* that have matching values in their identifier variable in *x* (i.e. all cases in *x* that are also found in *y* get the related values from the new columns in *y*). If there is no match between identifiers in *x* and *y*, the copied variable from *y* will get a NA value for this particular case. Other variables that occur both in *x* and *y*, but are not used as identifiers (with *by*), will be renamed to avoid multiple identical variable names. Cases in *y* where values from the identifier have no match in *x*'s identifier are removed. `join = "right"` works in a similar way as `join = "left"`, just that only cases from *x* that have matching values in their identifier variable in *y* are chosen.

In base R, these are equivalent to `merge(x, y, all.x = TRUE)` and `merge(x, y, all.y = TRUE)`.

Full joins: Full joins copy all cases from *y* to *x*. For matching cases in both data frames, values for new variables are copied from *y* to *x*. For cases in *y* not present in *x*, these will be added as new rows to *x*. Thus, full joins not only add new columns (variables), but also might add new rows (cases).

In base R, this is equivalent to `merge(x, y, all = TRUE)`.

Inner joins: Inner joins merge two data frames, however, only those rows (cases) are kept that are present in both data frames. Thus, inner joins usually add new columns (variables), but also remove rows (cases) that only occur in one data frame.

In base R, this is equivalent to `merge(x, y)`.

Binds: `join = "bind"` row-binds the complete second data frame *y* to *x*. Unlike simple `rbind()`, which requires the same columns for both data frames, `join = "bind"` will bind shared columns from *y* to *x*, and add new columns from *y* to *x*.

Value

A merged data frame.

See Also

- Functions to rename stuff: `data_rename()`, `data_rename_rows()`, `data_addprefix()`, `data_addsuffix()`
- Functions to reorder or remove columns: `data_reorder()`, `data_relocate()`, `data_remove()`
- Functions to reshape, pivot or rotate data frames: `data_to_long()`, `data_to_wide()`, `data_rotate()`
- Functions to recode data: `rescale()`, `reverse()`, `categorize()`, `recode_values()`, `slide()`
- Functions to standardize, normalize, rank-transform: `center()`, `standardize()`, `normalize()`, `ranktransform()`, `winsorize()`
- Split and merge data frames: `data_partition()`, `data_merge()`
- Functions to find or select columns: `data_select()`, `data_find()`
- Functions to filter rows: `data_match()`, `data_filter()`

Examples

```

x <- data.frame(a = 1:3, b = c("a", "b", "c"), c = 5:7, id = 1:3)
y <- data.frame(c = 6:8, d = c("f", "g", "h"), e = 100:102, id = 2:4)

x
y

# "by" will default to all shared columns, i.e. "c" and "id". new columns
# "d" and "e" will be copied from "y" to "x", but there are only two cases
# in "x" that have the same values for "c" and "id" in "y". only those cases
# have values in the copied columns, the other case gets "NA".
data_merge(x, y, join = "left")

# we change the id-value here
x <- data.frame(a = 1:3, b = c("a", "b", "c"), c = 5:7, id = 1:3)
y <- data.frame(c = 6:8, d = c("f", "g", "h"), e = 100:102, id = 3:5)

x
y

# no cases in "y" have the same matching "c" and "id" as in "x", thus
# copied variables from "y" to "x" copy no values, all get NA.
data_merge(x, y, join = "left")

# one case in "y" has a match in "id" with "x", thus values for this
# case from the remaining variables in "y" are copied to "x", all other
# values (cases) in those remaining variables get NA
data_merge(x, y, join = "left", by = "id")

data(mtcars)
x <- mtcars[1:5, 1:3]
y <- mtcars[28:32, 4:6]

# add ID common column
x$id <- 1:5
y$id <- 3:7

# left-join, add new variables and copy values from y to x,
# where "id" values match
data_merge(x, y)

# right-join, add new variables and copy values from x to y,
# where "id" values match
data_merge(x, y, join = "right")

# full-join
data_merge(x, y, join = "full")

data(mtcars)
x <- mtcars[1:5, 1:3]

```

```

y <- mtcars[28:32, c(1, 4:5)]

# add ID common column
x$id <- 1:5
y$id <- 3:7

# left-join, no matching rows (because columns "id" and "disp" are used)
# new variables get all NA values
data_merge(x, y)

# one common value in "mpg", so one row from y is copied to x
data_merge(x, y, by = "mpg")

# only keep rows with matching values in by-column
data_merge(x, y, join = "semi", by = "mpg")

# only keep rows with non-matching values in by-column
data_merge(x, y, join = "anti", by = "mpg")

# merge list of data frames. can be of different rows
x <- mtcars[1:5, 1:3]
y <- mtcars[28:31, 3:5]
z <- mtcars[11:18, c(1, 3:4, 6:8)]
x$id <- 1:5
y$id <- 4:7
z$id <- 3:10
data_merge(list(x, y, z), join = "bind", by = "id", id = "source")

```

data_partition

Partition data

Description

Creates data partitions (for instance, a training and a test set) based on a data frame that can also be stratified (i.e., evenly spread a given factor) using the `group` argument.

Usage

```

data_partition(
  data,
  proportion = 0.7,
  group = NULL,
  seed = NULL,
  row_id = ".row_id",
  verbose = TRUE,
  training_proportion = proportion,
  ...
)

```

Arguments

data	A data frame, or an object that can be coerced to a data frame.
proportion	Scalar (between 0 and 1) or numeric vector, indicating the proportion(s) of the training set(s). The sum of proportion must not be greater than 1. The remaining part will be used for the test set.
group	A character vector indicating the name(s) of the column(s) used for stratified partitioning.
seed	A random number generator seed. Enter an integer (e.g. 123) so that the random sampling will be the same each time you run the function.
row_id	Character string, indicating the name of the column that contains the row-id's.
verbose	Toggle messages and warnings.
training_proportion	Deprecated, please use proportion.
...	Other arguments passed to or from other functions.

Value

A list of data frames. The list includes one training set per given proportion and the remaining data as test set. List elements of training sets are named after the given proportions (e.g., `$p_0.7`), the test set is named `$test`.

See Also

- Functions to rename stuff: [data_rename\(\)](#), [data_rename_rows\(\)](#), [data_addprefix\(\)](#), [data_addsuffix\(\)](#)
- Functions to reorder or remove columns: [data_reorder\(\)](#), [data_relocate\(\)](#), [data_remove\(\)](#)
- Functions to reshape, pivot or rotate data frames: [data_to_long\(\)](#), [data_to_wide\(\)](#), [data_rotate\(\)](#)
- Functions to recode data: [rescale\(\)](#), [reverse\(\)](#), [categorize\(\)](#), [recode_values\(\)](#), [slide\(\)](#)
- Functions to standardize, normalize, rank-transform: [center\(\)](#), [standardize\(\)](#), [normalize\(\)](#), [ranktransform\(\)](#), [winsorize\(\)](#)
- Split and merge data frames: [data_partition\(\)](#), [data_merge\(\)](#)
- Functions to find or select columns: [data_select\(\)](#), [data_find\(\)](#)
- Functions to filter rows: [data_match\(\)](#), [data_filter\(\)](#)

Examples

```
data(iris)
out <- data_partition(iris, proportion = 0.9)
out$test
nrow(out$p_0.9)

# Stratify by group (equal proportions of each species)
out <- data_partition(iris, proportion = 0.9, group = "Species")
out$test

# Create multiple partitions
```

```

out <- data_partition(iris, proportion = c(0.3, 0.3))
lapply(out, head)

# Create multiple partitions, stratified by group - 30% equally sampled
# from species in first training set, 50% in second training set and
# remaining 20% equally sampled from each species in test set.
out <- data_partition(iris, proportion = c(0.3, 0.5), group = "Species")
lapply(out, function(i) table(i$Species))

```

data_peek

Peek at values and type of variables in a data frame

Description

This function creates a table a data frame, showing all column names, variable types and the first values (as many as fit into the screen).

Usage

```

data_peek(x, ...)

## S3 method for class 'data.frame'
data_peek(
  x,
  select = NULL,
  exclude = NULL,
  ignore_case = FALSE,
  regex = FALSE,
  width = NULL,
  verbose = TRUE,
  ...
)

```

Arguments

x	A data frame.
...	not used.
select	Variables that will be included when performing the required tasks. Can be either <ul style="list-style-type: none"> • a variable specified as a literal variable name (e.g., column_name), • a string with the variable name (e.g., "column_name"), or a character vector of variable names (e.g., c("col1", "col2", "col3")), • a formula with variable names (e.g., ~column_1 + column_2), • a vector of positive integers, giving the positions counting from the left (e.g. 1 or c(1, 3, 5)),

- a vector of negative integers, giving the positions counting from the right (e.g., -1 or -1:-3),
- one of the following select-helpers: starts_with(), ends_with(), contains(), a range using : or regex(""). starts_with(), ends_with(), and contains() accept several patterns, e.g starts_with("Sep", "Petal").
- or a function testing for logical conditions, e.g. is.numeric() (or is.numeric), or any user-defined function that selects the variables for which the function returns TRUE (like: foo <- function(x) mean(x) > 3),
- ranges specified via literal variable names, select-helpers (except regex()) and (user-defined) functions can be negated, i.e. return non-matching elements, when prefixed with a -, e.g. -ends_with(""), -is.numeric or -(Sepal.Width:Petal.Length). **Note:** Negation means that matches are *excluded*, and thus, the exclude argument can be used alternatively. For instance, select=-ends_with("Length") (with -) is equivalent to exclude=ends_with("Length") (no -). In case negation should not work as expected, use the exclude argument instead.

If NULL, selects all columns. Patterns that found no matches are silently ignored, e.g. find_columns(iris, select = c("Species", "Test")) will just return "Species".

exclude	See select, however, column names matched by the pattern from exclude will be excluded instead of selected. If NULL (the default), excludes no columns.
ignore_case	Logical, if TRUE and when one of the select-helpers or a regular expression is used in select, ignores lower/upper case in the search pattern when matching against variable names.
regex	Logical, if TRUE, the search pattern from select will be treated as regular expression. When regex = TRUE, select <i>must</i> be a character string (or a variable containing a character string) and is not allowed to be one of the supported select-helpers or a character vector of length > 1. regex = TRUE is comparable to using one of the two select-helpers, select = contains("") or select = regex(""), however, since the select-helpers may not work when called from inside other functions (see 'Details'), this argument may be used as workaround.
width	Maximum width of line length to display. If NULL, width will be determined using options()\$width.
verbose	Toggle warnings.

Value

A data frame with three columns, containing information about the name, type and first values of the input data frame.

Note

To show only specific or a limited number of variables, use the select argument, e.g. select = 1:5 to show only the first five variables.

Examples

```
data(efc)
data_peek(efc)
# show variables two to four
data_peek(efc, select = 2:4)
```

data_read

Read (import) data files from various sources

Description

This functions imports data from various file types. It is a small wrapper around `haven::read_spss()`, `haven::read_stata()`, `haven::read_sas()`, `readxl::read_excel()` and `data.table::fread()` resp. `readr::read_delim()` (the latter if package **data.table** is not installed). Thus, supported file types for importing data are data files from SPSS, SAS or Stata, Excel files or text files (like '.csv' files). All other file types are passed to `rio::import()`. `data_write()` works in a similar way.

Usage

```
data_read(
  path,
  path_catalog = NULL,
  encoding = NULL,
  convert_factors = TRUE,
  verbose = TRUE,
  ...
)

data_write(
  data,
  path,
  delimiter = ",",
  convert_factors = FALSE,
  save_labels = FALSE,
  verbose = TRUE,
  ...
)
```

Arguments

path	Character string, the file path to the data file.
path_catalog	Character string, path to the catalog file. Only relevant for SAS data files.
encoding	The character encoding used for the file. Usually not needed.
convert_factors	If TRUE (default), numeric variables, where all values have a value label, are assumed to be categorical and converted into factors. If FALSE, no variable types

are guessed and no conversion of numeric variables into factors will be performed. See also section 'Differences to other packages'. For `data_write()`, this argument only applies to the text (e.g. `.txt` or `.csv`) or spreadsheet file formats (like `.xlsx`). Converting to factors might be useful for these formats because labelled numeric variables are then converted into factors and exported as character columns - else, value labels would be lost and only numeric values are written to the file.

<code>verbose</code>	Toggle warnings and messages.
<code>...</code>	Arguments passed to the related <code>read_*</code> () or <code>write_*</code> () functions.
<code>data</code>	The data frame that should be written to a file.
<code>delimiter</code>	For CSV-files, specifies the delimiter. Defaults to <code>,</code> , but in particular in European regions, <code>;</code> might be a useful alternative, especially when exported CSV-files should be opened in Excel.
<code>save_labels</code>	Only applies to CSV files. If <code>TRUE</code> , value and variable labels (if any) will be saved as additional CSV file. This file has the same file name as the exported CSV file, but includes a <code>"_labels"</code> suffix (i.e. when the file name is <code>"mydat.csv"</code> , the additional file with value and variable labels is named <code>"mydat_labels.csv"</code>).

Value

A data frame.

Supported file types

- `data_read()` is a wrapper around the **haven**, **data.table**, **readr** **readxl** and **rio** packages. Currently supported file types are `.txt`, `.csv`, `.xls`, `.xlsx`, `.sav`, `.por`, `.dta` and `.sas` (and related files). All other file types are passed to `rio::import()`.
- `data_write()` is a wrapper around **haven**, **readr** and **rio** packages, and supports writing files into all formats supported by these packages.

Compressed files (zip) and URLs

`data_read()` can also read the above mentioned files from URLs or from inside zip-compressed files. Thus, `path` can also be a URL to a file like `"http://www.url.com/file.csv"`. When `path` points to a zip-compressed file, and there are multiple files inside the zip-archive, then the first supported file is extracted and loaded.

General behaviour

`data_read()` detects the appropriate `read_*`() function based on the file-extension of the data file. Thus, in most cases it should be enough to only specify the `path` argument. However, if more control is needed, all arguments in `...` are passed down to the related `read_*`() function. The same applies to `data_write()`, i.e. based on the file extension provided in `path`, the appropriate `write_*`() function is used automatically.

SPSS specific behaviour

`data_read()` does *not* import user-defined ("tagged") NA values from SPSS, i.e. argument `user_na` is always set to `FALSE` when importing SPSS data with the **haven** package. Use `convert_to_na()` to define missing values in the imported data, if necessary. Furthermore, `data_write()` compresses SPSS files by default. If this causes problems with (older) SPSS versions, use `compress = "none"`, for example `data_write(data, "myfile.sav", compress = "none")`.

Differences to other packages that read foreign data formats

`data_read()` is most comparable to `rio::import()`. For data files from SPSS, SAS or Stata, which support labelled data, variables are converted into their most appropriate type. The major difference to `rio::import()` is that `data_read()` automatically converts fully labelled numeric variables into factors, where imported value labels will be set as factor levels. If a numeric variable has *no* value labels or less value labels than values, it is not converted to factor. In this case, value labels are preserved as "labels" attribute. Character vectors are preserved. Use `convert_factors = FALSE` to remove the automatic conversion of numeric variables to factors.

data_relocate	<i>Relocate (reorder) columns of a data frame</i>
---------------	---

Description

`data_relocate()` will reorder columns to specific positions, indicated by before or after. `data_reorder()` will instead move selected columns to the beginning of a data frame. Finally, `data_remove()` removes columns from a data frame. All functions support select-helpers that allow flexible specification of a search pattern to find matching columns, which should be reordered or removed.

Usage

```
data_relocate(  
  data,  
  select,  
  before = NULL,  
  after = NULL,  
  ignore_case = FALSE,  
  regex = FALSE,  
  verbose = TRUE,  
  ...  
)
```

```
data_reorder(  
  data,  
  select,  
  exclude = NULL,  
  ignore_case = FALSE,  
  regex = FALSE,  
  verbose = TRUE,
```

```

    ...
  )

data_remove(
  data,
  select = NULL,
  exclude = NULL,
  ignore_case = FALSE,
  regex = FALSE,
  verbose = FALSE,
  ...
)

```

Arguments

data	A data frame.
select	<p>Variables that will be included when performing the required tasks. Can be either</p> <ul style="list-style-type: none"> • a variable specified as a literal variable name (e.g., column_name), • a string with the variable name (e.g., "column_name"), or a character vector of variable names (e.g., c("col1", "col2", "col3")), • a formula with variable names (e.g., ~column_1 + column_2), • a vector of positive integers, giving the positions counting from the left (e.g. 1 or c(1, 3, 5)), • a vector of negative integers, giving the positions counting from the right (e.g., -1 or -1:-3), • one of the following select-helpers: starts_with(), ends_with(), contains(), a range using : or regex(""). starts_with(), ends_with(), and contains() accept several patterns, e.g starts_with("Sep", "Petal"). • or a function testing for logical conditions, e.g. is.numeric() (or is.numeric), or any user-defined function that selects the variables for which the function returns TRUE (like: foo <- function(x) mean(x) > 3), • ranges specified via literal variable names, select-helpers (except regex()) and (user-defined) functions can be negated, i.e. return non-matching elements, when prefixed with a -, e.g. -ends_with(""), -is.numeric or -(Sepal.Width:Petal.Length). Note: Negation means that matches are <i>excluded</i>, and thus, the exclude argument can be used alternatively. For instance, select=-ends_with("Length") (with -) is equivalent to exclude=ends_with("Length") (no -). In case negation should not work as expected, use the exclude argument instead. <p>If NULL, selects all columns. Patterns that found no matches are silently ignored, e.g. find_columns(iris, select = c("Species", "Test")) will just return "Species".</p>
before, after	<p>Destination of columns. Supplying neither will move columns to the left-hand side; specifying both is an error. Can be a character vector, indicating the name of the destination column, or a numeric value, indicating the index number of the destination column. If -1, will be added before or after the last column.</p>

ignore_case	Logical, if TRUE and when one of the select-helpers or a regular expression is used in select, ignores lower/upper case in the search pattern when matching against variable names.
regex	Logical, if TRUE, the search pattern from select will be treated as regular expression. When regex = TRUE, select <i>must</i> be a character string (or a variable containing a character string) and is not allowed to be one of the supported select-helpers or a character vector of length > 1. regex = TRUE is comparable to using one of the two select-helpers, select = contains("") or select = regex(""), however, since the select-helpers may not work when called from inside other functions (see 'Details'), this argument may be used as workaround.
verbose	Toggle warnings.
...	Arguments passed down to other functions. Mostly not used yet.
exclude	See select, however, column names matched by the pattern from exclude will be excluded instead of selected. If NULL (the default), excludes no columns.

Value

A data frame with reordered columns.

See Also

- Functions to rename stuff: [data_rename\(\)](#), [data_rename_rows\(\)](#), [data_addprefix\(\)](#), [data_addsuffix\(\)](#)
- Functions to reorder or remove columns: [data_reorder\(\)](#), [data_relocate\(\)](#), [data_remove\(\)](#)
- Functions to reshape, pivot or rotate data frames: [data_to_long\(\)](#), [data_to_wide\(\)](#), [data_rotate\(\)](#)
- Functions to recode data: [rescale\(\)](#), [reverse\(\)](#), [categorize\(\)](#), [recode_values\(\)](#), [slide\(\)](#)
- Functions to standardize, normalize, rank-transform: [center\(\)](#), [standardize\(\)](#), [normalize\(\)](#), [ranktransform\(\)](#), [winsorize\(\)](#)
- Split and merge data frames: [data_partition\(\)](#), [data_merge\(\)](#)
- Functions to find or select columns: [data_select\(\)](#), [data_find\(\)](#)
- Functions to filter rows: [data_match\(\)](#), [data_filter\(\)](#)

Examples

```
# Reorder columns
head(data_relocate(iris, select = "Species", before = "Sepal.Length"))
head(data_relocate(iris, select = "Species", before = "Sepal.Width"))
head(data_relocate(iris, select = "Sepal.Width", after = "Species"))
# which is same as
head(data_relocate(iris, select = "Sepal.Width", after = -1))

# Reorder multiple columns
head(data_relocate(iris, select = c("Species", "Petal.Length"), after = "Sepal.Width"))
# which is same as
head(data_relocate(iris, select = c("Species", "Petal.Length"), after = 2))

# Reorder columns
head(data_reorder(iris, c("Species", "Sepal.Length")))
```

```
# Remove columns
head(data_remove(iris, "Sepal.Length"))
head(data_remove(iris, starts_with("Sepal")))
```

data_restoretype	<i>Restore the type of columns according to a reference data frame</i>
------------------	--

Description

Restore the type of columns according to a reference data frame

Usage

```
data_restoretype(data, reference = NULL, ...)
```

Arguments

data	A data frame to pivot.
reference	A reference data frame from which to find the correct column types. If NULL, each column is converted to numeric if it doesn't generate NAs. For example, <code>c("1", "2")</code> can be converted to numeric but not <code>c("Sepal.Length")</code> .
...	Currently not used.

Value

A data frame with columns whose types have been restored based on the reference data frame.

Examples

```
data <- data.frame(
  Sepal.Length = c("1", "3", "2"),
  Species = c("setosa", "versicolor", "setosa"),
  New = c("1", "3", "4")
)

fixed <- data_restoretype(data, reference = iris)
summary(fixed)
```

data_rotate	<i>Rotate a data frame</i>
-------------	----------------------------

Description

This function rotates a data frame, i.e. columns become rows and vice versa. It's the equivalent of using `t()` but restores the `data.frame` class, preserves attributes and prints a warning if the data type is modified (see example).

Usage

```
data_rotate(data, rownames = NULL, colnames = FALSE, verbose = TRUE)
```

```
data_transpose(data, rownames = NULL, colnames = FALSE, verbose = TRUE)
```

Arguments

data	A data frame.
rownames	Character vector (optional). If not NULL, the data frame's rownames will be added as (first) column to the output, with rownames being the name of this column.
colnames	Logical or character vector (optional). If TRUE, the values of the first column in x will be used as column names in the rotated data frame. If a character vector, values from that column are used as column names.
verbose	Toggle warnings.

Value

A (rotated) data frame.

See Also

- Functions to rename stuff: [data_rename\(\)](#), [data_rename_rows\(\)](#), [data_addprefix\(\)](#), [data_addsuffix\(\)](#)
- Functions to reorder or remove columns: [data_reorder\(\)](#), [data_relocate\(\)](#), [data_remove\(\)](#)
- Functions to reshape, pivot or rotate data frames: [data_to_long\(\)](#), [data_to_wide\(\)](#), [data_rotate\(\)](#)
- Functions to recode data: [rescale\(\)](#), [reverse\(\)](#), [categorize\(\)](#), [recode_values\(\)](#), [slide\(\)](#)
- Functions to standardize, normalize, rank-transform: [center\(\)](#), [standardize\(\)](#), [normalize\(\)](#), [ranktransform\(\)](#), [winsorize\(\)](#)
- Split and merge data frames: [data_partition\(\)](#), [data_merge\(\)](#)
- Functions to find or select columns: [data_select\(\)](#), [data_find\(\)](#)
- Functions to filter rows: [data_match\(\)](#), [data_filter\(\)](#)

Examples

```
x <- mtcars[1:3, 1:4]

x

data_rotate(x)
data_rotate(x, rownames = "property")

# use values in 1. column as column name
data_rotate(x, colnames = TRUE)
data_rotate(x, rownames = "property", colnames = TRUE)

# use either first column or specific column for column names
x <- data.frame(a = 1:5, b = 11:15, c = 21:25)
data_rotate(x, colnames = TRUE)
data_rotate(x, colnames = "c")
```

data_tabulate

Create frequency tables of variables

Description

This function creates frequency tables of variables, including the number of levels/values as well as the distribution of raw, valid and cumulative percentages.

Usage

```
data_tabulate(x, ...)

## Default S3 method:
data_tabulate(x, drop_levels = FALSE, name = NULL, verbose = TRUE, ...)

## S3 method for class 'data.frame'
data_tabulate(
  x,
  select = NULL,
  exclude = NULL,
  ignore_case = FALSE,
  regex = FALSE,
  collapse = FALSE,
  drop_levels = FALSE,
  verbose = TRUE,
  ...
)
```

Arguments

x	A (grouped) data frame, a vector or factor.
...	not used.
drop_levels	Logical, if TRUE, factor levels that do not occur in the data are included in the table (with frequency of zero), else unused factor levels are dropped from the frequency table.
name	Optional character string, which includes the name that is used for printing.
verbose	Toggle warnings.
select	<p>Variables that will be included when performing the required tasks. Can be either</p> <ul style="list-style-type: none"> • a variable specified as a literal variable name (e.g., column_name), • a string with the variable name (e.g., "column_name"), or a character vector of variable names (e.g., c("col1", "col2", "col3")), • a formula with variable names (e.g., ~column_1 + column_2), • a vector of positive integers, giving the positions counting from the left (e.g. 1 or c(1, 3, 5)), • a vector of negative integers, giving the positions counting from the right (e.g., -1 or -1:-3), • one of the following select-helpers: starts_with(), ends_with(), contains(), a range using : or regex(""). starts_with(), ends_with(), and contains() accept several patterns, e.g starts_with("Sep", "Petal"). • or a function testing for logical conditions, e.g. is.numeric() (or is.numeric), or any user-defined function that selects the variables for which the function returns TRUE (like: foo <- function(x) mean(x) > 3), • ranges specified via literal variable names, select-helpers (except regex()) and (user-defined) functions can be negated, i.e. return non-matching elements, when prefixed with a -, e.g. -ends_with(""), -is.numeric or -(Sepal.Width:Petal.Length). Note: Negation means that matches are <i>excluded</i>, and thus, the exclude argument can be used alternatively. For instance, select=-ends_with("Length") (with -) is equivalent to exclude=ends_with("Length") (no -). In case negation should not work as expected, use the exclude argument instead. <p>If NULL, selects all columns. Patterns that found no matches are silently ignored, e.g. find_columns(iris, select = c("Species", "Test")) will just return "Species".</p>
exclude	See select, however, column names matched by the pattern from exclude will be excluded instead of selected. If NULL (the default), excludes no columns.
ignore_case	Logical, if TRUE and when one of the select-helpers or a regular expression is used in select, ignores lower/upper case in the search pattern when matching against variable names.
regex	Logical, if TRUE, the search pattern from select will be treated as regular expression. When regex = TRUE, select <i>must</i> be a character string (or a variable containing a character string) and is not allowed to be one of the supported

select-helpers or a character vector of length > 1. `regex = TRUE` is comparable to using one of the two select-helpers, `select = contains("")` or `select = regex("")`, however, since the select-helpers may not work when called from inside other functions (see 'Details'), this argument may be used as workaround.

`collapse` Logical, if TRUE collapses multiple tables into one larger table for printing. This affects only printing, not the returned object.

Value

A data frame, or a list of data frames, with one frequency table as data frame per variable.

Examples

```
data(efc)

# vector/factor
data_tabulate(efc$c172code)

# data frame
data_tabulate(efc, c("e42dep", "c172code"))

# grouped data frame
suppressPackageStartupMessages(library(poorman, quietly = TRUE))
efc %>%
  group_by(c172code) %>%
  data_tabulate("e16sex")

# collapse tables
efc %>%
  group_by(c172code) %>%
  data_tabulate("e16sex", collapse = TRUE)

# for larger N's (> 100000), a big mark is automatically added
set.seed(123)
x <- sample(1:3, 1e6, TRUE)
data_tabulate(x, name = "Large Number")

# to remove the big mark, use "print(..., big_mark = "")"
print(data_tabulate(x), big_mark = "")
```

data_to_long

Reshape (pivot) data from wide to long

Description

This function "lengthens" data, increasing the number of rows and decreasing the number of columns. This is a dependency-free base-R equivalent of `tidyr::pivot_longer()`.

Usage

```
data_to_long(  
  data,  
  select = "all",  
  names_to = "name",  
  names_prefix = NULL,  
  names_sep = NULL,  
  names_pattern = NULL,  
  values_to = "value",  
  values_drop_na = FALSE,  
  rows_to = NULL,  
  ignore_case = FALSE,  
  regex = FALSE,  
  ...,  
  cols,  
  colnames_to  
)
```

```
reshape_longer(  
  data,  
  select = "all",  
  names_to = "name",  
  names_prefix = NULL,  
  names_sep = NULL,  
  names_pattern = NULL,  
  values_to = "value",  
  values_drop_na = FALSE,  
  rows_to = NULL,  
  ignore_case = FALSE,  
  regex = FALSE,  
  ...,  
  cols,  
  colnames_to  
)
```

Arguments

data	A data frame to pivot.
select	Variables that will be included when performing the required tasks. Can be either <ul style="list-style-type: none">• a variable specified as a literal variable name (e.g., <code>column_name</code>),• a string with the variable name (e.g., <code>"column_name"</code>), or a character vector of variable names (e.g., <code>c("col1", "col2", "col3")</code>),• a formula with variable names (e.g., <code>~column_1 + column_2</code>),• a vector of positive integers, giving the positions counting from the left (e.g. <code>1</code> or <code>c(1, 3, 5)</code>),

- a vector of negative integers, giving the positions counting from the right (e.g., -1 or -1:-3),
- one of the following select-helpers: `starts_with()`, `ends_with()`, `contains()`, a range using `:` or `regex("")`. `starts_with()`, `ends_with()`, and `contains()` accept several patterns, e.g. `starts_with("Sep", "Petal")`.
- or a function testing for logical conditions, e.g. `is.numeric()` (or `is.numeric`), or any user-defined function that selects the variables for which the function returns TRUE (like: `foo <- function(x) mean(x) > 3`),
- ranges specified via literal variable names, select-helpers (except `regex()`) and (user-defined) functions can be negated, i.e. return non-matching elements, when prefixed with a `-`, e.g. `-ends_with("")`, `-is.numeric` or `-(Sepal.Width:Petal.Length)`. **Note:** Negation means that matches are *excluded*, and thus, the `exclude` argument can be used alternatively. For instance, `select=-ends_with("Length")` (with `-`) is equivalent to `exclude=ends_with("Length")` (no `-`). In case negation should not work as expected, use the `exclude` argument instead.

If NULL, selects all columns. Patterns that found no matches are silently ignored, e.g. `find_columns(iris, select = c("Species", "Test"))` will just return "Species".

<code>names_to</code>	The name of the new column that will contain the column names.
<code>names_prefix</code>	A regular expression used to remove matching text from the start of each variable name.
<code>names_sep, names_pattern</code>	If <code>names_to</code> contains multiple values, this argument controls how the column name is broken up. <code>names_pattern</code> takes a regular expression containing matching groups, i.e. <code>"()"</code> .
<code>values_to</code>	The name of the new column that will contain the values of the pivoted variables.
<code>values_drop_na</code>	If TRUE, will drop rows that contain only NA in the <code>values_to</code> column. This effectively converts explicit missing values to implicit missing values, and should generally be used only when missing values in data were created by its structure.
<code>rows_to</code>	The name of the column that will contain the row names or row numbers from the original data. If NULL, will be removed.
<code>ignore_case</code>	Logical, if TRUE and when one of the select-helpers or a regular expression is used in <code>select</code> , ignores lower/upper case in the search pattern when matching against variable names.
<code>regex</code>	Logical, if TRUE, the search pattern from <code>select</code> will be treated as regular expression. When <code>regex = TRUE</code> , <code>select</code> <i>must</i> be a character string (or a variable containing a character string) and is not allowed to be one of the supported select-helpers or a character vector of length > 1. <code>regex = TRUE</code> is comparable to using one of the two select-helpers, <code>select = contains("")</code> or <code>select = regex("")</code> , however, since the select-helpers may not work when called from inside other functions (see 'Details'), this argument may be used as workaround.
<code>...</code>	Currently not used.
<code>cols</code>	Identical to <code>select</code> . This argument is here to ensure compatibility with <code>tidyr::pivot_longer()</code> . If both <code>select</code> and <code>cols</code> are provided, <code>cols</code> is used.
<code>colnames_to</code>	Deprecated. Use <code>names_to</code> instead.

Value

If a tibble was provided as input, `reshape_longer()` also returns a tibble. Otherwise, it returns a data frame.

See Also

- Functions to rename stuff: `data_rename()`, `data_rename_rows()`, `data_addprefix()`, `data_addsuffix()`
- Functions to reorder or remove columns: `data_reorder()`, `data_relocate()`, `data_remove()`
- Functions to reshape, pivot or rotate data frames: `data_to_long()`, `data_to_wide()`, `data_rotate()`
- Functions to recode data: `rescale()`, `reverse()`, `categorize()`, `recode_values()`, `slide()`
- Functions to standardize, normalize, rank-transform: `center()`, `standardize()`, `normalize()`, `ranktransform()`, `winsorize()`
- Split and merge data frames: `data_partition()`, `data_merge()`
- Functions to find or select columns: `data_select()`, `data_find()`
- Functions to filter rows: `data_match()`, `data_filter()`

Examples

```
wide_data <- data.frame(replicate(5, rnorm(10)))

# Default behaviour (equivalent to tidyr::pivot_longer(wide_data, cols = 1:5))
data_to_long(wide_data)

# Customizing the names
data_to_long(wide_data,
  select = c(1, 2),
  names_to = "Column",
  values_to = "Numbers",
  rows_to = "Row"
)

# Full example
# -----
data <- psych::bfi # Wide format with one row per participant's personality test

# Pivot long format
data_to_long(data,
  select = regex("\\d"), # Select all columns that contain a digit
  names_to = "Item",
  values_to = "Score",
  rows_to = "Participant"
)

data_to_long(
  tidyr::who,
  select = new_sp_m014:newrel_f65,
  names_to = c("diagnosis", "gender", "age"),
  names_pattern = "new_?(.*)_(.)(.*)",
```

```
  values_to = "count"  
)
```

data_to_wide

Reshape (pivot) data from long to wide

Description

This function "widens" data, increasing the number of columns and decreasing the number of rows. This is a dependency-free base-R equivalent of `tidyr::pivot_wider()`.

Usage

```
data_to_wide(  
  data,  
  id_cols = NULL,  
  values_from = "Value",  
  names_from = "Name",  
  names_sep = "_",  
  names_prefix = "",  
  names_glue = NULL,  
  values_fill = NULL,  
  verbose = TRUE,  
  ...,  
  colnames_from,  
  rows_from,  
  sep  
)  
  
reshape_wider(  
  data,  
  id_cols = NULL,  
  values_from = "Value",  
  names_from = "Name",  
  names_sep = "_",  
  names_prefix = "",  
  names_glue = NULL,  
  values_fill = NULL,  
  verbose = TRUE,  
  ...,  
  colnames_from,  
  rows_from,  
  sep  
)
```

Arguments

data	A data frame to pivot.
id_cols	The name of the column that identifies the rows. If NULL, it will use all the unique rows.
values_from	The name of the column that contains the values to be used as future variable values.
names_from	The name of the column that contains the levels to be used as future column names.
names_sep	If names_from or values_from contains multiple variables, this will be used to join their values together into a single string to use as a column name.
names_prefix	String added to the start of every variable name. This is particularly useful if names_from is a numeric vector and you want to create syntactic variable names.
names_glue	Instead of names_sep and names_prefix, you can supply a glue specification that uses the names_from columns to create custom column names. Note that the only delimiters supported by names_glue are curly brackets, { and }.
values_fill	Optionally, a (scalar) value that will be used to replace missing values in the new columns created.
verbose	Toggle warnings.
...	Not used for now.
colnames_from	Deprecated. Use names_from instead.
rows_from	Deprecated. Use id_cols instead.
sep	Deprecated. Use names_sep instead.

Value

If a tibble was provided as input, `reshape_wider()` also returns a tibble. Otherwise, it returns a data frame.

See Also

- Functions to rename stuff: [data_rename\(\)](#), [data_rename_rows\(\)](#), [data_addprefix\(\)](#), [data_addsuffix\(\)](#)
- Functions to reorder or remove columns: [data_reorder\(\)](#), [data_relocate\(\)](#), [data_remove\(\)](#)
- Functions to reshape, pivot or rotate data frames: [data_to_long\(\)](#), [data_to_wide\(\)](#), [data_rotate\(\)](#)
- Functions to recode data: [rescale\(\)](#), [reverse\(\)](#), [categorize\(\)](#), [recode_values\(\)](#), [slide\(\)](#)
- Functions to standardize, normalize, rank-transform: [center\(\)](#), [standardize\(\)](#), [normalize\(\)](#), [ranktransform\(\)](#), [winsorize\(\)](#)
- Split and merge data frames: [data_partition\(\)](#), [data_merge\(\)](#)
- Functions to find or select columns: [data_select\(\)](#), [data_find\(\)](#)
- Functions to filter rows: [data_match\(\)](#), [data_filter\(\)](#)

Examples

```
data_long <- read.table(header = TRUE, text = "
subject sex condition measurement
  1  M   control      7.9
  1  M   cond1       12.3
  1  M   cond2       10.7
  2  F   control      6.3
  2  F   cond1       10.6
  2  F   cond2       11.1
  3  F   control      9.5
  3  F   cond1       13.1
  3  F   cond2       13.8
  4  M   control     11.5
  4  M   cond1       13.4
  4  M   cond2       12.9")
```

```
data_to_wide(
  data_long,
  id_cols = "subject",
  names_from = "condition",
  values_from = "measurement"
)
```

```
data_to_wide(
  data_long,
  id_cols = "subject",
  names_from = "condition",
  values_from = "measurement",
  names_prefix = "Var.",
  names_sep = "."
)
```

```
production <- expand.grid(
  product = c("A", "B"),
  country = c("AI", "EI"),
  year = 2000:2014
)
production <- data_filter(production, (product == "A" & country == "AI") | product == "B")
```

```
production$production <- rnorm(nrow(production))
```

```
data_to_wide(
  production,
  names_from = c("product", "country"),
  values_from = "production",
  names_glue = "prod_{product}_{country}"
)
```

data_unique	<i>Keep only one row from all with duplicated IDs</i>
-------------	---

Description

From all rows with at least one duplicated ID, keep only one. Methods for selecting the duplicated row are either the first duplicate, the last duplicate, or the "best" duplicate (default), based on the duplicate with the smallest number of NA. In case of ties, it picks the first duplicate, as it is the one most likely to be valid and authentic, given practice effects.

Contrarily to `dplyr::distinct()`, `data_unique()` keeps all columns.

Usage

```
data_unique(
  data,
  select = NULL,
  keep = "best",
  exclude = NULL,
  ignore_case = FALSE,
  regex = FALSE,
  verbose = TRUE
)
```

Arguments

data	A data frame.
select	Variables that will be included when performing the required tasks. Can be either <ul style="list-style-type: none"> • a variable specified as a literal variable name (e.g., <code>column_name</code>), • a string with the variable name (e.g., <code>"column_name"</code>), or a character vector of variable names (e.g., <code>c("col1", "col2", "col3")</code>), • a formula with variable names (e.g., <code>~column_1 + column_2</code>), • a vector of positive integers, giving the positions counting from the left (e.g. 1 or <code>c(1, 3, 5)</code>), • a vector of negative integers, giving the positions counting from the right (e.g., <code>-1</code> or <code>-1:-3</code>), • one of the following select-helpers: <code>starts_with()</code>, <code>ends_with()</code>, <code>contains()</code>, a range using <code>:</code> or <code>regex("")</code>. <code>starts_with()</code>, <code>ends_with()</code>, and <code>contains()</code> accept several patterns, e.g <code>starts_with("Sep", "Petal")</code>. • or a function testing for logical conditions, e.g. <code>is.numeric()</code> (or <code>is.numeric</code>), or any user-defined function that selects the variables for which the function returns TRUE (like: <code>foo <- function(x) mean(x) > 3</code>), • ranges specified via literal variable names, select-helpers (except <code>regex()</code>) and (user-defined) functions can be negated, i.e. return non-matching elements, when prefixed with a <code>-</code>, e.g. <code>-ends_with("")</code>, <code>-is.numeric</code> or

-(Sepal.Width:Petal.Length). **Note:** Negation means that matches are *excluded*, and thus, the `exclude` argument can be used alternatively. For instance, `select=-ends_with("Length")` (with `-`) is equivalent to `exclude=ends_with("Length")` (no `-`). In case negation should not work as expected, use the `exclude` argument instead.

If `NULL`, selects all columns. Patterns that found no matches are silently ignored, e.g. `find_columns(iris, select = c("Species", "Test"))` will just return `"Species"`.

<code>keep</code>	The method to be used for duplicate selection, either <code>"best"</code> (the default), <code>"first"</code> , or <code>"last"</code> .
<code>exclude</code>	See <code>select</code> , however, column names matched by the pattern from <code>exclude</code> will be excluded instead of selected. If <code>NULL</code> (the default), excludes no columns.
<code>ignore_case</code>	Logical, if <code>TRUE</code> and when one of the select-helpers or a regular expression is used in <code>select</code> , ignores lower/upper case in the search pattern when matching against variable names.
<code>regex</code>	Logical, if <code>TRUE</code> , the search pattern from <code>select</code> will be treated as regular expression. When <code>regex = TRUE</code> , <code>select</code> <i>must</i> be a character string (or a variable containing a character string) and is not allowed to be one of the supported select-helpers or a character vector of length <code>> 1</code> . <code>regex = TRUE</code> is comparable to using one of the two select-helpers, <code>select = contains("")</code> or <code>select = regex("")</code> , however, since the select-helpers may not work when called from inside other functions (see 'Details'), this argument may be used as workaround.
<code>verbose</code>	Toggle warnings.

Value

A data frame, containing only the chosen duplicates.

See Also

[data_duplicated\(\)](#)

Examples

```
df1 <- data.frame(
  id = c(1, 2, 3, 1, 3),
  item1 = c(NA, 1, 1, 2, 3),
  item2 = c(NA, 1, 1, 2, 3),
  item3 = c(NA, 1, 1, 2, 3)
)

data_unique(df1, select = "id")
```

`demean`*Compute group-meaned and de-meaned variables*

Description

`demean()` computes group- and de-meaned versions of a variable that can be used in regression analysis to model the between- and within-subject effect. `degroup()` is more generic in terms of the centering-operation. While `demean()` always uses mean-centering, `degroup()` can also use the mode or median for centering.

Usage

```
demean(  
  x,  
  select,  
  group,  
  suffix_demean = "_within",  
  suffix_groupmean = "_between",  
  add_attributes = TRUE,  
  verbose = TRUE  
)
```

```
degroup(  
  x,  
  select,  
  group,  
  center = "mean",  
  suffix_demean = "_within",  
  suffix_groupmean = "_between",  
  add_attributes = TRUE,  
  verbose = TRUE  
)
```

```
detrend(  
  x,  
  select,  
  group,  
  center = "mean",  
  suffix_demean = "_within",  
  suffix_groupmean = "_between",  
  add_attributes = TRUE,  
  verbose = TRUE  
)
```

Arguments

`x` A data frame.

select	Character vector (or formula) with names of variables to select that should be group- and de-meanded.
group	Character vector (or formula) with the name of the variable that indicates the group- or cluster-ID.
suffix_demean, suffix_groupmean	String value, will be appended to the names of the group-meanded and de-meanded variables of x. By default, de-meanded variables will be suffixed with "_within" and grouped-meanded variables with "_between".
add_attributes	Logical, if TRUE, the returned variables gain attributes to indicate the within- and between-effects. This is only relevant when printing <code>model_parameters()</code> - in such cases, the within- and between-effects are printed in separated blocks.
verbose	Toggle warnings and messages.
center	Method for centering. <code>demean()</code> always performs mean-centering, while <code>degrouop()</code> can use <code>center = "median"</code> or <code>center = "mode"</code> for median- or mode-centering, and also "min" or "max".

Details

Heterogeneity Bias: Mixed models include different levels of sources of variability, i.e. error terms at each level. When macro-indicators (or level-2 predictors, or higher-level units, or more general: *group-level predictors that vary within and across groups*) are included as fixed effects (i.e. treated as covariate at level-1), the variance that is left unaccounted for this covariate will be absorbed into the error terms of level-1 and level-2 (*Bafumi and Gelman 2006; Gelman and Hill 2007, Chapter 12.6.*): “Such covariates contain two parts: one that is specific to the higher-level entity that does not vary between occasions, and one that represents the difference between occasions, within higher-level entities” (*Bell et al. 2015*). Hence, the error terms will be correlated with the covariate, which violates one of the assumptions of mixed models (iid, independent and identically distributed error terms). This bias is also called the *heterogeneity bias* (*Bell et al. 2015*). To resolve this problem, level-2 predictors used as (level-1) covariates should be separated into their "within" and "between" effects by "de-meaning" and "group-meaning": After demeaning time-varying predictors, “at the higher level, the mean term is no longer constrained by Level 1 effects, so it is free to account for all the higher-level variance associated with that variable” (*Bell et al. 2015*).

Panel data and correlating fixed and group effects: `demean()` is intended to create group- and de-meanded variables for panel regression models (fixed effects models), or for complex random-effect-within-between models (see *Bell et al. 2015, 2018*), where group-effects (random effects) and fixed effects correlate (see *Bafumi and Gelman 2006*). This can happen, for instance, when analyzing panel data, which can lead to *Heterogeneity Bias*. To control for correlating predictors and group effects, it is recommended to include the group-meanded and de-meanded version of *time-varying covariates* (and group-meanded version of *time-invariant covariates* that are on a higher level, e.g. level-2 predictors) in the model. By this, one can fit complex multilevel models for panel data, including time-varying predictors, time-invariant predictors and random effects.

Why mixed models are preferred over fixed effects models: A mixed models approach can model the causes of endogeneity explicitly by including the (separated) within- and between-effects of time-varying fixed effects and including time-constant fixed effects. Furthermore, mixed

models also include random effects, thus a mixed models approach is superior to classic fixed-effects models, which lack information of variation in the group-effects or between-subject effects. Furthermore, fixed effects regression cannot include random slopes, which means that fixed effects regressions are neglecting “cross-cluster differences in the effects of lower-level controls (which) reduces the precision of estimated context effects, resulting in unnecessarily wide confidence intervals and low statistical power” (Heisig et al. 2017).

Terminology: The group-measured variable is simply the mean of an independent variable within each group (or id-level or cluster) represented by group. It represents the cluster-mean of an independent variable. The regression coefficient of a group-measured variable is the *between-subject-effect*. The de-measured variable is then the centered version of the group-measured variable. De-meaning is sometimes also called person-mean centering or centering within clusters. The regression coefficient of a de-measured variable represents the *within-subject-effect*.

De-meaning with continuous predictors: For continuous time-varying predictors, the recommendation is to include both their de-measured and group-measured versions as fixed effects, but not the raw (untransformed) time-varying predictors themselves. The de-measured predictor should also be included as random effect (random slope). In regression models, the coefficient of the de-measured predictors indicates the within-subject effect, while the coefficient of the group-measured predictor indicates the between-subject effect.

De-meaning with binary predictors: For binary time-varying predictors, there are two recommendations. First is to include the raw (untransformed) binary predictor as fixed effect only and the *de-measured* variable as random effect (random slope). The alternative would be to add the de-measured version(s) of binary time-varying covariates as additional fixed effect as well (instead of adding it as random slope). Centering time-varying binary variables to obtain within-effects (level 1) isn’t necessary. They have a sensible interpretation when left in the typical 0/1 format (Hoffmann 2015, chapter 8-2.1). `demean()` will thus coerce categorical time-varying predictors to numeric to compute the de- and group-measured versions for these variables, where the raw (untransformed) binary predictor and the de-measured version should be added to the model.

De-meaning of factors with more than 2 levels: Factors with more than two levels are de-measured in two ways: first, these are also converted to numeric and de-measured; second, dummy variables are created (binary, with 0/1 coding for each level) and these binary dummy-variables are de-measured in the same way (as described above). Packages like **panelr** internally convert factors to dummies before demeaning, so this behaviour can be mimicked here.

De-meaning interaction terms: There are multiple ways to deal with interaction terms of within- and between-effects. A classical approach is to simply use the product term of the de-measured variables (i.e. introducing the de-measured variables as interaction term in the model formula, e.g. $y \sim x_{\text{within}} * \text{time}_{\text{within}}$). This approach, however, might be subject to bias (see Giesselmann & Schmidt-Catran 2020).

Another option is to first calculate the product term and then apply the de-meaning to it. This approach produces an estimator “that reflects unit-level differences of interacted variables whose moderators vary within units”, which is desirable if *no* within interaction of two time-dependent variables is required.

A third option, when the interaction should result in a genuine within estimator, is to “double de-mean” the interaction terms (Giesselmann & Schmidt-Catran 2018), however, this is currently

not supported by `demean()`. If this is required, the `wmb()` function from the **panelr** package should be used.

To de-mean interaction terms for within-between models, simply specify the term as interaction for the `select`-argument, e.g. `select = "a*b"` (see 'Examples').

Analysing panel data with mixed models using lme4: A description of how to translate the formulas described in *Bell et al. 2018* into R using `lmer()` from **lme4** can be found in [this vignette](#).

Value

A data frame with the group-/de-measured variables, which get the suffix `"_between"` (for the group-measured variable) and `"_within"` (for the de-measured variable) by default.

References

- Bafumi J, Gelman A. 2006. Fitting Multilevel Models When Predictors and Group Effects Correlate. In. Philadelphia, PA: Annual meeting of the American Political Science Association.
- Bell A, Fairbrother M, Jones K. 2019. Fixed and Random Effects Models: Making an Informed Choice. *Quality & Quantity* (53); 1051-1074
- Bell A, Jones K. 2015. Explaining Fixed Effects: Random Effects Modeling of Time-Series Cross-Sectional and Panel Data. *Political Science Research and Methods*, 3(1), 133–153.
- Gelman A, Hill J. 2007. *Data Analysis Using Regression and Multilevel/Hierarchical Models*. Analytical Methods for Social Research. Cambridge, New York: Cambridge University Press
- Giesselmann M, Schmidt-Catran, AW. 2020. Interactions in fixed effects regression models. *Sociological Methods & Research*, 1–28. <https://doi.org/10.1177/0049124120914934>
- Heisig JP, Schaeffer M, Giesecke J. 2017. The Costs of Simplicity: Why Multilevel Models May Benefit from Accounting for Cross-Cluster Differences in the Effects of Controls. *American Sociological Review* 82 (4): 796–827.
- Hoffman L. 2015. *Longitudinal analysis: modeling within-person fluctuation and change*. New York: Routledge

See Also

If grand-mean centering (instead of centering within-clusters) is required, see `center()`.

Examples

```
data(iris)
iris$ID <- sample(1:4, nrow(iris), replace = TRUE) # fake-ID
iris$binary <- as.factor(rbinom(150, 1, .35)) # binary variable

x <- demean(iris, select = c("Sepal.Length", "Petal.Length"), group = "ID")
head(x)
```

```
x <- demean(iris, select = c("Sepal.Length", "binary", "Species"), group = "ID")
head(x)

# demean interaction term x*y
dat <- data.frame(
  a = c(1, 2, 3, 4, 1, 2, 3, 4),
  x = c(4, 3, 3, 4, 1, 2, 1, 2),
  y = c(1, 2, 1, 2, 4, 3, 2, 1),
  ID = c(1, 2, 3, 1, 2, 3, 1, 2)
)
demean(dat, select = c("a", "x*y"), group = "ID")

# or in formula-notation
demean(dat, select = ~ a + x * y, group = ~ID)
```

describe_distribution *Describe a distribution*

Description

This function describes a distribution by a set of indices (e.g., measures of centrality, dispersion, range, skewness, kurtosis).

Usage

```
describe_distribution(x, ...)

## S3 method for class 'numeric'
describe_distribution(
  x,
  centrality = "mean",
  dispersion = TRUE,
  iqr = TRUE,
  range = TRUE,
  quartiles = FALSE,
  ci = NULL,
  iterations = 100,
  threshold = 0.1,
  verbose = TRUE,
  ...
)

## S3 method for class 'factor'
describe_distribution(x, dispersion = TRUE, range = TRUE, verbose = TRUE, ...)

## S3 method for class 'data.frame'
```

```

describe_distribution(
  x,
  select = NULL,
  exclude = NULL,
  centrality = "mean",
  dispersion = TRUE,
  iqr = TRUE,
  range = TRUE,
  quartiles = FALSE,
  include_factors = FALSE,
  ci = NULL,
  iterations = 100,
  threshold = 0.1,
  ignore_case = FALSE,
  regex = FALSE,
  verbose = TRUE,
  ...
)

```

Arguments

x	A numeric vector, a character vector, a data frame, or a list. See Details.
...	Additional arguments to be passed to or from methods.
centrality	The point-estimates (centrality indices) to compute. Character (vector) or list with one or more of these options: "median", "mean", "MAP" or "all".
dispersion	Logical, if TRUE, computes indices of dispersion related to the estimate(s) (SD and MAD for mean and median, respectively).
iqr	Logical, if TRUE, the interquartile range is calculated (based on <code>stats::IQR()</code> , using <code>type = 6</code>).
range	Return the range (min and max).
quartiles	Return the first and third quartiles (25th and 75pth percentiles).
ci	Confidence Interval (CI) level. Default is NULL, i.e. no confidence intervals are computed. If not NULL, confidence intervals are based on bootstrap replicates (see <code>iterations</code>). If <code>centrality = "all"</code> , the bootstrapped confidence interval refers to the first centrality index (which is typically the median).
iterations	The number of bootstrap replicates for computing confidence intervals. Only applies when <code>ci</code> is not NULL.
threshold	For <code>centrality = "trimmed"</code> (i.e. trimmed mean), indicates the fraction (0 to 0.5) of observations to be trimmed from each end of the vector before the mean is computed.
verbose	Toggle warnings and messages.
select	Variables that will be included when performing the required tasks. Can be either <ul style="list-style-type: none"> • a variable specified as a literal variable name (e.g., <code>column_name</code>),

- a string with the variable name (e.g., "column_name"), or a character vector of variable names (e.g., c("col1", "col2", "col3")),
- a formula with variable names (e.g., ~column_1 + column_2),
- a vector of positive integers, giving the positions counting from the left (e.g. 1 or c(1, 3, 5)),
- a vector of negative integers, giving the positions counting from the right (e.g., -1 or -1:-3),
- one of the following select-helpers: starts_with(), ends_with(), contains(), a range using : or regex(""). starts_with(), ends_with(), and contains() accept several patterns, e.g starts_with("Sep", "Petal").
- or a function testing for logical conditions, e.g. is.numeric() (or is.numeric), or any user-defined function that selects the variables for which the function returns TRUE (like: foo <- function(x) mean(x) > 3),
- ranges specified via literal variable names, select-helpers (except regex()) and (user-defined) functions can be negated, i.e. return non-matching elements, when prefixed with a -, e.g. -ends_with(""), -is.numeric or -(Sepal.Width:Petal.Length). **Note:** Negation means that matches are *excluded*, and thus, the exclude argument can be used alternatively. For instance, select=-ends_with("Length") (with -) is equivalent to exclude=ends_with("Length") (no -). In case negation should not work as expected, use the exclude argument instead.

If NULL, selects all columns. Patterns that found no matches are silently ignored, e.g. find_columns(iris, select = c("Species", "Test")) will just return "Species".

exclude	See select, however, column names matched by the pattern from exclude will be excluded instead of selected. If NULL (the default), excludes no columns.
include_factors	Logical, if TRUE, factors are included in the output, however, only columns for range (first and last factor levels) as well as n and missing will contain information.
ignore_case	Logical, if TRUE and when one of the select-helpers or a regular expression is used in select, ignores lower/upper case in the search pattern when matching against variable names.
regex	Logical, if TRUE, the search pattern from select will be treated as regular expression. When regex = TRUE, select <i>must</i> be a character string (or a variable containing a character string) and is not allowed to be one of the supported select-helpers or a character vector of length > 1. regex = TRUE is comparable to using one of the two select-helpers, select = contains("") or select = regex(""), however, since the select-helpers may not work when called from inside other functions (see 'Details'), this argument may be used as workaround.

Details

If x is a data frame, only numeric variables are kept and will be displayed in the summary.

If x is a list, the behavior is different whether x is a stored list. If x is stored (for example, describe_distribution(mylist) where mylist was created before), artificial variable names

are used in the summary (Var_1, Var_2, etc.). If x is an unsorted list (for example, describe_distribution(list(mtcars\$mpg, mtcars\$wt)) then "mtcars\$mpg" is used as variable name.

Value

A data frame with columns that describe the properties of the variables.

Selection of variables - the select argument

For most functions that have a select argument (including this function), the complete input data frame is returned, even when select only selects a range of variables. That is, the function is only applied to those variables that have a match in select, while all other variables remain unchanged. In other words: for this function, select will not omit any non-included variables, so that the returned data frame will include all variables from the input data frame.

Note

There is also a `plot()`-method implemented in the [see-package](#).

Examples

```
describe_distribution(rnorm(100))

data(iris)
describe_distribution(iris)
describe_distribution(iris, include_factors = TRUE, quartiles = TRUE)
describe_distribution(list(mtcars$mpg, mtcars$cyl))
```

distribution_mode	<i>Compute mode for a statistical distribution</i>
-------------------	--

Description

Compute mode for a statistical distribution

Usage

```
distribution_mode(x)
```

Arguments

x An atomic vector, a list, or a data frame.

Value

The value that appears most frequently in the provided data. The returned data structure will be the same as the entered one.

See Also

For continuous variables, the **Highest Maximum a Posteriori probability estimate (MAP)** may be a more useful way to estimate the most commonly-observed value than the mode. See [bayestestR::map_estimate\(\)](#).

Examples

```
distribution_mode(c(1, 2, 3, 3, 4, 5))
distribution_mode(c(1.5, 2.3, 3.7, 3.7, 4.0, 5))
```

efc	<i>Sample dataset from the EFC Survey</i>
-----	---

Description

Selected variables from the EUROFAMCARE survey. Useful when testing on "real-life" data sets, including random missing values. This data set also has value and variable label attributes.

find_columns	<i>Find or get columns in a data frame based on search patterns</i>
--------------	---

Description

`find_columns()` returns column names from a data set that match a certain search pattern, while `get_columns()` returns the found data. `data_select()` is an alias for `get_columns()`, and `data_find()` is an alias for `find_columns()`.

Usage

```
find_columns(  
  data,  
  select = NULL,  
  exclude = NULL,  
  ignore_case = FALSE,  
  regex = FALSE,  
  verbose = TRUE,  
  ...  
)
```

```
data_find(  
  data,  
  select = NULL,  
  exclude = NULL,  
  ignore_case = FALSE,
```

```

    regex = FALSE,
    verbose = TRUE,
    ...
)

get_columns(
  data,
  select = NULL,
  exclude = NULL,
  ignore_case = FALSE,
  regex = FALSE,
  verbose = TRUE,
  ...
)

data_select(
  data,
  select = NULL,
  exclude = NULL,
  ignore_case = FALSE,
  regex = FALSE,
  verbose = TRUE,
  ...
)

```

Arguments

data	A data frame.
select	<p>Variables that will be included when performing the required tasks. Can be either</p> <ul style="list-style-type: none"> • a variable specified as a literal variable name (e.g., <code>column_name</code>), • a string with the variable name (e.g., <code>"column_name"</code>), or a character vector of variable names (e.g., <code>c("col1", "col2", "col3")</code>), • a formula with variable names (e.g., <code>~column_1 + column_2</code>), • a vector of positive integers, giving the positions counting from the left (e.g. <code>1</code> or <code>c(1, 3, 5)</code>), • a vector of negative integers, giving the positions counting from the right (e.g., <code>-1</code> or <code>-1:-3</code>), • one of the following select-helpers: <code>starts_with()</code>, <code>ends_with()</code>, <code>contains()</code>, a range using <code>:</code> or <code>regex("")</code>. <code>starts_with()</code>, <code>ends_with()</code>, and <code>contains()</code> accept several patterns, e.g. <code>starts_with("Sep", "Petal")</code>. • or a function testing for logical conditions, e.g. <code>is.numeric()</code> (or <code>is.numeric</code>), or any user-defined function that selects the variables for which the function returns TRUE (like: <code>foo <- function(x) mean(x) > 3</code>), • ranges specified via literal variable names, select-helpers (except <code>regex()</code>) and (user-defined) functions can be negated, i.e. return non-matching elements, when prefixed with a <code>-</code>, e.g. <code>-ends_with("")</code>, <code>-is.numeric</code> or

-(Sepal.Width:Petal.Length). **Note:** Negation means that matches are *excluded*, and thus, the `exclude` argument can be used alternatively. For instance, `select=-ends_with("Length")` (with `-`) is equivalent to `exclude=ends_with("Length")` (no `-`). In case negation should not work as expected, use the `exclude` argument instead.

If `NULL`, selects all columns. Patterns that found no matches are silently ignored, e.g. `find_columns(iris, select = c("Species", "Test"))` will just return "Species".

<code>exclude</code>	See <code>select</code> , however, column names matched by the pattern from <code>exclude</code> will be excluded instead of selected. If <code>NULL</code> (the default), excludes no columns.
<code>ignore_case</code>	Logical, if <code>TRUE</code> and when one of the select-helpers or a regular expression is used in <code>select</code> , ignores lower/upper case in the search pattern when matching against variable names.
<code>regex</code>	Logical, if <code>TRUE</code> , the search pattern from <code>select</code> will be treated as regular expression. When <code>regex = TRUE</code> , <code>select</code> <i>must</i> be a character string (or a variable containing a character string) and is not allowed to be one of the supported select-helpers or a character vector of length > 1. <code>regex = TRUE</code> is comparable to using one of the two select-helpers, <code>select = contains("")</code> or <code>select = regex("")</code> , however, since the select-helpers may not work when called from inside other functions (see 'Details'), this argument may be used as workaround.
<code>verbose</code>	Toggle warnings.
<code>...</code>	Arguments passed down to other functions. Mostly not used yet.

Details

Note that it is possible to either pass an entire select helper or only the pattern inside a select helper as a function argument:

```
foo <- function(data, pattern) {
  find_columns(data, select = starts_with(pattern))
}
foo(iris, pattern = "Sep")
```

```
foo2 <- function(data, pattern) {
  find_columns(data, select = pattern)
}
foo2(iris, pattern = starts_with("Sep"))
```

This means that it is also possible to use loop values as arguments or patterns:

```
for (i in c("Sepal", "Sp")) {
  head(iris) |>
  find_columns(select = starts_with(i)) |>
  print()
}
```

However, this behavior is limited to a "single-level function". It will not work in nested functions, like below:

```
inner <- function(data, arg) {
  find_columns(data, select = arg)
}
outer <- function(data, arg) {
  inner(data, starts_with(arg))
}
outer(iris, "Sep")
```

In this case, it is better to pass the whole select helper as the argument of `outer()`:

```
outer <- function(data, arg) {
  inner(data, arg)
}
outer(iris, starts_with("Sep"))
```

Value

`find_columns()` returns a character vector with column names that matched the pattern in `select` and `exclude`, or `NULL` if no matching column name was found. `get_columns()` returns a data frame with matching columns.

See Also

- Functions to rename stuff: [data_rename\(\)](#), [data_rename_rows\(\)](#), [data_addprefix\(\)](#), [data_addsuffix\(\)](#)
- Functions to reorder or remove columns: [data_reorder\(\)](#), [data_relocate\(\)](#), [data_remove\(\)](#)
- Functions to reshape, pivot or rotate data frames: [data_to_long\(\)](#), [data_to_wide\(\)](#), [data_rotate\(\)](#)
- Functions to recode data: [rescale\(\)](#), [reverse\(\)](#), [categorize\(\)](#), [recode_values\(\)](#), [slide\(\)](#)
- Functions to standardize, normalize, rank-transform: [center\(\)](#), [standardize\(\)](#), [normalize\(\)](#), [ranktransform\(\)](#), [winsorize\(\)](#)
- Split and merge data frames: [data_partition\(\)](#), [data_merge\(\)](#)
- Functions to find or select columns: [data_select\(\)](#), [data_find\(\)](#)
- Functions to filter rows: [data_match\(\)](#), [data_filter\(\)](#)

Examples

```
# Find columns names by pattern
find_columns(iris, starts_with("Sepal"))
find_columns(iris, ends_with("Width"))
find_columns(iris, regex("\\."))
find_columns(iris, c("Petal.Width", "Sepal.Length"))

# starts with "Sepal", but not allowed to end with "width"
find_columns(iris, starts_with("Sepal"), exclude = contains("Width"))

# find numeric with mean > 3.5
numeric_mean_35 <- function(x) is.numeric(x) && mean(x, na.rm = TRUE) > 3.5
find_columns(iris, numeric_mean_35)
```

`makepredictcall.dw_transformer`*Utility Function for Safe Prediction with datawizard transformers*

Description

This function allows for the use of (some of) datawizard's transformers inside a model formula. See examples below.

Currently, `center()`, `standardize()`, `normalize()`, & `rescale()` are supported.

Usage

```
## S3 method for class 'dw_transformer'  
makepredictcall(var, call)
```

Arguments

<code>var</code>	A variable.
<code>call</code>	The term in the formula, as a call.

Value

A replacement for `call` for the `predvars` attribute of the terms.

See Also

[stats::makepredictcall\(\)](#)

Examples

```
data("mtcars")  
train <- mtcars[1:30, ]  
test <- mtcars[31:32, ]  
  
m1 <- lm(mpg ~ center(hp), data = train)  
predict(m1, newdata = test) # Data is "centered" before the prediction is made,  
# according to the center of the old data  
  
m2 <- lm(mpg ~ standardize(hp), data = train)  
m3 <- lm(mpg ~ scale(hp), data = train) # same as above  
predict(m2, newdata = test) # Data is "standardized" before the prediction is made.  
predict(m3, newdata = test) # Data is "standardized" before the prediction is made.  
  
m4 <- lm(mpg ~ normalize(hp), data = mtcars)  
m5 <- lm(mpg ~ rescale(hp, to = c(-3, 3)), data = mtcars)
```

```
(newdata <- data.frame(hp = c(range(mtcars$hp), 400))) # 400 is outside original range!
model.frame(delete.response(terms(m4)), data = newdata)
model.frame(delete.response(terms(m5)), data = newdata)
```

mean_sd

Summary Helpers

Description

Summary Helpers

Usage

```
mean_sd(x, times = 1L, na.rm = TRUE, named = TRUE, ...)
median_mad(x, times = 1L, na.rm = TRUE, constant = 1.4826, named = TRUE, ...)
```

Arguments

x	A numeric vector (or one that can be coerced to one via <code>as.numeric()</code>) to be summarized.
times	How many SDs above and below the Mean (or MADs around the Median)
na.rm	if TRUE then NA values are stripped from x before computation takes place.
named	Should the vector be named? (E.g., <code>c("-SD" = -1, Mean = 1, "+SD" = 2)</code> .)
...	Not used.
constant	scale factor.

Value

A (possibly named) numeric vector of length $2 \times \text{times} + 1$ of SDs below the mean, the mean, and SDs above the mean (or median and MAD).

Examples

```
mean_sd(mtcars$mpg)
mean_sd(mtcars$mpg, times = 2L)
median_mad(mtcars$mpg)
```

nhanes_sample	<i>Sample dataset from the National Health and Nutrition Examination Survey</i>
---------------	---

Description

Selected variables from the National Health and Nutrition Examination Survey that are used in the example from Lumley (2010), Appendix E.

References

Lumley T (2010). Complex Surveys: a guide to analysis using R. Wiley

normalize	<i>Normalize numeric variable to 0-1 range</i>
-----------	--

Description

Performs a normalization of data, i.e., it scales variables in the range 0 - 1. This is a special case of `rescale()`. `unnormalize()` is the counterpart, but only works for variables that have been normalized with `normalize()`.

Usage

```
normalize(x, ...)  
  
## S3 method for class 'numeric'  
normalize(x, include_bounds = TRUE, verbose = TRUE, ...)  
  
## S3 method for class 'data.frame'  
normalize(  
  x,  
  select = NULL,  
  exclude = NULL,  
  include_bounds = TRUE,  
  ignore_case = FALSE,  
  regex = FALSE,  
  verbose = TRUE,  
  ...  
)  
  
unnormalize(x, ...)  
  
## S3 method for class 'numeric'  
unnormalize(x, verbose = TRUE, ...)
```

```
## S3 method for class 'data.frame'
unnormalize(
  x,
  select = NULL,
  exclude = NULL,
  ignore_case = FALSE,
  regex = FALSE,
  verbose = TRUE,
  ...
)
```

Arguments

x	A numeric vector, (grouped) data frame, or matrix. See 'Details'.
...	Arguments passed to or from other methods.
include_bounds	Numeric or logical. Using this can be useful in case of beta-regression, where the response variable is not allowed to include zeros and ones. If TRUE, the input is normalized to a range that includes zero and one. If FALSE, the return value is compressed, using Smithson and Verkuilen's (2006) formula $(x * (n - 1) + 0.5) / n$, to avoid zeros and ones in the normalized variables. Else, if numeric (e.g., 0.001), include_bounds defines the "distance" to the lower and upper bound, i.e. the normalized vectors are rescaled to a range from 0 + include_bounds to 1 - include_bounds.
verbose	Toggle warnings and messages on or off.
select	Variables that will be included when performing the required tasks. Can be either <ul style="list-style-type: none"> • a variable specified as a literal variable name (e.g., column_name), • a string with the variable name (e.g., "column_name"), or a character vector of variable names (e.g., c("col1", "col2", "col3")), • a formula with variable names (e.g., ~column_1 + column_2), • a vector of positive integers, giving the positions counting from the left (e.g. 1 or c(1, 3, 5)), • a vector of negative integers, giving the positions counting from the right (e.g., -1 or -1:-3), • one of the following select-helpers: starts_with(), ends_with(), contains(), a range using : or regex(""). starts_with(), ends_with(), and contains() accept several patterns, e.g starts_with("Sep", "Petal"). • or a function testing for logical conditions, e.g. is.numeric() (or is.numeric), or any user-defined function that selects the variables for which the function returns TRUE (like: foo <- function(x) mean(x) > 3), • ranges specified via literal variable names, select-helpers (except regex()) and (user-defined) functions can be negated, i.e. return non-matching elements, when prefixed with a -, e.g. -ends_with(""), -is.numeric or -(Sepal.Width:Petal.Length). Note: Negation means that matches are <i>excluded</i>, and thus, the exclude argument can be used alternatively.

For instance, `select=-ends_with("Length")` (with `-`) is equivalent to `exclude=ends_with("Length")` (no `-`). In case negation should not work as expected, use the `exclude` argument instead.

If `NULL`, selects all columns. Patterns that found no matches are silently ignored, e.g. `find_columns(iris, select = c("Species", "Test"))` will just return `"Species"`.

<code>exclude</code>	See <code>select</code> , however, column names matched by the pattern from <code>exclude</code> will be excluded instead of selected. If <code>NULL</code> (the default), excludes no columns.
<code>ignore_case</code>	Logical, if <code>TRUE</code> and when one of the <code>select</code> -helpers or a regular expression is used in <code>select</code> , ignores lower/upper case in the search pattern when matching against variable names.
<code>regex</code>	Logical, if <code>TRUE</code> , the search pattern from <code>select</code> will be treated as regular expression. When <code>regex = TRUE</code> , <code>select</code> <i>must</i> be a character string (or a variable containing a character string) and is not allowed to be one of the supported <code>select</code> -helpers or a character vector of length <code>> 1</code> . <code>regex = TRUE</code> is comparable to using one of the two <code>select</code> -helpers, <code>select = contains("")</code> or <code>select = regex("")</code> , however, since the <code>select</code> -helpers may not work when called from inside other functions (see 'Details'), this argument may be used as workaround.

Details

- If `x` is a matrix, normalization is performed across all values (not column- or row-wise). For column-wise normalization, convert the matrix to a `data.frame`.
- If `x` is a grouped data frame (`grouped_df`), normalization is performed separately for each group.

Value

A normalized object.

Selection of variables - the `select` argument

For most functions that have a `select` argument (including this function), the complete input data frame is returned, even when `select` only selects a range of variables. That is, the function is only applied to those variables that have a match in `select`, while all other variables remain unchanged. In other words: for this function, `select` will not omit any non-included variables, so that the returned data frame will include all variables from the input data frame.

References

Smithson M, Verkuilen J (2006). A Better Lemon Squeezer? Maximum-Likelihood Regression with Beta-Distributed Dependent Variables. *Psychological Methods*, 11(1), 54–71.

See Also

See [makepredictcall.dw_transformer\(\)](#) for use in model formulas.

Other transform utilities: [ranktransform\(\)](#), [rescale\(\)](#), [reverse\(\)](#), [standardize\(\)](#)

Examples

```

normalize(c(0, 1, 5, -5, -2))
normalize(c(0, 1, 5, -5, -2), include_bounds = FALSE)
# use a value defining the bounds
normalize(c(0, 1, 5, -5, -2), include_bounds = .001)

head(normalize(trees))

```

ranktransform	<i>(Signed) rank transformation</i>
---------------	-------------------------------------

Description

Transform numeric values with the integers of their rank (i.e., 1st smallest, 2nd smallest, 3rd smallest, etc.). Setting the `sign` argument to `TRUE` will give you signed ranks, where the ranking is done according to absolute size but where the sign is preserved (i.e., 2, 1, -3, 4).

Usage

```

ranktransform(x, ...)

## S3 method for class 'numeric'
ranktransform(x, sign = FALSE, method = "average", verbose = TRUE, ...)

## S3 method for class 'data.frame'
ranktransform(
  x,
  select = NULL,
  exclude = NULL,
  sign = FALSE,
  method = "average",
  ignore_case = FALSE,
  regex = FALSE,
  verbose = TRUE,
  ...
)

```

Arguments

<code>x</code>	Object.
<code>...</code>	Arguments passed to or from other methods.
<code>sign</code>	Logical, if <code>TRUE</code> , return signed ranks.
<code>method</code>	Treatment of ties. Can be one of "average" (default), "first", "last", "random", "max" or "min". See rank() for details.

verbose	Toggle warnings.
select	<p>Variables that will be included when performing the required tasks. Can be either</p> <ul style="list-style-type: none"> • a variable specified as a literal variable name (e.g., <code>column_name</code>), • a string with the variable name (e.g., <code>"column_name"</code>), or a character vector of variable names (e.g., <code>c("col1", "col2", "col3")</code>), • a formula with variable names (e.g., <code>~column_1 + column_2</code>), • a vector of positive integers, giving the positions counting from the left (e.g. <code>1</code> or <code>c(1, 3, 5)</code>), • a vector of negative integers, giving the positions counting from the right (e.g., <code>-1</code> or <code>-1:-3</code>), • one of the following select-helpers: <code>starts_with()</code>, <code>ends_with()</code>, <code>contains()</code>, a range using <code>:</code> or <code>regex("")</code>. <code>starts_with()</code>, <code>ends_with()</code>, and <code>contains()</code> accept several patterns, e.g. <code>starts_with("Sep", "Petal")</code>. • or a function testing for logical conditions, e.g. <code>is.numeric()</code> (or <code>is.numeric</code>), or any user-defined function that selects the variables for which the function returns TRUE (like: <code>foo <- function(x) mean(x) > 3</code>), • ranges specified via literal variable names, select-helpers (except <code>regex()</code>) and (user-defined) functions can be negated, i.e. return non-matching elements, when prefixed with a <code>-</code>, e.g. <code>-ends_with("")</code>, <code>-is.numeric</code> or <code>-(Sepal.Width:Petal.Length)</code>. Note: Negation means that matches are <i>excluded</i>, and thus, the <code>exclude</code> argument can be used alternatively. For instance, <code>select=-ends_with("Length")</code> (with <code>-</code>) is equivalent to <code>exclude=ends_with("Length")</code> (no <code>-</code>). In case negation should not work as expected, use the <code>exclude</code> argument instead. <p>If NULL, selects all columns. Patterns that found no matches are silently ignored, e.g. <code>find_columns(iris, select = c("Species", "Test"))</code> will just return "Species".</p>
exclude	See <code>select</code> , however, column names matched by the pattern from <code>exclude</code> will be excluded instead of selected. If NULL (the default), excludes no columns.
ignore_case	Logical, if TRUE and when one of the select-helpers or a regular expression is used in <code>select</code> , ignores lower/upper case in the search pattern when matching against variable names.
regex	Logical, if TRUE, the search pattern from <code>select</code> will be treated as regular expression. When <code>regex = TRUE</code> , <code>select</code> <i>must</i> be a character string (or a variable containing a character string) and is not allowed to be one of the supported select-helpers or a character vector of length > 1. <code>regex = TRUE</code> is comparable to using one of the two select-helpers, <code>select = contains("")</code> or <code>select = regex("")</code> , however, since the select-helpers may not work when called from inside other functions (see 'Details'), this argument may be used as workaround.

Value

A rank-transformed object.

Selection of variables - the select argument

For most functions that have a select argument (including this function), the complete input data frame is returned, even when select only selects a range of variables. That is, the function is only applied to those variables that have a match in select, while all other variables remain unchanged. In other words: for this function, select will not omit any non-included variables, so that the returned data frame will include all variables from the input data frame.

See Also

Other transform utilities: [normalize\(\)](#), [rescale\(\)](#), [reverse\(\)](#), [standardize\(\)](#)

Examples

```
ranktransform(c(0, 1, 5, -5, -2))

# Won't work
# ranktransform(c(0, 1, 5, -5, -2), sign = TRUE)

head(ranktransform(trees))
```

recode_into

Recode values from one or more variables into a new variable

Description

This functions recodes values from one or more variables into a new variable. It is a convenient function to avoid nested `ifelse()` statements, which is similar to `dplyr::case_when()`.

Usage

```
recode_into(..., data = NULL, default = NA, verbose = TRUE)
```

Arguments

...	A sequence of two-sided formulas, where the left hand side (LHS) is a logical matching condition that determines which values match this case. The LHS of this formula is also called "recode pattern" (e.g., in messages). The right hand side (RHS) indicates the replacement value.
data	Optional, name of a data frame. This can be used to avoid writing the data name multiple times in See 'Examples'.
default	Indicates the default value that is chosen when no match in the formulas in ... is found. If not provided, NA is used as default value.
verbose	Toggle warnings.

Value

A vector with recoded values.

Examples

```

x <- 1:30
recode_into(
  x > 15 ~ "a",
  x > 10 & x <= 15 ~ "b",
  default = "c"
)

set.seed(123)
d <- data.frame(
  x = sample(1:5, 30, TRUE),
  y = sample(letters[1:5], 30, TRUE),
  stringsAsFactors = FALSE
)

# from different variables into new vector
recode_into(
  d$x %in% 1:3 & d$y %in% c("a", "b") ~ 1,
  d$x > 3 ~ 2,
  default = 0
)

# no need to write name of data frame each time
recode_into(
  x %in% 1:3 & y %in% c("a", "b") ~ 1,
  x > 3 ~ 2,
  data = d,
  default = 0
)

```

recode_values

Recode old values of variables into new values

Description

This functions recodes old values into new values and can be used to to recode numeric or character vectors, or factors.

Usage

```

recode_values(x, ...)

## S3 method for class 'numeric'
recode_values(
  x,
  recode = NULL,
  default = NULL,
  preserve_na = TRUE,
  verbose = TRUE,

```

```

    ...
  )

## S3 method for class 'data.frame'
recode_values(
  x,
  select = NULL,
  exclude = NULL,
  recode = NULL,
  default = NULL,
  preserve_na = TRUE,
  append = FALSE,
  ignore_case = FALSE,
  regex = FALSE,
  verbose = TRUE,
  ...
)

change_code(x, ...)
```

Arguments

<code>x</code>	A data frame, numeric or character vector, or factor.
<code>...</code>	not used.
<code>recode</code>	A list of named vectors, which indicate the recode pairs. The <i>names</i> of the list-elements (i.e. the left-hand side) represent the <i>new</i> values, while the values of the list-elements indicate the original (old) values that should be replaced. When recoding numeric vectors, element names have to be surrounded in backticks. For example, <code>recode=list(`0`=1)</code> would recode all 1 into 0 in a numeric vector. See also 'Examples' and 'Details'.
<code>default</code>	Defines the default value for all values that have no match in the recode-pairs. Note that, if <code>preserve_na=FALSE</code> , missing values (NA) are also captured by the <code>default</code> argument, and thus will also be recoded into the specified value. See 'Examples' and 'Details'.
<code>preserve_na</code>	Logical, if TRUE, NA (missing values) are preserved. This overrides any other arguments, including <code>default</code> . Hence, if <code>preserve_na=TRUE</code> , <code>default</code> will no longer convert NA into the specified default value.
<code>verbose</code>	Toggle warnings.
<code>select</code>	Variables that will be included when performing the required tasks. Can be either <ul style="list-style-type: none"> • a variable specified as a literal variable name (e.g., <code>column_name</code>), • a string with the variable name (e.g., <code>"column_name"</code>), or a character vector of variable names (e.g., <code>c("col1", "col2", "col3")</code>), • a formula with variable names (e.g., <code>~column_1 + column_2</code>), • a vector of positive integers, giving the positions counting from the left (e.g. <code>1</code> or <code>c(1, 3, 5)</code>),

- a vector of negative integers, giving the positions counting from the right (e.g., -1 or -1:-3),
- one of the following select-helpers: `starts_with()`, `ends_with()`, `contains()`, a range using `:` or `regex("")`. `starts_with()`, `ends_with()`, and `contains()` accept several patterns, e.g. `starts_with("Sep", "Petal")`.
- or a function testing for logical conditions, e.g. `is.numeric()` (or `is.numeric`), or any user-defined function that selects the variables for which the function returns TRUE (like: `foo <- function(x) mean(x) > 3`),
- ranges specified via literal variable names, select-helpers (except `regex()`) and (user-defined) functions can be negated, i.e. return non-matching elements, when prefixed with a `-`, e.g. `-ends_with("")`, `-is.numeric` or `-(Sepal.Width:Petal.Length)`. **Note:** Negation means that matches are *excluded*, and thus, the `exclude` argument can be used alternatively. For instance, `select=-ends_with("Length")` (with `-`) is equivalent to `exclude=ends_with("Length")` (no `-`). In case negation should not work as expected, use the `exclude` argument instead.

If NULL, selects all columns. Patterns that found no matches are silently ignored, e.g. `find_columns(iris, select = c("Species", "Test"))` will just return "Species".

<code>exclude</code>	See <code>select</code> , however, column names matched by the pattern from <code>exclude</code> will be excluded instead of selected. If NULL (the default), excludes no columns.
<code>append</code>	Logical or string. If TRUE, recoded or converted variables get new column names and are appended (column bind) to <code>x</code> , thus returning both the original and the recoded variables. The new columns get a suffix, based on the calling function: <code>"_r"</code> for recode functions, <code>"_n"</code> for <code>to_numeric()</code> , <code>"_f"</code> for <code>to_factor()</code> , or <code>"_s"</code> for <code>slide()</code> . If <code>append=FALSE</code> , original variables in <code>x</code> will be overwritten by their recoded versions. If a character value, recoded variables are appended with new column names (using the defined suffix) to the original data frame.
<code>ignore_case</code>	Logical, if TRUE and when one of the select-helpers or a regular expression is used in <code>select</code> , ignores lower/upper case in the search pattern when matching against variable names.
<code>regex</code>	Logical, if TRUE, the search pattern from <code>select</code> will be treated as regular expression. When <code>regex = TRUE</code> , <code>select</code> <i>must</i> be a character string (or a variable containing a character string) and is not allowed to be one of the supported select-helpers or a character vector of length > 1. <code>regex = TRUE</code> is comparable to using one of the two select-helpers, <code>select = contains("")</code> or <code>select = regex("")</code> , however, since the select-helpers may not work when called from inside other functions (see 'Details'), this argument may be used as workaround.

Details

This section describes the pattern of the recode arguments, which also provides some shortcuts, in particular when recoding numeric values.

- Single values

Single values either need to be wrapped in backticks (in case of numeric values) or "as is" (for character or factor levels). Example: `recode=list(`0`=1, `1`=2)` would recode 1 into

0, and 2 into 1. For factors or character vectors, an example is: `recode=list(x="a",y="b")` (recode "a" into "x" and "b" into "y").

- Multiple values

Multiple values that should be recoded into a new value can be separated with comma. Example: `recode=list(`1`=c(1,4),`2`=c(2,3))` would recode the values 1 and 4 into 1, and 2 and 3 into 2. It is also possible to define the old values as a character string, like: `recode=list(`1`="1,4",`2`="2,3")` For factors or character vectors, an example is: `recode=list(x=c("a","b"),`

- Value range

Numeric value ranges can be defined using the `:`. Example: `recode=list(`1`=1:3,`2`=4:6)` would recode all values from 1 to 3 into 1, and 4 to 6 into 2.

- min and max

placeholder to use the minimum or maximum value of the (numeric) variable. Useful, e.g., when recoding ranges of values. Example: `recode=list(`1`="min:10",`2`="11:max")`.

- default values

The default argument defines the default value for all values that have no match in the recode-pairs. For example, `recode=list(`1`=c(1,2),`2`=c(3,4))`, `default=9` would recode values 1 and 2 into 1, 3 and 4 into 2, and all other values into 9. If `preserve_na` is set to FALSE, NA (missing values) will also be recoded into the specified default value.

- Reversing and rescaling

See [reverse\(\)](#) and [rescale\(\)](#).

Value

x, where old values are replaced by new values.

Selection of variables - the select argument

For most functions that have a select argument (including this function), the complete input data frame is returned, even when select only selects a range of variables. That is, the function is only applied to those variables that have a match in select, while all other variables remain unchanged. In other words: for this function, select will not omit any non-included variables, so that the returned data frame will include all variables from the input data frame.

Note

You can use `options(data_recode_pattern = "old=new")` to switch the behaviour of the recode-argument, i.e. recode-pairs are now following the pattern old values = new values, e.g. if `getOption("data_recode_pattern")` is set to "old=new", then `recode(`1`=0)` would recode all 1 into 0. The default for `recode(`1`=0)` is to recode all 0 into 1.

See Also

- Functions to rename stuff: [data_rename\(\)](#), [data_rename_rows\(\)](#), [data_addprefix\(\)](#), [data_addsuffix\(\)](#)
- Functions to reorder or remove columns: [data_reorder\(\)](#), [data_relocate\(\)](#), [data_remove\(\)](#)
- Functions to reshape, pivot or rotate data frames: [data_to_long\(\)](#), [data_to_wide\(\)](#), [data_rotate\(\)](#)
- Functions to recode data: [rescale\(\)](#), [reverse\(\)](#), [categorize\(\)](#), [recode_values\(\)](#), [slide\(\)](#)

- Functions to standardize, normalize, rank-transform: `center()`, `standardize()`, `normalize()`, `ranktransform()`, `winsorize()`
- Split and merge data frames: `data_partition()`, `data_merge()`
- Functions to find or select columns: `data_select()`, `data_find()`
- Functions to filter rows: `data_match()`, `data_filter()`

Examples

```
# numeric -----
set.seed(123)
x <- sample(c(1:4, NA), 15, TRUE)
table(x, useNA = "always")

out <- recode_values(x, list(`0` = 1, `1` = 2:3, `2` = 4))
out
table(out, useNA = "always")

# to recode NA values, set preserve_na to FALSE
out <- recode_values(
  x,
  list(`0` = 1, `1` = 2:3, `2` = 4, `9` = NA),
  preserve_na = FALSE
)
out
table(out, useNA = "always")

# preserve na -----
out <- recode_values(x, list(`0` = 1, `1` = 2:3), default = 77)
out
table(out, useNA = "always")

# recode na into default -----
out <- recode_values(
  x,
  list(`0` = 1, `1` = 2:3),
  default = 77,
  preserve_na = FALSE
)
out
table(out, useNA = "always")

# factors (character vectors are similar) -----
set.seed(123)
x <- as.factor(sample(c("a", "b", "c"), 15, TRUE))
table(x)

out <- recode_values(x, list(x = "a", y = c("b", "c")))
out
table(out)

out <- recode_values(x, list(x = "a", y = "b", z = "c"))
```

```

out
table(out)

out <- recode_values(x, list(y = "b,c"), default = 77)
# same as
# recode_values(x, list(y = c("b", "c")), default = 77)
out
table(out)

# data frames -----
set.seed(123)
d <- data.frame(
  x = sample(c(1:4, NA), 12, TRUE),
  y = as.factor(sample(c("a", "b", "c"), 12, TRUE)),
  stringsAsFactors = FALSE
)

recode_values(
  d,
  recode = list(`0` = 1, `1` = 2:3, `2` = 4, x = "a", y = c("b", "c")),
  append = TRUE
)

# switch recode pattern to "old=new" -----
options(data_recode_pattern = "old=new")

# numeric
set.seed(123)
x <- sample(c(1:4, NA), 15, TRUE)
table(x, useNA = "always")

out <- recode_values(x, list(`1` = 0, `2:3` = 1, `4` = 2))
table(out, useNA = "always")

# factors (character vectors are similar)
set.seed(123)
x <- as.factor(sample(c("a", "b", "c"), 15, TRUE))
table(x)

out <- recode_values(x, list(a = "x", `b, c` = "y"))
table(out)

# reset options
options(data_recode_pattern = NULL)

```

Description

These functions check which rows or columns of a data frame completely contain missing values, i.e. which observations or variables completely have missing values, and either (1) returns their indices; or (2) removes them from the data frame.

Usage

```
empty_columns(x)

empty_rows(x)

remove_empty_columns(x)

remove_empty_rows(x)

remove_empty(x)
```

Arguments

x A data frame.

Details

For character vectors, empty string values (i.e. "") are also considered as missing value. Thus, if a character vector only contains NA and "", it is considered as empty variable and will be removed. Same applies to data frames.

Value

- For `empty_columns()` and `empty_rows()`, a numeric (named) vector with row or column indices of those variables that completely have missing values.
- For `remove_empty_columns()` and `remove_empty_rows()`, a data frame with "empty" columns or rows removed, respectively.
- For `remove_empty()`, **both** empty rows and columns will be removed.

Examples

```
tmp <- data.frame(
  a = c(1, 2, 3, NA, 5),
  b = c(1, NA, 3, NA, 5),
  c = c(NA, NA, NA, NA, NA),
  d = c(1, NA, 3, NA, 5)
)

tmp

# indices of empty columns or rows
empty_columns(tmp)
empty_rows(tmp)

# remove empty columns or rows
```

```
remove_empty_columns(tmp)
remove_empty_rows(tmp)

# remove empty columns and rows
remove_empty(tmp)

# also remove "empty" character vectors
tmp <- data.frame(
  a = c(1, 2, 3, NA, 5),
  b = c(1, NA, 3, NA, 5),
  c = c("", "", "", "", ""),
  stringsAsFactors = FALSE
)
empty_columns(tmp)
```

replace_nan_inf

Convert infinite or NaN values into NA

Description

Replaces all infinite (Inf and -Inf) or NaN values with NA.

Usage

```
replace_nan_inf(x, ...)
```

Arguments

x	A vector or a dataframe
...	Currently not used.

Value

Data with Inf, -Inf, and NaN converted to NA.

Examples

```
# a vector
x <- c(1, 2, NA, 3, NaN, 4, NA, 5, Inf, -Inf, 6, 7)
replace_nan_inf(x)

# a data frame
df <- data.frame(
  x = c(1, NA, 5, Inf, 2, NA),
  y = c(3, NaN, 4, -Inf, 6, 7),
  stringsAsFactors = FALSE
)
replace_nan_inf(df)
```

rescale	<i>Rescale Variables to a New Range</i>
---------	---

Description

Rescale variables to a new range. Can also be used to reverse-score variables (change the keying/scoring direction).

Usage

```
rescale(x, ...)

change_scale(x, ...)

## S3 method for class 'numeric'
rescale(x, to = c(0, 100), range = NULL, verbose = TRUE, ...)

## S3 method for class 'data.frame'
rescale(
  x,
  select = NULL,
  exclude = NULL,
  to = c(0, 100),
  range = NULL,
  ignore_case = FALSE,
  regex = FALSE,
  verbose = FALSE,
  ...
)
```

Arguments

<code>x</code>	A (grouped) data frame, numeric vector or factor.
<code>...</code>	Arguments passed to or from other methods.
<code>to</code>	Numeric vector of length 2 giving the new range that the variable will have after rescaling. To reverse-score a variable, the range should be given with the maximum value first. See examples.
<code>range</code>	Initial (old) range of values. If NULL, will take the range of the input vector (<code>range(x)</code>).
<code>verbose</code>	Toggle warnings.
<code>select</code>	Variables that will be included when performing the required tasks. Can be either <ul style="list-style-type: none"> • a variable specified as a literal variable name (e.g., <code>column_name</code>), • a string with the variable name (e.g., <code>"column_name"</code>), or a character vector of variable names (e.g., <code>c("col1", "col2", "col3")</code>),

- a formula with variable names (e.g., `~column_1 + column_2`),
- a vector of positive integers, giving the positions counting from the left (e.g. `1` or `c(1, 3, 5)`),
- a vector of negative integers, giving the positions counting from the right (e.g., `-1` or `-1:-3`),
- one of the following select-helpers: `starts_with()`, `ends_with()`, `contains()`, a range using `:` or `regex("")`. `starts_with()`, `ends_with()`, and `contains()` accept several patterns, e.g. `starts_with("Sep", "Petal")`.
- or a function testing for logical conditions, e.g. `is.numeric()` (or `is.numeric`), or any user-defined function that selects the variables for which the function returns TRUE (like: `foo <- function(x) mean(x) > 3`),
- ranges specified via literal variable names, select-helpers (except `regex()`) and (user-defined) functions can be negated, i.e. return non-matching elements, when prefixed with a `-`, e.g. `-ends_with("")`, `-is.numeric` or `-(Sepal.Width:Petal.Length)`. **Note:** Negation means that matches are *excluded*, and thus, the `exclude` argument can be used alternatively. For instance, `select=-ends_with("Length")` (with `-`) is equivalent to `exclude=ends_with("Length")` (no `-`). In case negation should not work as expected, use the `exclude` argument instead.

If NULL, selects all columns. Patterns that found no matches are silently ignored, e.g. `find_columns(iris, select = c("Species", "Test"))` will just return "Species".

<code>exclude</code>	See <code>select</code> , however, column names matched by the pattern from <code>exclude</code> will be excluded instead of selected. If NULL (the default), excludes no columns.
<code>ignore_case</code>	Logical, if TRUE and when one of the select-helpers or a regular expression is used in <code>select</code> , ignores lower/upper case in the search pattern when matching against variable names.
<code>regex</code>	Logical, if TRUE, the search pattern from <code>select</code> will be treated as regular expression. When <code>regex = TRUE</code> , <code>select</code> <i>must</i> be a character string (or a variable containing a character string) and is not allowed to be one of the supported select-helpers or a character vector of length > 1. <code>regex = TRUE</code> is comparable to using one of the two select-helpers, <code>select = contains("")</code> or <code>select = regex("")</code> , however, since the select-helpers may not work when called from inside other functions (see 'Details'), this argument may be used as workaround.

Value

A rescaled object.

Selection of variables - the `select` argument

For most functions that have a `select` argument (including this function), the complete input data frame is returned, even when `select` only selects a range of variables. That is, the function is only applied to those variables that have a match in `select`, while all other variables remain unchanged. In other words: for this function, `select` will not omit any non-included variables, so that the returned data frame will include all variables from the input data frame.

See Also

See `makepredictcall.dw_transformer()` for use in model formulas.

Other transform utilities: `normalize()`, `ranktransform()`, `reverse()`, `standardize()`

Examples

```
rescale(c(0, 1, 5, -5, -2))
rescale(c(0, 1, 5, -5, -2), to = c(-5, 5))
rescale(c(1, 2, 3, 4, 5), to = c(-2, 2))

# Specify the "theoretical" range of the input vector
rescale(c(1, 3, 4), to = c(0, 40), range = c(0, 4))

# Reverse-score a variable
rescale(c(1, 2, 3, 4, 5), to = c(5, 1))
rescale(c(1, 2, 3, 4, 5), to = c(2, -2))

# Data frames
head(rescale(iris, to = c(0, 1)))
head(rescale(iris, to = c(0, 1), select = "Sepal.Length"))

# One can specify a list of ranges
head(rescale(iris, to = list(
  "Sepal.Length" = c(0, 1),
  "Petal.Length" = c(-1, 0)
)))
```

rescale_weights

Rescale design weights for multilevel analysis

Description

Most functions to fit multilevel and mixed effects models only allow to specify frequency weights, but not design (i.e. sampling or probability) weights, which should be used when analyzing complex samples and survey data. `rescale_weights()` implements an algorithm proposed by *Asparouhov (2006)* and *Carle (2009)* to rescale design weights in survey data to account for the grouping structure of multilevel models, which then can be used for multilevel modelling.

Usage

```
rescale_weights(data, group, probability_weights, nest = FALSE)
```

Arguments

<code>data</code>	A data frame.
<code>group</code>	Variable names (as character vector, or as formula), indicating the grouping structure (strata) of the survey data (level-2-cluster variable). It is also possible to create weights for multiple group variables; in such cases, each created weighting variable will be suffixed by the name of the group variable.

probability_weights	Variable indicating the probability (design or sampling) weights of the survey data (level-1-weight).
nest	Logical, if TRUE and group indicates at least two group variables, then groups are "nested", i.e. groups are now a combination from each group level of the variables in group.

Details

Rescaling is based on two methods: For `pweights_a`, the sample weights `probability_weights` are adjusted by a factor that represents the proportion of group size divided by the sum of sampling weights within each group. The adjustment factor for `pweights_b` is the sum of sample weights within each group divided by the sum of squared sample weights within each group (see Carle (2009), Appendix B). In other words, `pweights_a` "scales the weights so that the new weights sum to the cluster sample size" while `pweights_b` "scales the weights so that the new weights sum to the effective cluster size".

Regarding the choice between scaling methods A and B, Carle suggests that "analysts who wish to discuss point estimates should report results based on weighting method A. For analysts more interested in residual between-group variance, method B may generally provide the least biased estimates". In general, it is recommended to fit a non-weighted model and weighted models with both scaling methods and when comparing the models, see whether the "inferential decisions converge", to gain confidence in the results.

Though the bias of scaled weights decreases with increasing group size, method A is preferred when insufficient or low group size is a concern.

The group ID and probably PSU may be used as random effects (e.g. nested design, or group and PSU as varying intercepts), depending on the survey design that should be mimicked.

Value

data, including the new weighting variables: `pweights_a` and `pweights_b`, which represent the rescaled design weights to use in multilevel models (use these variables for the `weights` argument).

References

- Carle A.C. (2009). Fitting multilevel models in complex survey data with design weights: Recommendations. *BMC Medical Research Methodology* 9(49): 1-13
- Asparouhov T. (2006). General Multi-Level Modeling with Sampling Weights. *Communications in Statistics - Theory and Methods* 35: 439-460

Examples

```
if (require("lme4")) {
  data(nhanes_sample)
  head(rescale_weights(nhanes_sample, "SDMVSTRA", "WTINT2YR"))

  # also works with multiple group-variables
  head(rescale_weights(nhanes_sample, c("SDMVSTRA", "SDMVPSU"), "WTINT2YR"))

  # or nested structures.
```



```

x <- rescale_weights(
  data = nhanes_sample,
  group = c("SDMVSTRA", "SDMVPSU"),
  probability_weights = "WTINT2YR",
  nest = TRUE
)
head(x)

nhanes_sample <- rescale_weights(nhanes_sample, "SDMVSTRA", "WTINT2YR")

glmer(
  total ~ factor(RIAGENDR) * (log(age) + factor(RIDRETH1)) + (1 | SDMVPSU),
  family = poisson(),
  data = nhanes_sample,
  weights = pweights_a
)
}

```

 reshape_ci

Reshape CI between wide/long formats

Description

Reshape CI between wide/long formats.

Usage

```
reshape_ci(x, ci_type = "CI")
```

Arguments

x	A data frame containing columns named CI_low and CI_high (or similar, see ci_type).
ci_type	String indicating the "type" (i.e. prefix) of the interval columns. Per <i>easystats</i> convention, confidence or credible intervals are named CI_low and CI_high, and the related ci_type would be "CI". If column names for other intervals differ, ci_type can be used to indicate the name, e.g. ci_type = "SI" can be used for support intervals, where the column names in the data frame would be SI_low and SI_high.

Value

A data frame with columns corresponding to confidence intervals reshaped either to wide or long format.

Examples

```
x <- data.frame(
  Parameter = c("Term 1", "Term 2", "Term 1", "Term 2"),
  CI = c(.8, .8, .9, .9),
  CI_low = c(.2, .3, .1, .15),
  CI_high = c(.5, .6, .8, .85),
  stringsAsFactors = FALSE
)

reshape_ci(x)
reshape_ci(reshape_ci(x))
```

reverse

*Reverse-Score Variables***Description**

Reverse-score variables (change the keying/scoring direction).

Usage

```
reverse(x, ...)

reverse_scale(x, ...)

## S3 method for class 'numeric'
reverse(x, range = NULL, verbose = TRUE, ...)

## S3 method for class 'data.frame'
reverse(
  x,
  select = NULL,
  exclude = NULL,
  range = NULL,
  ignore_case = FALSE,
  regex = FALSE,
  verbose = FALSE,
  ...
)
```

Arguments

x	A (grouped) data frame, numeric vector or factor.
...	Arguments passed to or from other methods.
range	Range of values that is used as reference for reversing the scale. For numeric variables, can be NULL or a numeric vector of length two, indicating the lowest and highest value of the reference range. If NULL, will take the range of the input

	vector (<code>range(x)</code>). For factors, range can be NULL, a numeric vector of length two, or a (numeric) vector of at least the same length as factor levels (i.e. must be equal to or larger than <code>nlevels(x)</code>). Note that providing a range for factors usually only makes sense when factor levels are numeric, not characters.
verbose	Toggle warnings.
select	<p>Variables that will be included when performing the required tasks. Can be either</p> <ul style="list-style-type: none"> • a variable specified as a literal variable name (e.g., <code>column_name</code>), • a string with the variable name (e.g., <code>"column_name"</code>), or a character vector of variable names (e.g., <code>c("col1", "col2", "col3")</code>), • a formula with variable names (e.g., <code>~column_1 + column_2</code>), • a vector of positive integers, giving the positions counting from the left (e.g. 1 or <code>c(1, 3, 5)</code>), • a vector of negative integers, giving the positions counting from the right (e.g., -1 or <code>-1:-3</code>), • one of the following select-helpers: <code>starts_with()</code>, <code>ends_with()</code>, <code>contains()</code>, a range using <code>:</code> or <code>regex("")</code>. <code>starts_with()</code>, <code>ends_with()</code>, and <code>contains()</code> accept several patterns, e.g. <code>starts_with("Sep", "Petal")</code>. • or a function testing for logical conditions, e.g. <code>is.numeric()</code> (or <code>is.numeric</code>), or any user-defined function that selects the variables for which the function returns TRUE (like: <code>foo <- function(x) mean(x) > 3</code>), • ranges specified via literal variable names, select-helpers (except <code>regex()</code>) and (user-defined) functions can be negated, i.e. return non-matching elements, when prefixed with a <code>-</code>, e.g. <code>-ends_with("")</code>, <code>-is.numeric</code> or <code>-(Sepal.Width:Petal.Length)</code>. Note: Negation means that matches are <i>excluded</i>, and thus, the <code>exclude</code> argument can be used alternatively. For instance, <code>select=-ends_with("Length")</code> (with <code>-</code>) is equivalent to <code>exclude=ends_with("Length")</code> (no <code>-</code>). In case negation should not work as expected, use the <code>exclude</code> argument instead. <p>If NULL, selects all columns. Patterns that found no matches are silently ignored, e.g. <code>find_columns(iris, select = c("Species", "Test"))</code> will just return "Species".</p>
exclude	See <code>select</code> , however, column names matched by the pattern from <code>exclude</code> will be excluded instead of selected. If NULL (the default), excludes no columns.
ignore_case	Logical, if TRUE and when one of the select-helpers or a regular expression is used in <code>select</code> , ignores lower/upper case in the search pattern when matching against variable names.
regex	Logical, if TRUE, the search pattern from <code>select</code> will be treated as regular expression. When <code>regex = TRUE</code> , <code>select</code> <i>must</i> be a character string (or a variable containing a character string) and is not allowed to be one of the supported select-helpers or a character vector of length > 1. <code>regex = TRUE</code> is comparable to using one of the two select-helpers, <code>select = contains("")</code> or <code>select = regex("")</code> , however, since the select-helpers may not work when called from inside other functions (see 'Details'), this argument may be used as workaround.

Value

A reverse-scored object.

Selection of variables - the select argument

For most functions that have a select argument (including this function), the complete input data frame is returned, even when select only selects a range of variables. That is, the function is only applied to those variables that have a match in select, while all other variables remain unchanged. In other words: for this function, select will not omit any non-included variables, so that the returned data frame will include all variables from the input data frame.

See Also

Other transform utilities: [normalize\(\)](#), [ranktransform\(\)](#), [rescale\(\)](#), [standardize\(\)](#)

Examples

```
reverse(c(1, 2, 3, 4, 5))
reverse(c(-2, -1, 0, 2, 1))

# Specify the "theoretical" range of the input vector
reverse(c(1, 3, 4), range = c(0, 4))

# Factor variables
reverse(factor(c(1, 2, 3, 4, 5)))
reverse(factor(c(1, 2, 3, 4, 5)), range = 0:10)

# Data frames
head(reverse(iris))
head(reverse(iris, select = "Sepal.Length"))
```

rownames_as_column *Tools for working with row names*

Description

Tools for working with row names

Usage

```
rownames_as_column(x, var = "rowname")
column_as_rownames(x, var = "rowname")
```

Arguments

x	A data frame.
var	Name of column to use for rownames. For <code>column_as_rownames()</code> , this argument can be the variable name or the column number.

Value

rownames_as_column() and column_as_rownames() both return a data frame.

Examples

```
# Convert between row names and column -----
test <- rownames_as_column(mtcars, var = "car")
test
head(column_as_rownames(test, var = "car"))
```

row_to_colnames	<i>Tools for working with column names</i>
-----------------	--

Description

Tools for working with column names

Usage

```
row_to_colnames(x, row = 1, na_prefix = "x", verbose = TRUE)
```

```
colnames_to_row(x, prefix = "x")
```

Arguments

x	A data frame.
row	Row to use as column names.
na_prefix	Prefix to give to the column name if the row has an NA. Default is 'x', and it will be incremented at each NA (x1, x2, etc.).
verbose	Toggle warnings.
prefix	Prefix to give to the column name. Default is 'x', and it will be incremented at each column (x1, x2, etc.).

Value

row_to_colnames() and colnames_to_row() both return a data frame.

Examples

```
# Convert a row to column names -----
test <- data.frame(
  a = c("iso", 2, 5),
  b = c("year", 3, 6),
  c = c("value", 5, 7)
)
test
```

```

row_to_colnames(test)

# Convert column names to row -----
test <- data.frame(
  ARG = c("BRA", "FRA"),
  `1960` = c(1960, 1960),
  `2000` = c(2000, 2000)
)
test
colnames_to_row(test)

```

skewness

Compute Skewness and (Excess) Kurtosis

Description

Compute Skewness and (Excess) Kurtosis

Usage

```
skewness(x, na.rm = TRUE, type = "2", iterations = NULL, verbose = TRUE, ...)
```

```
kurtosis(x, na.rm = TRUE, type = "2", iterations = NULL, verbose = TRUE, ...)
```

```
## S3 method for class 'parameters_kurtosis'
print(x, digits = 3, test = FALSE, ...)
```

```
## S3 method for class 'parameters_skewness'
print(x, digits = 3, test = FALSE, ...)
```

```
## S3 method for class 'parameters_skewness'
summary(object, test = FALSE, ...)
```

```
## S3 method for class 'parameters_kurtosis'
summary(object, test = FALSE, ...)
```

Arguments

x	A numeric vector or data.frame.
na.rm	Remove missing values.
type	Type of algorithm for computing skewness. May be one of 1 (or "1", "I" or "classic"), 2 (or "2", "II" or "SPSS" or "SAS") or 3 (or "3", "III" or "Minitab"). See 'Details'.
iterations	The number of bootstrap replicates for computing standard errors. If NULL (default), parametric standard errors are computed.
verbose	Toggle warnings and messages.

...	Arguments passed to or from other methods.
digits	Number of decimal places.
test	Logical, if TRUE, tests if skewness or kurtosis is significantly different from zero.
object	An object returned by skewness() or kurtosis().

Details

Skewness: Symmetric distributions have a skewness around zero, while a negative skewness values indicates a "left-skewed" distribution, and a positive skewness values indicates a "right-skewed" distribution. Examples for the relationship of skewness and distributions are:

- Normal distribution (and other symmetric distribution) has a skewness of 0
- Half-normal distribution has a skewness just below 1
- Exponential distribution has a skewness of 2
- Lognormal distribution can have a skewness of any positive value, depending on its parameters

(<https://en.wikipedia.org/wiki/Skewness>)

Types of Skewness: skewness() supports three different methods for estimating skewness, as discussed in *Joanes and Gill (1988)*:

- Type "1" is the "classical" method, which is $g1 = (\text{sum}((x - \text{mean}(x))^3) / n) / (\text{sum}((x - \text{mean}(x))^2) / n)^{1.5}$
- Type "2" first calculates the type-1 skewness, then adjusts the result: $G1 = g1 * \text{sqrt}(n * (n - 1)) / (n - 2)$. This is what SAS and SPSS usually return.
- Type "3" first calculates the type-1 skewness, then adjusts the result: $b1 = g1 * ((1 - 1 / n))^{1.5}$. This is what Minitab usually returns.

Kurtosis: The kurtosis is a measure of "tailedness" of a distribution. A distribution with a kurtosis values of about zero is called "mesokurtic". A kurtosis value larger than zero indicates a "leptokurtic" distribution with *fatter* tails. A kurtosis value below zero indicates a "platykurtic" distribution with *thinner* tails (<https://en.wikipedia.org/wiki/Kurtosis>).

Types of Kurtosis: kurtosis() supports three different methods for estimating kurtosis, as discussed in *Joanes and Gill (1988)*:

- Type "1" is the "classical" method, which is $g2 = n * \text{sum}((x - \text{mean}(x))^4) / (\text{sum}((x - \text{mean}(x))^2)^2) - 3$.
- Type "2" first calculates the type-1 kurtosis, then adjusts the result: $G2 = ((n + 1) * g2 + 6) * (n - 1) / ((n - 2) * (n - 3))$. This is what SAS and SPSS usually return
- Type "3" first calculates the type-1 kurtosis, then adjusts the result: $b2 = (g2 + 3) * (1 - 1 / n)^2 - 3$. This is what Minitab usually returns.

Standard Errors: It is recommended to compute empirical (bootstrapped) standard errors (via the iterations argument) than relying on analytic standard errors (*Wright & Herrington, 2011*).

Value

Values of skewness or kurtosis.

References

- D. N. Joanes and C. A. Gill (1998). Comparing measures of sample skewness and kurtosis. *The Statistician*, 47, 183–189.
- Wright, D. B., & Herrington, J. A. (2011). Problematic standard errors and confidence intervals for skewness and kurtosis. *Behavior research methods*, 43(1), 8-17.

Examples

```
skewness(rnorm(1000))
kurtosis(rnorm(1000))
```

slide

Shift numeric value range

Description

This functions shifts the value range of a numeric variable, so that the new range starts at a given value.

Usage

```
slide(x, ...)

## S3 method for class 'numeric'
slide(x, lowest = 0, ...)

## S3 method for class 'data.frame'
slide(
  x,
  select = NULL,
  exclude = NULL,
  lowest = 0,
  append = FALSE,
  ignore_case = FALSE,
  regex = FALSE,
  verbose = TRUE,
  ...
)
```

Arguments

x	A data frame or numeric vector.
...	not used.
lowest	Numeric, indicating the lowest (minimum) value when converting factors or character vectors to numeric values.

select	<p>Variables that will be included when performing the required tasks. Can be either</p> <ul style="list-style-type: none"> • a variable specified as a literal variable name (e.g., <code>column_name</code>), • a string with the variable name (e.g., <code>"column_name"</code>), or a character vector of variable names (e.g., <code>c("col1", "col2", "col3")</code>), • a formula with variable names (e.g., <code>~column_1 + column_2</code>), • a vector of positive integers, giving the positions counting from the left (e.g. <code>1</code> or <code>c(1, 3, 5)</code>), • a vector of negative integers, giving the positions counting from the right (e.g., <code>-1</code> or <code>-1:-3</code>), • one of the following select-helpers: <code>starts_with()</code>, <code>ends_with()</code>, <code>contains()</code>, a range using <code>:</code> or <code>regex("")</code>. <code>starts_with()</code>, <code>ends_with()</code>, and <code>contains()</code> accept several patterns, e.g. <code>starts_with("Sep", "Petal")</code>. • or a function testing for logical conditions, e.g. <code>is.numeric()</code> (or <code>is.numeric</code>), or any user-defined function that selects the variables for which the function returns TRUE (like: <code>foo <- function(x) mean(x) > 3</code>), • ranges specified via literal variable names, select-helpers (except <code>regex()</code>) and (user-defined) functions can be negated, i.e. return non-matching elements, when prefixed with a <code>-</code>, e.g. <code>-ends_with("")</code>, <code>-is.numeric</code> or <code>-(Sepal.Width:Petal.Length)</code>. Note: Negation means that matches are <i>excluded</i>, and thus, the <code>exclude</code> argument can be used alternatively. For instance, <code>select=-ends_with("Length")</code> (with <code>-</code>) is equivalent to <code>exclude=ends_with("Length")</code> (no <code>-</code>). In case negation should not work as expected, use the <code>exclude</code> argument instead. <p>If NULL, selects all columns. Patterns that found no matches are silently ignored, e.g. <code>find_columns(iris, select = c("Species", "Test"))</code> will just return "Species".</p>
exclude	See <code>select</code> , however, column names matched by the pattern from <code>exclude</code> will be excluded instead of selected. If NULL (the default), excludes no columns.
append	Logical or string. If TRUE, recoded or converted variables get new column names and are appended (column bind) to <code>x</code> , thus returning both the original and the recoded variables. The new columns get a suffix, based on the calling function: <code>"_r"</code> for recode functions, <code>"_n"</code> for <code>to_numeric()</code> , <code>"_f"</code> for <code>to_factor()</code> , or <code>"_s"</code> for <code>slide()</code> . If <code>append=FALSE</code> , original variables in <code>x</code> will be overwritten by their recoded versions. If a character value, recoded variables are appended with new column names (using the defined suffix) to the original data frame.
ignore_case	Logical, if TRUE and when one of the select-helpers or a regular expression is used in <code>select</code> , ignores lower/upper case in the search pattern when matching against variable names.
regex	Logical, if TRUE, the search pattern from <code>select</code> will be treated as regular expression. When <code>regex = TRUE</code> , <code>select</code> <i>must</i> be a character string (or a variable containing a character string) and is not allowed to be one of the supported select-helpers or a character vector of length > 1. <code>regex = TRUE</code> is comparable to using one of the two select-helpers, <code>select = contains("")</code> or <code>select = regex("")</code> , however, since the select-helpers may not work when called from inside other functions (see 'Details'), this argument may be used as workaround.
verbose	Toggle warnings.

Value

`x`, where the range of numeric variables starts at a new value.

Selection of variables - the `select` argument

For most functions that have a `select` argument (including this function), the complete input data frame is returned, even when `select` only selects a range of variables. That is, the function is only applied to those variables that have a match in `select`, while all other variables remain unchanged. In other words: for this function, `select` will not omit any non-included variables, so that the returned data frame will include all variables from the input data frame.

See Also

- Functions to rename stuff: `data_rename()`, `data_rename_rows()`, `data_addprefix()`, `data_addsuffix()`
- Functions to reorder or remove columns: `data_reorder()`, `data_relocate()`, `data_remove()`
- Functions to reshape, pivot or rotate data frames: `data_to_long()`, `data_to_wide()`, `data_rotate()`
- Functions to recode data: `rescale()`, `reverse()`, `categorize()`, `recode_values()`, `slide()`
- Functions to standardize, normalize, rank-transform: `center()`, `standardize()`, `normalize()`, `ranktransform()`, `winsorize()`
- Split and merge data frames: `data_partition()`, `data_merge()`
- Functions to find or select columns: `data_select()`, `data_find()`
- Functions to filter rows: `data_match()`, `data_filter()`

Examples

```
# numeric
head(mtcars$gear)
head(slide(mtcars$gear))
head(slide(mtcars$gear, lowest = 10))

# data frame
sapply(slide(mtcars, lowest = 1), min)
sapply(mtcars, min)
```

smoothness

Quantify the smoothness of a vector

Description

Quantify the smoothness of a vector

Usage

```
smoothness(x, method = "cor", lag = 1, iterations = NULL, ...)
```

Arguments

x	Numeric vector (similar to a time series).
method	Can be "diff" (the standard deviation of the standardized differences) or "cor" (default, lag-one autocorrelation).
lag	An integer indicating which lag to use. If less than 1, will be interpreted as expressed in percentage of the length of the vector.
iterations	The number of bootstrap replicates for computing standard errors. If NULL (default), parametric standard errors are computed.
...	Arguments passed to or from other methods.

Value

Value of smoothness.

References

<https://stats.stackexchange.com/questions/24607/how-to-measure-smoothness-of-a-time-series-in-r>

Examples

```
x <- (-10:10)^3 + rnorm(21, 0, 100)
plot(x)
smoothness(x, method = "cor")
smoothness(x, method = "diff")
```

standardize	<i>Standardization (Z-scoring)</i>
-------------	------------------------------------

Description

Performs a standardization of data (z-scoring), i.e., centering and scaling, so that the data is expressed in terms of standard deviation (i.e., mean = 0, SD = 1) or Median Absolute Deviance (median = 0, MAD = 1). When applied to a statistical model, this function extracts the dataset, standardizes it, and refits the model with this standardized version of the dataset. The [normalize\(\)](#) function can also be used to scale all numeric variables within the 0 - 1 range.

For model standardization, see [standardize.default\(\)](#).

Usage

```
standardize(x, ...)

standardise(x, ...)

## S3 method for class 'numeric'
standardize(
```

```
x,  
robust = FALSE,  
two_sd = FALSE,  
weights = NULL,  
reference = NULL,  
center = NULL,  
scale = NULL,  
verbose = TRUE,  
...  
)  
  
## S3 method for class 'factor'  
standardize(  
  x,  
  robust = FALSE,  
  two_sd = FALSE,  
  weights = NULL,  
  force = FALSE,  
  verbose = TRUE,  
  ...  
)  
  
## S3 method for class 'data.frame'  
standardize(  
  x,  
  select = NULL,  
  exclude = NULL,  
  robust = FALSE,  
  two_sd = FALSE,  
  weights = NULL,  
  reference = NULL,  
  center = NULL,  
  scale = NULL,  
  remove_na = c("none", "selected", "all"),  
  force = FALSE,  
  append = FALSE,  
  ignore_case = FALSE,  
  regex = FALSE,  
  verbose = TRUE,  
  ...  
)  
  
unstandardize(x, ...)  
  
unstandardise(x, ...)  
  
## S3 method for class 'numeric'  
unstandardize(  
  x,  
  robust = FALSE,  
  two_sd = FALSE,  
  weights = NULL,  
  reference = NULL,  
  center = NULL,  
  scale = NULL,  
  verbose = TRUE,  
  ...  
)
```

```

    x,
    center = NULL,
    scale = NULL,
    reference = NULL,
    robust = FALSE,
    two_sd = FALSE,
    ...
)

## S3 method for class 'data.frame'
unstandardize(
  x,
  center = NULL,
  scale = NULL,
  reference = NULL,
  robust = FALSE,
  two_sd = FALSE,
  select = NULL,
  exclude = NULL,
  ignore_case = FALSE,
  regex = FALSE,
  verbose = TRUE,
  ...
)

```

Arguments

x	A (grouped) data frame, a vector or a statistical model (for unstandardize() cannot be a model).
...	Arguments passed to or from other methods.
robust	Logical, if TRUE, centering is done by subtracting the median from the variables and dividing it by the median absolute deviation (MAD). If FALSE, variables are standardized by subtracting the mean and dividing it by the standard deviation (SD).
two_sd	If TRUE, the variables are scaled by two times the deviation (SD or MAD depending on robust). This method can be useful to obtain model coefficients of continuous parameters comparable to coefficients related to binary predictors, when applied to the predictors (not the outcome) (Gelman, 2008).
weights	Can be NULL (for no weighting), or: <ul style="list-style-type: none"> • For model: if TRUE (default), a weighted-standardization is carried out. • For data.frames: a numeric vector of weights, or a character of the name of a column in the data.frame that contains the weights. • For numeric vectors: a numeric vector of weights.
reference	A data frame or variable from which the centrality and deviation will be computed instead of from the input variable. Useful for standardizing a subset or new data according to another data frame.

- center, scale
- For `standardize()`:
Numeric values, which can be used as alternative to reference to define a reference centrality and deviation. If scale and center are of length 1, they will be recycled to match the length of selected variables for standardization. Else, center and scale must be of same length as the number of selected variables. Values in center and scale will be matched to selected variables in the provided order, unless a named vector is given. In this case, names are matched against the names of the selected variables.
 - For `unstandardize()`:
center and scale correspond to the center (the mean / median) and the scale (SD / MAD) of the original non-standardized data (for data frames, should be named, or have column order correspond to the numeric column). However, one can also directly provide the original data through reference, from which the center and the scale will be computed (according to `robust` and `two_sd`). Alternatively, if the input contains the attributes center and scale (as does the output of `standardize()`), it will take it from there if the rest of the arguments are absent.
- verbose Toggle warnings and messages on or off.
- force Logical, if TRUE, forces recoding of factors and character vectors as well.
- select Variables that will be included when performing the required tasks. Can be either
- a variable specified as a literal variable name (e.g., `column_name`),
 - a string with the variable name (e.g., `"column_name"`), or a character vector of variable names (e.g., `c("col1", "col2", "col3")`),
 - a formula with variable names (e.g., `~column_1 + column_2`),
 - a vector of positive integers, giving the positions counting from the left (e.g. 1 or `c(1, 3, 5)`),
 - a vector of negative integers, giving the positions counting from the right (e.g., -1 or `-1:-3`),
 - one of the following select-helpers: `starts_with()`, `ends_with()`, `contains()`, a range using `:` or `regex("")`. `starts_with()`, `ends_with()`, and `contains()` accept several patterns, e.g. `starts_with("Sep", "Petal")`.
 - or a function testing for logical conditions, e.g. `is.numeric()` (or `is.numeric`), or any user-defined function that selects the variables for which the function returns TRUE (like: `foo <- function(x) mean(x) > 3`),
 - ranges specified via literal variable names, select-helpers (except `regex()`) and (user-defined) functions can be negated, i.e. return non-matching elements, when prefixed with a `-`, e.g. `-ends_with("")`, `-is.numeric` or `-(Sepal.Width:Petal.Length)`. **Note:** Negation means that matches are *excluded*, and thus, the `exclude` argument can be used alternatively. For instance, `select=-ends_with("Length")` (with `-`) is equivalent to `exclude=ends_with("Length")` (no `-`). In case negation should not work as expected, use the `exclude` argument instead.
- If NULL, selects all columns. Patterns that found no matches are silently ignored, e.g. `find_columns(iris, select = c("Species", "Test"))` will just return "Species".

<code>exclude</code>	See <code>select</code> , however, column names matched by the pattern from <code>exclude</code> will be excluded instead of selected. If <code>NULL</code> (the default), excludes no columns.
<code>remove_na</code>	How should missing values (NA) be treated: if <code>"none"</code> (default): each column's standardization is done separately, ignoring NAs. Else, rows with NA in the columns selected with <code>select / exclude</code> (<code>"selected"</code>) or in all columns (<code>"all"</code>) are dropped before standardization, and the resulting data frame does not include these cases.
<code>append</code>	Logical or string. If <code>TRUE</code> , standardized variables get new column names (with the suffix <code>"_z"</code>) and are appended (column bind) to <code>x</code> , thus returning both the original and the standardized variables. If <code>FALSE</code> , original variables in <code>x</code> will be overwritten by their standardized versions. If a character value, standardized variables are appended with new column names (using the defined suffix) to the original data frame.
<code>ignore_case</code>	Logical, if <code>TRUE</code> and when one of the select-helpers or a regular expression is used in <code>select</code> , ignores lower/upper case in the search pattern when matching against variable names.
<code>regex</code>	Logical, if <code>TRUE</code> , the search pattern from <code>select</code> will be treated as regular expression. When <code>regex = TRUE</code> , <code>select</code> <i>must</i> be a character string (or a variable containing a character string) and is not allowed to be one of the supported select-helpers or a character vector of length > 1. <code>regex = TRUE</code> is comparable to using one of the two select-helpers, <code>select = contains("")</code> or <code>select = regex("")</code> , however, since the select-helpers may not work when called from inside other functions (see 'Details'), this argument may be used as workaround.

Value

The standardized object (either a standardize data frame or a statistical model fitted on standardized data).

Selection of variables - the `select` argument

For most functions that have a `select` argument (including this function), the complete input data frame is returned, even when `select` only selects a range of variables. That is, the function is only applied to those variables that have a match in `select`, while all other variables remain unchanged. In other words: for this function, `select` will not omit any non-included variables, so that the returned data frame will include all variables from the input data frame.

Note

When `x` is a vector or a data frame with `remove_na = "none"`, missing values are preserved, so the return value has the same length / number of rows as the original input.

See Also

See [center\(\)](#) for grand-mean centering of variables, and [makepredictcall.dw_transformer\(\)](#) for use in model formulas.

Other transform utilities: [normalize\(\)](#), [ranktransform\(\)](#), [rescale\(\)](#), [reverse\(\)](#)

Other standardize: [standardize.default\(\)](#)

Examples

```

d <- iris[1:4, ]

# vectors
standardize(d$Petal.Length)

# Data frames
# overwrite
standardize(d, select = c("Sepal.Length", "Sepal.Width"))

# append
standardize(d, select = c("Sepal.Length", "Sepal.Width"), append = TRUE)

# append, suffix
standardize(d, select = c("Sepal.Length", "Sepal.Width"), append = "_std")

# standardizing with reference center and scale
d <- data.frame(
  a = c(-2, -1, 0, 1, 2),
  b = c(3, 4, 5, 6, 7)
)

# default standardization, based on mean and sd of each variable
standardize(d) # means are 0 and 5, sd ~ 1.581139

# standardization, based on mean and sd set to the same values
standardize(d, center = c(0, 5), scale = c(1.581, 1.581))

# standardization, mean and sd for each variable newly defined
standardize(d, center = c(3, 4), scale = c(2, 4))

# standardization, taking same mean and sd for each variable
standardize(d, center = 1, scale = 3)

```

standardize.default *Re-fit a model with standardized data*

Description

Performs a standardization of data (z-scoring) using `standardize()` and then re-fits the model to the standardized data.

Standardization is done by completely refitting the model on the standardized data. Hence, this approach is equal to standardizing the variables *before* fitting the model and will return a new model object. This method is particularly recommended for complex models that include interactions or transformations (e.g., polynomial or spline terms). The `robust` (default to `FALSE`) argument enables a robust standardization of data, based on the median and the MAD instead of the mean and the SD.

Usage

```
## Default S3 method:
standardize(
  x,
  robust = FALSE,
  two_sd = FALSE,
  weights = TRUE,
  verbose = TRUE,
  include_response = TRUE,
  ...
)
```

Arguments

x	A statistical model.
robust	Logical, if TRUE, centering is done by subtracting the median from the variables and dividing it by the median absolute deviation (MAD). If FALSE, variables are standardized by subtracting the mean and dividing it by the standard deviation (SD).
two_sd	If TRUE, the variables are scaled by two times the deviation (SD or MAD depending on robust). This method can be useful to obtain model coefficients of continuous parameters comparable to coefficients related to binary predictors, when applied to the predictors (not the outcome) (Gelman, 2008).
weights	If TRUE (default), a weighted-standardization is carried out.
verbose	Toggle warnings and messages on or off.
include_response	If TRUE (default), the response value will also be standardized. If FALSE, only the predictors will be standardized. <ul style="list-style-type: none"> • Note that for GLMs and models with non-linear link functions, the response value will not be standardized, to make re-fitting the model work. • If the model contains an <code>stats::offset()</code>, the offset variable(s) will be standardized only if the response is standardized. If <code>two_sd = TRUE</code>, offsets are standardized by one-sd (similar to the response). • (For mediate models, the <code>include_response</code> refers to the outcome in the y model; m model's response will always be standardized when possible).
...	Arguments passed to or from other methods.

Value

A statistical model fitted on standardized data

Generalized Linear Models

Standardization for generalized linear models (GLM, GLMM, etc) is done only with respect to the predictors (while the outcome remains as-is, unstandardized) - maintaining the interpretability of the coefficients (e.g., in a binomial model: the exponent of the standardized parameter is the OR of a change of 1 SD in the predictor, etc.)

Dealing with Factors

`standardize(model)` or `standardize_parameters(model, method = "refit")` do *not* standardize categorical predictors (i.e. factors) / their dummy-variables, which may be a different behaviour compared to other R packages (such as **lm.beta**) or other software packages (like SPSS). To mimic such behaviours, either use `standardize_parameters(model, method = "basic")` to obtain post-hoc standardized parameters, or standardize the data with `standardize(data, force = TRUE)` *before* fitting the model.

Transformed Variables

When the model's formula contains transformations (e.g. $y \sim \exp(X)$) the transformation effectively takes place after standardization (e.g., $\exp(\text{scale}(X))$). Since some transformations are undefined for none positive values, such as `log()` and `sqrt()`, the relevant variables are shifted (post standardization) by $Z - \min(Z) + 1$ or $Z - \min(Z)$ (respectively).

See Also

Other standardize: [standardize\(\)](#)

Examples

```
model <- lm(Infant.Mortality ~ Education * Fertility, data = swiss)
coef(standardize(model))
```

text_format

Convenient text formatting functionalities

Description

Convenience functions to manipulate and format text.

Usage

```
text_format(
  text,
  sep = ", ",
  last = " and ",
  width = NULL,
  enclose = NULL,
  ...
)
```

```
format_text(
  text,
  sep = ", ",
  last = " and ",
```

```

    width = NULL,
    enclose = NULL,
    ...
)

text_fullstop(text)

text_lastchar(text, n = 1)

text_concatenate(text, sep = ", ", last = " and ", enclose = NULL)

text_paste(text, text2 = NULL, sep = ", ", enclose = NULL, ...)

text_remove(text, pattern = "", ...)

text_wrap(text, width = NULL, ...)

```

Arguments

text, text2	A character string.
sep	Separator.
last	Last separator.
width	Positive integer giving the target column width for wrapping lines in the output. Can be "auto", in which case it will select 90\ default width.
enclose	Character that will be used to wrap elements of text, so these can be, e.g., enclosed with quotes or backticks. If NULL (default), text elements will not be enclosed.
...	Other arguments to be passed to or from other functions.
n	The number of characters to find.
pattern	Character vector. For data_rename(), indicates columns that should be selected for renaming. Can be NULL (in which case all columns are selected). For data_addprefix() or data_addsuffix(), a character string, which will be added as prefix or suffix to the column names.

Value

A character string.

Examples

```

# Add full stop if missing
text_fullstop(c("something", "something else.))

# Find last characters
text_lastchar(c("ABC", "DEF"), n = 2)

# Smart concatenation
text_concatenate(c("First", "Second", "Last"))

```

```

text_concatenate(c("First", "Second", "Last"), last = " or ", enclose = "`")

# Remove parts of string
text_remove(c("one!", "two", "three!"), "!")

# Wrap text
long_text <- paste(rep("abc ", 100), collapse = "")
cat(text_wrap(long_text, width = 50))

# Paste with optional separator
text_paste(c("A", "", "B"), c("42", "42", "42"))

```

to_factor

Convert data to factors

Description

Convert data to factors

Usage

```

to_factor(x, ...)

## S3 method for class 'data.frame'
to_factor(
  x,
  select = NULL,
  exclude = NULL,
  ignore_case = FALSE,
  append = FALSE,
  regex = FALSE,
  verbose = TRUE,
  ...
)

```

Arguments

x	A data frame or vector.
...	Arguments passed to or from other methods.
select	Variables that will be included when performing the required tasks. Can be either <ul style="list-style-type: none"> • a variable specified as a literal variable name (e.g., column_name), • a string with the variable name (e.g., "column_name"), or a character vector of variable names (e.g., c("col1", "col2", "col3")), • a formula with variable names (e.g., ~column_1 + column_2), • a vector of positive integers, giving the positions counting from the left (e.g. 1 or c(1, 3, 5)),

- a vector of negative integers, giving the positions counting from the right (e.g., -1 or -1:-3),
- one of the following select-helpers: starts_with(), ends_with(), contains(), a range using : or regex(""). starts_with(), ends_with(), and contains() accept several patterns, e.g starts_with("Sep", "Petal").
- or a function testing for logical conditions, e.g. is.numeric() (or is.numeric), or any user-defined function that selects the variables for which the function returns TRUE (like: foo <- function(x) mean(x) > 3),
- ranges specified via literal variable names, select-helpers (except regex()) and (user-defined) functions can be negated, i.e. return non-matching elements, when prefixed with a -, e.g. -ends_with(""), -is.numeric or -(Sepal.Width:Petal.Length). **Note:** Negation means that matches are *excluded*, and thus, the exclude argument can be used alternatively. For instance, select=-ends_with("Length") (with -) is equivalent to exclude=ends_with("Length") (no -). In case negation should not work as expected, use the exclude argument instead.

If NULL, selects all columns. Patterns that found no matches are silently ignored, e.g. find_columns(iris, select = c("Species", "Test")) will just return "Species".

exclude	See select, however, column names matched by the pattern from exclude will be excluded instead of selected. If NULL (the default), excludes no columns.
ignore_case	Logical, if TRUE and when one of the select-helpers or a regular expression is used in select, ignores lower/upper case in the search pattern when matching against variable names.
append	Logical or string. If TRUE, recoded or converted variables get new column names and are appended (column bind) to x, thus returning both the original and the recoded variables. The new columns get a suffix, based on the calling function: "_r" for recode functions, "_n" for to_numeric(), "_f" for to_factor(), or "_s" for slide(). If append=FALSE, original variables in x will be overwritten by their recoded versions. If a character value, recoded variables are appended with new column names (using the defined suffix) to the original data frame.
regex	Logical, if TRUE, the search pattern from select will be treated as regular expression. When regex = TRUE, select <i>must</i> be a character string (or a variable containing a character string) and is not allowed to be one of the supported select-helpers or a character vector of length > 1. regex = TRUE is comparable to using one of the two select-helpers, select = contains("") or select = regex(""), however, since the select-helpers may not work when called from inside other functions (see 'Details'), this argument may be used as workaround.
verbose	Toggle warnings.

Details

Convert variables or data into factors. If the data is labelled, value labels will be used as factor levels. The counterpart to convert variables into numeric is to_numeric().

Value

A factor, or a data frame of factors.

Selection of variables - the select argument

For most functions that have a select argument (including this function), the complete input data frame is returned, even when select only selects a range of variables. That is, the function is only applied to those variables that have a match in select, while all other variables remain unchanged. In other words: for this function, select will not omit any non-included variables, so that the returned data frame will include all variables from the input data frame.

Examples

```
str(to_factor(iris))

# use labels as levels
data(efc)
str(efc$c172code)
head(to_factor(efc$c172code))
```

to_numeric	<i>Convert data to numeric</i>
------------	--------------------------------

Description

Convert data to numeric by converting characters to factors and factors to either numeric levels or dummy variables. The "counterpart" to convert variables into factors is to_factor().

Usage

```
to_numeric(x, ...)

## S3 method for class 'data.frame'
to_numeric(
  x,
  select = NULL,
  exclude = NULL,
  dummy_factors = TRUE,
  preserve_levels = FALSE,
  lowest = NULL,
  append = FALSE,
  ignore_case = FALSE,
  regex = FALSE,
  verbose = TRUE,
  ...
)
```

Arguments

x	A data frame, factor or vector.
...	Arguments passed to or from other methods.

select	<p>Variables that will be included when performing the required tasks. Can be either</p> <ul style="list-style-type: none"> • a variable specified as a literal variable name (e.g., <code>column_name</code>), • a string with the variable name (e.g., <code>"column_name"</code>), or a character vector of variable names (e.g., <code>c("col1", "col2", "col3")</code>), • a formula with variable names (e.g., <code>~column_1 + column_2</code>), • a vector of positive integers, giving the positions counting from the left (e.g. <code>1</code> or <code>c(1, 3, 5)</code>), • a vector of negative integers, giving the positions counting from the right (e.g., <code>-1</code> or <code>-1:-3</code>), • one of the following select-helpers: <code>starts_with()</code>, <code>ends_with()</code>, <code>contains()</code>, a range using <code>:</code> or <code>regex("")</code>. <code>starts_with()</code>, <code>ends_with()</code>, and <code>contains()</code> accept several patterns, e.g. <code>starts_with("Sep", "Petal")</code>. • or a function testing for logical conditions, e.g. <code>is.numeric()</code> (or <code>is.numeric</code>), or any user-defined function that selects the variables for which the function returns TRUE (like: <code>foo <- function(x) mean(x) > 3</code>), • ranges specified via literal variable names, select-helpers (except <code>regex()</code>) and (user-defined) functions can be negated, i.e. return non-matching elements, when prefixed with a <code>-</code>, e.g. <code>-ends_with("")</code>, <code>-is.numeric</code> or <code>-(Sepal.Width:Petal.Length)</code>. Note: Negation means that matches are <i>excluded</i>, and thus, the <code>exclude</code> argument can be used alternatively. For instance, <code>select=-ends_with("Length")</code> (with <code>-</code>) is equivalent to <code>exclude=ends_with("Length")</code> (no <code>-</code>). In case negation should not work as expected, use the <code>exclude</code> argument instead. <p>If NULL, selects all columns. Patterns that found no matches are silently ignored, e.g. <code>find_columns(iris, select = c("Species", "Test"))</code> will just return <code>"Species"</code>.</p>
exclude	See <code>select</code> , however, column names matched by the pattern from <code>exclude</code> will be excluded instead of selected. If NULL (the default), excludes no columns.
dummy_factors	Transform factors to dummy factors (all factor levels as different columns filled with a binary 0-1 value).
preserve_levels	Logical, only applies if <code>x</code> is a factor. If TRUE, and <code>x</code> has numeric factor levels, these will be converted into the related numeric values. If this is not possible, the converted numeric values will start from 1 to number of levels.
lowest	Numeric, indicating the lowest (minimum) value when converting factors or character vectors to numeric values.
append	Logical or string. If TRUE, recoded or converted variables get new column names and are appended (column bind) to <code>x</code> , thus returning both the original and the recoded variables. The new columns get a suffix, based on the calling function: <code>"_r"</code> for recode functions, <code>"_n"</code> for <code>to_numeric()</code> , <code>"_f"</code> for <code>to_factor()</code> , or <code>"_s"</code> for <code>slide()</code> . If <code>append=FALSE</code> , original variables in <code>x</code> will be overwritten by their recoded versions. If a character value, recoded variables are appended with new column names (using the defined suffix) to the original data frame.

ignore_case	Logical, if TRUE and when one of the select-helpers or a regular expression is used in select, ignores lower/upper case in the search pattern when matching against variable names.
regex	Logical, if TRUE, the search pattern from select will be treated as regular expression. When regex = TRUE, select <i>must</i> be a character string (or a variable containing a character string) and is not allowed to be one of the supported select-helpers or a character vector of length > 1. regex = TRUE is comparable to using one of the two select-helpers, select = contains("") or select = regex(""), however, since the select-helpers may not work when called from inside other functions (see 'Details'), this argument may be used as workaround.
verbose	Toggle warnings.

Value

A data frame of numeric variables.

Selection of variables - select argument

For most functions that have a select argument the complete input data frame is returned, even when select only selects a range of variables. However, for to_numeric(), factors might be converted into dummies, thus, the number of variables of the returned data frame no longer match the input data frame. Hence, when select is used, *only* those variables (or their dummies) specified in select will be returned. Use append=TRUE to also include the original variables in the returned data frame.

Examples

```
to_numeric(head(ToothGrowth))
to_numeric(head(ToothGrowth), dummy_factors = FALSE)

# factors
x <- as.factor(mtcars$gear)
to_numeric(x, dummy_factors = FALSE)
to_numeric(x, dummy_factors = FALSE, preserve_levels = TRUE)
```

visualisation_recipe *Prepare objects for visualisation*

Description

This function prepares objects for visualisation by returning a list of layers with data and geoms that can be easily plotted using for instance ggplot2.

If the see package is installed, the call to visualization_recipe() can be replaced by plot(), which will internally call the former and then plot it using ggplot. The resulting plot can be customized ad-hoc (by adding ggplot's geoms, theme or specifications), or via some of the arguments of visualisation_recipe() that control the aesthetic parameters.

See the specific documentation page for your object's class:

- modelbased: https://easystats.github.io/modelbased/reference/visualisation_recipe_estimate_predicted.html
- correlation: https://easystats.github.io/correlation/reference/visualisation_recipe_easycormatrix.html

Usage

```
visualisation_recipe(x, ...)
```

Arguments

x An easystats object.
 ... Other arguments passed to other functions.

weighted_mean	<i>Weighted Mean, Median, SD, and MAD</i>
---------------	---

Description

Weighted Mean, Median, SD, and MAD

Usage

```
weighted_mean(x, weights = NULL, verbose = TRUE, ...)
```

```
weighted_median(x, weights = NULL, verbose = TRUE, ...)
```

```
weighted_sd(x, weights = NULL, verbose = TRUE, ...)
```

```
weighted_mad(x, weights = NULL, constant = 1.4826, verbose = TRUE, ...)
```

Arguments

x an object containing the values whose weighted mean is to be computed.
 weights A numerical vector of weights the same length as x giving the weights to use for elements of x.
 verbose Show warning when weights are negative?
 If weights = NULL, x is passed to the non-weighted function.
 ... arguments to be passed to or from methods.
 constant scale factor.

Examples

```
## GPA from Siegel 1994
x <- c(3.7, 3.3, 3.5, 2.8)
wt <- c(5, 5, 4, 1) / 15

weighted_mean(x, wt)
weighted_median(x, wt)

weighted_sd(x, wt)
weighted_mad(x, wt)
```

 winsorize

Winsorize data

Description

Winsorize data

Usage

```
winsorize(data, ...)

## S3 method for class 'numeric'
winsorize(
  data,
  threshold = 0.2,
  method = "percentile",
  robust = FALSE,
  verbose = TRUE,
  ...
)
```

Arguments

data	data frame or vector.
...	Currently not used.
threshold	The amount of winsorization, depends on the value of method: <ul style="list-style-type: none"> • For method = "percentile": the amount to winsorize from <i>each</i> tail. The value of threshold must be between 0 and 0.5 and of length 1. • For method = "zscore": the number of <i>SD/MAD</i>-deviations from the <i>mean/median</i> (see robust). The value of threshold must be greater than 0 and of length 1. • For method = "raw": a vector of length 2 with the lower and upper bound for winsorization.
method	One of "percentile" (default), "zscore", or "raw".

robust	Logical, if TRUE, winsorizing through the "zscore" method is done via the median and the median absolute deviation (MAD); if FALSE, via the mean and the standard deviation.
verbose	Not used anymore since datawizard 0.6.6.

Details

Winsorizing or winsorization is the transformation of statistics by limiting extreme values in the statistical data to reduce the effect of possibly spurious outliers. The distribution of many statistics can be heavily influenced by outliers. A typical strategy is to set all outliers (values beyond a certain threshold) to a specified percentile of the data; for example, a 90% winsorization would see all data below the 5th percentile set to the 5th percentile, and data above the 95th percentile set to the 95th percentile. Winsorized estimators are usually more robust to outliers than their more standard forms.

Value

A data frame with winsorized columns or a winsorized vector.

See Also

- Functions to rename stuff: [data_rename\(\)](#), [data_rename_rows\(\)](#), [data_addprefix\(\)](#), [data_addsuffix\(\)](#)
- Functions to reorder or remove columns: [data_reorder\(\)](#), [data_relocate\(\)](#), [data_remove\(\)](#)
- Functions to reshape, pivot or rotate data frames: [data_to_long\(\)](#), [data_to_wide\(\)](#), [data_rotate\(\)](#)
- Functions to recode data: [rescale\(\)](#), [reverse\(\)](#), [categorize\(\)](#), [recode_values\(\)](#), [slide\(\)](#)
- Functions to standardize, normalize, rank-transform: [center\(\)](#), [standardize\(\)](#), [normalize\(\)](#), [ranktransform\(\)](#), [winsorize\(\)](#)
- Split and merge data frames: [data_partition\(\)](#), [data_merge\(\)](#)
- Functions to find or select columns: [data_select\(\)](#), [data_find\(\)](#)
- Functions to filter rows: [data_match\(\)](#), [data_filter\(\)](#)

Examples

```
hist(iris$Sepal.Length, main = "Original data")

hist(winsorize(iris$Sepal.Length, threshold = 0.2),
     xlim = c(4, 8), main = "Percentile Winsorization"
     )

hist(winsorize(iris$Sepal.Length, threshold = 1.5, method = "zscore"),
     xlim = c(4, 8), main = "Mean (+/- SD) Winsorization"
     )

hist(winsorize(iris$Sepal.Length, threshold = 1.5, method = "zscore", robust = TRUE),
     xlim = c(4, 8), main = "Median (+/- MAD) Winsorization"
     )

hist(winsorize(iris$Sepal.Length, threshold = c(5, 7.5), method = "raw"),
```

```
    xlim = c(4, 8), main = "Raw Thresholds"  
  )
```

```
# Also works on a data frame:  
winsorize(iris, threshold = 0.2)
```

Index

- * **datawizard-transformers**
 - makepredictcall.dw_transformer, 77
- * **data**
 - efc, 73
 - nhanes_sample, 79
- * **duplicates**
 - data_duplicated, 31
- * **standardize**
 - standardize, 107
 - standardize.default, 112
- * **transform utilities**
 - normalize, 79
 - ranktransform, 82
 - rescale, 93
 - reverse, 98
 - standardize, 107
- add_labs, 3
- adjust, 6
- bayestestR::map_estimate(), 73
- categorize, 9
- categorize(), 12, 27, 39, 41, 44, 51, 53, 59, 61, 76, 88, 106, 123
- center, 13
- center(), 12, 27, 39, 41, 44, 51, 53, 59, 61, 68, 76, 77, 89, 106, 111, 123
- centre (center), 13
- change_code (recode_values), 85
- change_scale (rescale), 93
- coef_var, 17
- coerce_to_numeric, 18
- colnames_to_row (row_to_colnames), 101
- column_as_rownames (rownames_as_column), 100
- convert_na_to, 19
- convert_to_na, 22
- data_addprefix, 24
- data_addprefix(), 12, 26, 39, 41, 44, 51, 53, 59, 61, 76, 88, 106, 123
- data_addsuffix (data_addprefix), 24
- data_addsuffix(), 12, 26, 39, 41, 44, 51, 53, 59, 61, 76, 88, 106, 123
- data_adjust (adjust), 6
- data_arrange, 27
- data_codebook, 28
- data_duplicated, 31
- data_duplicated(), 64
- data_extract, 33
- data_filter (data_match), 37
- data_filter(), 12, 27, 39, 41, 44, 51, 53, 59, 61, 76, 89, 106, 123
- data_find (find_columns), 73
- data_find(), 12, 27, 39, 41, 44, 51, 53, 59, 61, 76, 89, 106, 123
- data_group, 35
- data_join (data_merge), 40
- data_match, 37
- data_match(), 12, 27, 39, 41, 44, 51, 53, 59, 61, 76, 89, 106, 123
- data_merge, 40
- data_merge(), 12, 27, 39, 41, 44, 51, 53, 59, 61, 76, 89, 106, 123
- data_partition, 43
- data_partition(), 12, 27, 39, 41, 44, 51, 53, 59, 61, 76, 89, 106, 123
- data_peek, 45
- data_read, 47
- data_relocate, 49
- data_relocate(), 12, 26, 39, 41, 44, 51, 53, 59, 61, 76, 88, 106, 123
- data_remove (data_relocate), 49
- data_remove(), 12, 26, 39, 41, 44, 51, 53, 59, 61, 76, 88, 106, 123
- data_rename (data_addprefix), 24
- data_rename(), 12, 26, 39, 41, 44, 51, 53, 59, 61, 76, 88, 106, 123

- data_rename_rows (data_addprefix), 24
- data_rename_rows(), 12, 26, 39, 41, 44, 51, 53, 59, 61, 76, 88, 106, 123
- data_reorder (data_relocate), 49
- data_reorder(), 12, 26, 39, 41, 44, 51, 53, 59, 61, 76, 88, 106, 123
- data_restoretype, 52
- data_rotate, 53
- data_rotate(), 12, 27, 39, 41, 44, 51, 53, 59, 61, 76, 88, 106, 123
- data_select (find_columns), 73
- data_select(), 12, 27, 39, 41, 44, 51, 53, 59, 61, 76, 89, 106, 123
- data_tabulate, 54
- data_to_long, 56
- data_to_long(), 12, 27, 39, 41, 44, 51, 53, 59, 61, 76, 88, 106, 123
- data_to_wide, 60
- data_to_wide(), 12, 27, 39, 41, 44, 51, 53, 59, 61, 76, 88, 106, 123
- data_transpose (data_rotate), 53
- data_ungroup (data_group), 35
- data_unique, 63
- data_unique(), 32
- data_write (data_read), 47
- degrouper (demean), 65
- demean, 65
- demean(), 16
- describe_distribution, 69
- detrend (demean), 65
- distribution_coef_var (coef_var), 17
- distribution_cv (coef_var), 17
- distribution_mode, 72
- dplyr::distinct(), 31
- uplicated(), 31
- efc, 73
- empty_columns (remove_empty), 90
- empty_rows (remove_empty), 90
- find_columns, 73
- format_text (text_format), 114
- get_columns (find_columns), 73
- ifelse(), 84
- kurtosis (skewness), 102
- makepredictcall.dw_transformer, 77
- makepredictcall.dw_transformer(), 16, 81, 95, 111
- mean_sd, 78
- median_mad (mean_sd), 78
- nhanes_sample, 79
- normalize, 79, 84, 95, 100, 111
- normalize(), 12, 27, 39, 41, 44, 51, 53, 59, 61, 76, 77, 89, 106, 107, 123
- print.parameters_kurtosis (skewness), 102
- print.parameters_skewness (skewness), 102
- print.html.data_codebook (data_codebook), 28
- rank(), 82
- ranktransform, 81, 82, 95, 100, 111
- ranktransform(), 12, 27, 39, 41, 44, 51, 53, 59, 61, 76, 89, 106, 123
- recode_into, 84
- recode_values, 85
- recode_values(), 12, 27, 39, 41, 44, 51, 53, 59, 61, 76, 88, 106, 123
- remove_empty, 90
- remove_empty_columns (remove_empty), 90
- remove_empty_rows (remove_empty), 90
- replace_nan_inf, 92
- rescale, 81, 84, 93, 100, 111
- rescale(), 12, 27, 39, 41, 44, 51, 53, 59, 61, 76, 77, 79, 88, 106, 123
- rescale_weights, 95
- reshape_ci, 97
- reshape_longer (data_to_long), 56
- reshape_wider (data_to_wide), 60
- reverse, 81, 84, 95, 98, 111
- reverse(), 12, 27, 39, 41, 44, 51, 53, 59, 61, 76, 88, 106, 123
- reverse_scale (reverse), 98
- row_to_colnames, 101
- rownames_as_column, 100
- skewness, 102
- slide, 104
- slide(), 12, 27, 39, 41, 44, 51, 53, 59, 61, 76, 88, 106, 123
- smoothness, 106
- standardise (standardize), 107

standardize, [81](#), [84](#), [95](#), [100](#), [107](#), [114](#)
standardize(), [12](#), [16](#), [27](#), [39](#), [41](#), [44](#), [51](#), [53](#),
[59](#), [61](#), [76](#), [77](#), [89](#), [106](#), [112](#), [123](#)
standardize.default, [111](#), [112](#)
standardize.default(), [107](#)
standardize_models
 (standardize.default), [112](#)
stats::IQR(), [70](#)
stats::mad(), [17](#)
stats::makepredictcall(), [77](#)
stats::offset(), [113](#)
summary.parameters_kurtosis (skewness),
[102](#)
summary.parameters_skewness (skewness),
[102](#)

text_concatenate (text_format), [114](#)
text_format, [114](#)
text_fullstop (text_format), [114](#)
text_lastchar (text_format), [114](#)
text_paste (text_format), [114](#)
text_remove (text_format), [114](#)
text_wrap (text_format), [114](#)
to_factor, [116](#)
to_numeric, [118](#)

unnormalize (normalize), [79](#)
unstandardise (standardize), [107](#)
unstandardize (standardize), [107](#)

visualisation_recipe, [120](#)

weighted_mad (weighted_mean), [121](#)
weighted_mean, [121](#)
weighted_median (weighted_mean), [121](#)
weighted_sd (weighted_mean), [121](#)
winsorize, [122](#)
winsorize(), [12](#), [27](#), [39](#), [41](#), [44](#), [51](#), [53](#), [59](#),
[61](#), [76](#), [89](#), [106](#), [123](#)