

# Package ‘nmixgof’

February 12, 2025

**Title** Goodness of Fit Checks for Binomial N-Mixture Models

**Version** 0.1.1

**Description** Provides residuals and overdispersion metrics to assess the fit of N-mixture models obtained using the package 'unmarked'.  
Details on the methods are given in Knape et al. (2017) <[doi:10.1101/194340](https://doi.org/10.1101/194340)>.

**Depends** R (>= 3.3.0)

**License** GPL-3

**Encoding** UTF-8

**LazyData** true

**LinkingTo** Rcpp

**Imports** Rcpp, unmarked

**RoxygenNote** 7.3.2

**URL** <https://github.com/jknape/nmixgof>

**BugReports** <https://github.com/jknape/nmixgof/issues>

**NeedsCompilation** yes

**Author** Jonas Knape [aut, cre] (<<https://orcid.org/0000-0002-8012-5131>>)

**Maintainer** Jonas Knape <[jonas.knape@slu.se](mailto:jonas.knape@slu.se)>

**Repository** CRAN

**Date/Publication** 2025-02-12 17:50:05 UTC

## Contents

chat . . . . .	2
nmixgof . . . . .	2
residcov . . . . .	3
residfit . . . . .	3
residqq . . . . .	4
rqresiduals . . . . .	5
shoveler . . . . .	6
<b>Index</b>	<b>7</b>

---

chat	<i>Overdispersion metrics for binomial N-mixture models.</i>
------	--

---

**Description**

Computes various types of overdispersion metrics, based on Pearson residuals, for binomial N-mixture models.

**Usage**

```
chat(umFit, type = "marginal")
```

**Arguments**

umFit	An object of class <code>unmarkedFit</code> from a model fitted using <code>pcount</code> .
type	The type of metric to compute, one of 'marginal', 'site-sum' or 'observation'.

**Value**

An estimate of overdispersion relative to the fitted model.

**Examples**

```
library(unmarked)
data(mallard)
fm.mallard <- pcount(~ 1 ~ 1, unmarkedFramePCount(y = mallard.y), K=100)
chat(fm.mallard, "m")
chat(fm.mallard, "s")
chat(fm.mallard, "o")
```

---

nmixgof	<i>Goodness of fit checks for binomial N-mixture models</i>
---------	---

---

**Description**

The package contains methods to compute overdispersion metrics, randomized quantile residuals, and graphical diagnostics of model fit for binomial N-mixture models fitted using the `unmarked` package. Details about the checks are given in Knape et al. (2018).

**Author(s)**

**Maintainer:** Jonas Knape <jonas.knape@slu.se> ([ORCID](#))

**References**

Knape et al. 2018. Sensitivity of binomial N-mixture models to overdispersion: the importance of assessing model fit. *Methods in Ecology and Evolution*, 9:2102-2114. doi:10.1111/2041210X.13062

**See Also**

Useful links:

- <https://github.com/jknape/nmixgof>
- Report bugs at <https://github.com/jknape/nmixgof/issues>

---

residcov *Plot residuals against covariates*

---

**Description**

A convenience function to plot rq residuals against all untransformed numeric covariates. Site-sum randomized quantile residuals are used for site covariates while marginal residuals are used for observation covariates. The same random residual draws are reused for different covariates.

**Usage**

```
residcov(umFit, ...)
```

**Arguments**

umFit	An object of class <code>unmarkedFit</code> from a model fitted using <code>pcount</code> .
...	Plot arguments.

**Examples**

```
library(unmarked)
umf = unmarkedFramePCount(y = shoveler$y, obsCovs = shoveler$obs, siteCovs = shoveler$site)
fmP = pcount(~scale(date) + scale(reedcover) ~ scale(log(water)) + scale(latitude),
             data = umf, K = 80)
residcov(fmP)
```

---

residfit *Plot residuals against fitted values*

---

**Description**

Plots randomized-quantile residuals for binomial N-mixture models against fitted values.

**Usage**

```
residfit(umFit, type = "marginal", ...)
```

**Arguments**

umFit	An object from a model fitted using <a href="#">pcount</a> .
type	The type of randomized quantile residual to plot. One of 'marginal', 'site-sum' or 'observation'.
...	Plot arguments.

**Examples**

```
library(unmarked)
umf = unmarkedFramePCount(y = shoveler$y, obsCovs = shoveler$obs, siteCovs = shoveler$site)
fmP = pcount(~scale(date) + scale(reedcover) ~ scale(log(water)) + scale(latitude),
             data = umf, K = 80)
residfit(fmP, "marginal")
residfit(fmP, "site-sum")
residfit(fmP, "observation")
```

---

residqq	<i>Qq plot of randomized quantile residuals against standard normal quantiles</i>
---------	---

---

**Description**

Qq plot of randomized quantile residuals against standard normal quantiles

**Usage**

```
residqq(
  umFit,
  type = "site-sum",
  main = "Residual qq plot",
  plotLine = TRUE,
  ...
)
```

**Arguments**

umFit	An object of class <a href="#">unmarkedFit</a> from a model fitted using <a href="#">pcount</a> .
type	The type of randomized quantile residual to plot. One of 'site-sum' or 'observation'.
main	Plot label.
plotLine	If true, the identity line is added to the plot.
...	Further arguments passed to <a href="#">qqnorm</a> .

**Value**

A list with x and y coordinates of the qq plot, see [qqnorm](#).

**Examples**

```
library(unmarked)
umf = unmarkedFramePCount(y = shoveler$y, obsCovs = shoveler$obs, siteCovs = shoveler$site)
fmP = pcount(~scale(date) + scale(reedcover) ~ scale(log(water)) + scale(latitude),
             data = umf, K = 80)
residqq(fmP, "site-sum")
residqq(fmP, "observation")
```

---

rqresiduals

*Randomized quantile residuals for binomial N-mixture models.*


---

**Description**

Computes three types of randomized quantile residuals for binomial N-mixture models.

**Usage**

```
rqresiduals(umFit, type = "marginal")
```

**Arguments**

umFit	An object of class <code>unmarkedFit</code> from a model fitted using <code>pcount</code> .
type	The type of rq residuals to compute, one of 'marginal', 'site-sum' or 'observation'.

**Value**

A matrix (if type is 'marginal' or 'site-sum') or vector (for ) con.

**Examples**

```
library(unmarked)
umf = unmarkedFramePCount(y = shoveler$y, obsCovs = shoveler$obs, siteCovs = shoveler$site)
fmP = pcount(~scale(date) + scale(reedcover) ~ scale(log(water)) + scale(latitude),
             data = umf, K = 80)
qqnorm(rqresiduals(fmP, "s"))
qqnorm(rqresiduals(fmP, "o"))
par(mfcol = c(3,4))
invisible(apply(rqresiduals(fmP, "m"), 2, qqnorm))
```

---

shoveler

*Northern shoveler data*

---

### Description

Repeated count data of Northern shoveler with covariates, formatted for use with the [unmarked](#) package.

### Usage

```
shoveler
```

### Format

A list with three elements

**y** A matrix with Northern shoveler counts

**site** A data frame with site specific covariates

**obs** A list containing observation specific covariates

### References

Knape et al. (2018) *Methods in Ecology and Evolution*, 9:2102-2114. [doi:10.1111/2041210X.13062](https://doi.org/10.1111/2041210X.13062)

### Examples

```
library(unmarked)
umf = unmarkedFramePCount(y = shoveler$y, obsCovs = shoveler$obs, siteCovs = shoveler$site)
```

# Index

## \* datasets

shoveler, 6

chat, 2

nmixgof, 2

nmixgof-package (nmixgof), 2

pcount, 2–5

qqnorm, 4

residcov, 3

residfit, 3

residqq, 4

rqresiduals, 5

shoveler, 6

unmarked, 2, 6

unmarkedFit, 2–5